

List of Lights, Buoys and Fog Signals – Atlantic Coast

No. ----- Intl No.	Name ----- RACON	Location ----- Latitude N. Longitude W.	Light Characteristics	Focal Height Above Water (m)	Nominal Range (NM)	Description ----- Height of Structure Above Ground Level (m)	Remarks ----- Audible Signals ----- AIS
BAY OF FUNDY, N.B. - EAST							
145	Saint John Harbour light and whistle buoy J Racon N (-.) X Band	S. of Partridge Island. 45 12 55.3 066 02 36.9	Mo(A) W 6s	Red-white, pillar, marked "J".	Year round. Audible signal: Whistle
145.3 H4080	Black Point	S. tip of point. 45 12 59.8 066 00 27.9	Iso R 4s	11.1	14	Red and white cylindrical tower. 8.2	Year round.
145.4	Black Point light and bell spoil ground buoy JB	SW. of point. 45 12 27.3 066 01 00.9	Fl Y 4s	Yellow, pillar, marked "JB".	Year round. Audible signal: Bell
146 H4078	Cape Spencer	Pitch of cape. 45 11 42.5 065 54 35.5	Fl W 11s	61.6	14	Red and white cylindrical tower. 8.6	Year round. Operates 24 h. Flash 1 s; eclipse 10 s.
147 H4077	Black River	On SW. point entrance to river. 45 15 27.4 065 48 39.6	Fl W 5s	13.9	7	Pipe swing pole.	Year round. Flash 1 s; eclipse 4 s.
147.1 H4079.5	LNG West Initial (060) Sector	45 12 34.6 065 59 22.2	F R W G	23.3	On building. Private aid. Year round. Operates 24 h. R 057°30'-058°39'; AI RW 058°39'-059°39'; W 059°39'-060°21'; AI WG 060°21'-061°21'; G 061°21'-062°30'. For sole use of LNG vessels transmitting to and from Canaport facility (Occasional).
147.12 H4079.5	LNG East Secondary (310) Sector	45 12 34.6 065 59 22.2	F R W G	23.3	On building. Private aid. Year round. Operates 24 h. R 307°30'-308°39'; AI RW 308°39'-309°39'; W 309°-310°21'; AI WG 310°21'-311°21'; G 311°21'-312°30'. For sole use of vessels transmitting to and from Canaport facility (Occasional).
147.13 H4078.7	LNG East Initial (000) Sector	45 12 51.9 065 56 51.2	F R W G	18.3	On building. Private aid. Year round. Operates 24 h. R 358°36'-359°06'; AI RW 359°06'-359°48'; W 359°48'-000°12'; AI GW 000°12'-000°54'; G 000°54'-002°06'. For sole use of vessels transmitting to and from Canaport facility (Occasional).

List of Lights, Buoys and Fog Signals – Atlantic Coast

No. ----- Intl No.	Name ----- RACON	Location ----- Latitude N. Longitude W.	Light Characteristics	Focal Height Above Water (m)	Nominal Range (NM)	Description ----- Height of Structure Above Ground Level (m)	Remarks ----- Audible Signals ----- AIS	
BAY OF FUNDY, N.B. - EAST								
147.14 H4078.5	LNG West Secondary (088) Sector	45 12 16.4 065 55 34.6	F R W G	23.4	On building. Private aid. Year round. Operates 24 h. R 085°54'-087°06'; AI RW 087°06'-087°48'; W 087°48'-088°12'; AI WG 088°12'-088°54'; G 088°54'-089°24'. For sole use of vessels transmitting to and from Canaport facility (Occasional).	
147.15	LNG West Turn Point Sector Light	45 12 16.4 065 55 34.6	F W	22.8	13	On building. Private aid. Year round. Operates 24 h. FI W 81°45'-82°45'; F W 82°45'-83°15'; FI W 83°15'-84°15'.	
147.16	LNG East Turn Point Sector Light	45 12 16.4 065 55 34.6	F W	22.8	10	On building. Private aid. Year round. Operates 24 h. FI W 23°30'-25°30'; F W 25°30'-26°30'; FI W 26°30'-28°30'.	
147.17 H4079.35	LNG MD1 Jetty Light	45 12 21.0 065 59 00.4	FI Y	4s	7.3	5	Cylindrical mast. Private aid. Year round.	
147.171 H4079.3	LNG BD1 Jetty Light	45 12 19.2 065 58 53.2	FI G	4s	5	Cylindrical mast. Private aid. Year round.	
147.173 H4079.25	LNG BD4 Jetty Light	45 12 18.8 065 58 48.2	FI G	4s	7.7	5	Cylindrical mast. Private aid. Year round.	
147.174 H4079.2	LNG MD6 Jetty Light	45 12 19.3 065 58 41.4	FI Y	4s	7.7	5	Cylindrical mast. Private aid. Year round.	
147.21	LNG Cautionary light buoy	45 12 23.8 065 58 19.3	FI Y	4s	Yellow, can. Private aid. Year round. Operates 24 h.	
147.22 H4078.6	LNG Black Rock light	45 12 19.6 065 56 58.2	FI Y	4s	4.8	3	On rock. Private aid. Year round. Operates 24 h.	
148	The Sisters South Cardinal light and bell buoy KB	On S. side of rocks. 45 14 30.3 065 46 55.8	Q(6) + LFI	W	15s	Yellow-black, pillar, marked "KB". Year round. Audible signal: Bell
149	Quaco Ledge North Cardinal light and bell buoy KW	NW. of ledge. 45 14 42.3 065 22 09.8	Q	W	1s	Black-yellow, pillar, marked "KW". Year round. Audible signal: Bell
150 H4076	West Quaco	On Quaco Head. 45 19 25.3 065 32 08.8	FI W	10s	26.0	21	White rectangular tower with red top. 11.7	Year round. Operates 24 h. Flash 0.3 s; eclipse 9.7 s. Fog Horn Blast 3 s; sil. 27 s.
151	Quaco light and bell buoy K15	SE. of Quaco Head Reef. 45 19 16.3 065 31 15.8	FI G	4s	Green, pillar, marked "K15". Year round. Audible signal: Bell	

List of Lights, Buoys and Fog Signals – Atlantic Coast

No. ----- Intl No.	Name ----- RACON	Location ----- Latitude N. Longitude W.	Light Characteristics	Focal Height Above Water (m)	Nominal Range (NM)	Description ----- Height of Structure Above Ground Level (m)	Remarks ----- Audible Signals ----- AIS
--------------------------	------------------------	--	--------------------------	--	--------------------------	--	---

BAY OF FUNDY, N.B. - EAST

152 H4074	St. Martins	On outer end of E. breakwater pier. 45 21 18.0 065 31 55.0	LFl R 6s	7.2	4	Triangular skeleton tower. 5.9	Year round. Flash 2 s; eclipse 4 s.
155 H4064	Alma	On outer end of public wharf. 45 36 00.0 064 56 37.0	Iso R 4s	4	Cylindrical mast, red and white triangular daymark. 6.0	Year round.
155.5	Alma light and bell buoy KX	45 35 32.3 064 55 59.8	Mo(A) W 6s	Red-white, pillar, marked "KX".	Year round. (Winter spar.) Audible signal: Bell
156	Cape Enrage light and bell buoy K19	Off reef extending S. from cape. 45 35 08.8 064 47 16.3	Fl G 4s	Green, pillar, marked "K19".	Year round. Audible signal: Bell
157 H4060	Cape Enragé	Pitch of cape. 45 35 38.1 064 46 47.7	Fl G 6s	40.7	10	White square tower with red upper portion. 9.2	Private aid. Year round. Operates 24 h. Flash 1 s; eclipse 5 s. Fog Horn Blast 2 s; sil. 3 s; blast 2 s; sil. 3 s; blast 2 s; sil. 48 s.