

List of Lights, Buoys and Fog Signals – Atlantic Coast

No. ----- Intl No.	Name ----- RACON	Location ----- Latitude N. Longitude W.	Light Characteristics	Focal Height Above Water (m)	Nominal Range (NM)	Description ----- Height of Structure Above Ground Level (m)	Remarks ----- Audible Signals ----- AIS
--------------------------	------------------------	--	--------------------------	--	--------------------------	--	---

BAY OF FUNDY, N.S.

163 H4032	Apple River	On Cape Capstan, N. entrance. 45 28 24.0 064 51 22.9	LFI W 12s	20.8	9	White square tower. 11.2	Year round. Flash 2 s; eclipse 10 s.
164 H3928	Île Haute	On highest point. 45 15 03.4 065 00 19.8	FI W 4s	112.1	7	Square skeleton tower. 13.0	Year round. Visibility of light may be obscured when the navigator is less than 2.5 nautical miles from light.
165	Advocate Harbour light and bell buoy MM	At entrance to harbour. 45 19 10.3 064 48 00.8	Mo(A) W 6s	Red-white, pillar, marked "MM".	Year round. Audible signal: Bell
166 H3934	Advocate Harbour	On S. side of entrance. 45 19 07.1 064 46 59.9	FI R 4s	5	Square skeleton tower, red and white rectangular daymark.	Year round. Flash 1 s; eclipse 3 s.
167 H3938	Cape d'Or	On extreme point. 45 17 27.0 064 46 27.5	LFI W 6s	20.3	8	White square tower with red top, connected to white building. 10.7	Year round. Operates 24 h. Flash 2 s; eclipse 4 s.

Minas Basin

171 H3950	Cape Sharp	On S. extremity of cape. 45 21 52.2 064 23 31.5	Oc W 10s	17.4	11	White square tower with red upper portion. 11.7	Year round. Operates 24 h. Flash 7 s; eclipse 3 s. Fog Horn Blast 4 s; sil. 56 s. Mariners requiring the operation of the fog signal will have to select VHF channel 65 and key their microphones five (5) times within 10 seconds. The fog signal will be in operation for 15 minutes. The fog signal can be activated within a 1 NM distance. The fog signal can be activated for another 15 minutes by repeating the above procedure.
172 H3952	Parrsboro	At entrance to harbour. 45 23 12.8 064 18 59.5	LFI G 6s	8.4	7	White square tower with red top. 8.5	Year round. Flash 2 s; eclipse 4 s. Fog Horn Blast 3 s; sil. 27 s.
173 H3954	Parrsboro Wharf	SE. corner of wharf. 45 23 24.2 064 19 06.6	FI R 4s	5.1	3	Pipe swing pole. 3.7	Year round.
189.5 H3957	Delhaven Shore Light	45 12 04.5 064 22 42.2	FI R 4s	4.8	4	Pipe swing pole. 4.8	Seasonal. Radar reflector.
190	Delhaven Entrance	45 12 02.8 064 22 40.4	FI R 4s	4.9	4	Pipe swing pole. 4.9	Year round. Radar reflector.

List of Lights, Buoys and Fog Signals – Atlantic Coast

No. ----- Intl No.	Name ----- RACON	Location ----- Latitude N. Longitude W.	Light Characteristics	Focal Height Above Water (m)	Nominal Range (NM)	Description ----- Height of Structure Above Ground Level (m)	Remarks ----- Audible Signals ----- AIS
BAY OF FUNDY, N.S.							
191 H3956	Minas Basin	On outer SW. corner of wharf at Delhaven. 45 12 07.6 064 22 48.5	F R	7.3	5	Pipe swing pole, red and white triangular daymark. 5.2	Year round. Radar reflector.
192 H3942	Halls Harbour	On end of wharf. 45 12 06.6 064 37 11.8	Fl R 4s	5.8	7	Cylindrical mast, red and white triangular daymark. 5.6	Year round.
193 H3932	Black Rock	S. shore Minas channel. 45 10 13.2 064 45 42.6	Fl(2) W 12s	15.9	12	White cylindrical tower with red horizontal band. 10.4	Year round. Flash 1 s; eclipse 2 s; flash 1 s; eclipse 8 s.
194	Harbourville	Near outer end of W. pier. 45 09 09.3 064 48 42.2	Fl R 4s	9.8	5	Square skeleton tower, red and white rectangular daymark, red triangle in centre. 6.6	Year round.
195 H3926	Margaretsville	On extremity of point, S. of breakwater. 45 03 00.3 065 03 57.8	Oc(2) W 20s	11.2	10	Square tower, white and black horizontal bands. 9.7	Year round. Flash 4 s; eclipse 3 s; flash 10 s; eclipse 3 s. Visible 095°-236°.
197.3 H3920	Port Lorne breakwater Light	S. shore. 44 56 57.7 065 15 55.7	Fl R 4s	3.0	2	Pipe swing pole, red triangular daymark.	Year round. Flash 1 s; eclipse 3 s.
198 H3918	Hampton Breakwater	E. of W. breakwater at Chute Cove. 44 54 24.9 065 21 05.6	Fl R 4s	18.9	2	White tower. 9.8	Year round.
199 H3916	Parkers Cove	On end of E. breakwater. 44 48 51.1 065 32 18.1	LFl G 12s	8.0	2	Cylindrical mast. 6.3	Year round. Flash 2 s; eclipse 10 s.
199.5 H3914	Delap Cove Wharf	E. of Digby Gut. 44 46 11.8 065 38 11.7	Fl W 4s	6.0	3	Pipe swing pole. 6.8	Seasonal.
201 H3890	Prim Point	Digby Gut, W. point of entrance to Annapolis Basin. 44 41 28.0 065 47 10.8	Iso W 6s	24.8	13	White rectangular tower with red vertical stripes. 13.9	Year round. Operates 24 h.
202 H3892	Digby Gut	E. side of entrance to Digby Gut. 44 41 17.4 065 45 35.1	LFl G 6s	20.0	Square skeleton tower, green and white rectangular daymark.	Year round. Flash 2 s; eclipse 4 s.
203.5	Battery Point Wharf Light	44 40 29.3 065 45 12.4	Fl G 4s	17	Square skeleton tower, green and white rectangular daymark.	Year round. Flash 1 s; eclipse 3 s.
204	<i>Bear Island light buoy V1</i>	<i>E. of Fannan Ledge. 44 38 57.9 065 44 48.8</i>	<i>Fl G 4s</i>	<i>.....</i>	<i>.....</i>	<i>Green, spar, marked "V1".</i>	<i>Year round.</i>

List of Lights, Buoys and Fog Signals – Atlantic Coast

No. ----- Intl No.	Name ----- RACON	Location ----- Latitude N. Longitude W.	Light Characteristics	Focal Height Above Water (m)	Nominal Range (NM)	Description ----- Height of Structure Above Ground Level (m)	Remarks ----- Audible Signals ----- AIS
BAY OF FUNDY, N.S.							
205	<i>The Raquette light buoy V2</i>	44 37 55.4 065 45 05.8	Fl R 4s	Red, spar, marked "V2".	Year round.
206.2	Digby Breakwater Light	44 37 33.0 065 45 02.1	Fl R 4s	15.5	4	Cylindrical mast, red and white triangular daymark. 3.0	Year round. Flash 1 s; eclipse 3 s.
209.1	<i>Port Wade Light Buoy VE1</i>	Annapolis Basin. 44 39 36.0 065 42 05.4	Fl G 4s	Green, spar, marked "VE1".	Year round.
209.3	<i>Black Point light buoy VE3</i>	Annapolis Basin. 44 40 57.4 065 39 07.8	Fl G 4s	Green, can, marked "VE3".	Year round.
209.8	<i>Goat Island light buoy VE4</i>	NW. of island. 44 42 18.9 065 37 16.8	Fl R 4s	Red, conical, marked "VE4".	Year round.
Annapolis River							
210 H3906	Schafners Point	On N. side of river. 44 42 35.5 065 37 08.6	F W	13.3	10 White square tower with red upper portion. 11.1	Private aid. Year round. Operates 24 h.
210.3	<i>Marsh Point light buoy VE5</i>	44 42 47.6 065 34 42.5	Fl G 4s	Green, pillar, marked "VE5".	Year round.
211 H3908	Annapolis	NE. of pier. 44 44 39.6 065 31 11.8	F R	9.1	8 White square tower with red upper portion. 8.5	Private aid. Year round.
213	<i>Centreville light buoy MA</i>	Trout Cove entrance. 44 33 20.0 066 02 40.0	Mo(A) W	6s Red-white, pillar, marked "MA".	Year round.
214 H3888	Centreville Breakwater Light	On W. side of cove. 44 33 05.5 066 02 02.6	Fl G 4s	13.6	7	Square skeleton tower, red and white rectangular daymark, green square in centre. 7.7	Year round. Flash 1 s; eclipse 3 s.
216 H3884	Boars Head	On W. side of N. entrance to Petit Passage. 44 24 14.5 066 12 55.0	Fl W 4s	28.0	17	White square tower with red upper portion. 11.6	Year round. Operates 24 h. Flash 1 s; eclipse 3 s.
217 H3885	Tiverton	Near outer end of breakwater. 44 23 47.0 066 12 45.0	Fl Y 4s	4.7	6	Cylindrical mast. 3.6	Year round. Flash 1 s; eclipse 3 s.
220	<i>Northwest Ledge light buoy M4</i>	Off Beatson Rocks. 44 18 17.0 066 25 55.0	Fl R 4s	Red, pillar, marked "M4".	Year round.
221 H3874	Grand Passage	N. point of Brier Island. 44 17 13.0 066 20 31.2	Fl W 9s	14.3	21	White rectangular tower with red top. 8.6	Year round. Operates 24 h. Flash 1 s; eclipse 8 s.

List of Lights, Buoys and Fog Signals – Atlantic Coast

No. ----- Intl No.	Name ----- RACON	Location ----- Latitude N. Longitude W.	Light Characteristics	Focal Height Above Water (m)	Nominal Range (NM)	Description ----- Height of Structure Above Ground Level (m)	Remarks ----- Audible Signals ----- AIS
--------------------------	------------------------	--	--------------------------	--	--------------------------	--	---

BAY OF FUNDY, N.S.

222	Cow Ledge Shoal light buoy HA4	E. of North Point. 44 17 11.0 066 20 03.0	Fl R 4s	Red, pillar, marked "HA4".	Year round.	
223 H3872	Brier Island	On W. point of island. 44 14 55.0 066 23 32.0	Fl(3) W 18s	22.2	14	White octagonal tower with horizontal red bands. 16.7	Year round. Operates 24 h.	
224	Gull Rock light buoy HA1	S. of rock. 44 12 08.0 066 23 11.0	Fl G 4s	Green, pillar, marked "HA1".	Year round.	
225	Southwest Ledge (Brier Island) light buoy M2	Off W. end of ledge. 44 10 09.0 066 27 12.0	Fl R 4s	Red, pillar, marked "M2".	Year round.	
226	Dartmouth Point light buoy HA2	Grand Passage. 44 14 45.0 066 19 57.0	Fl R 4s	Red, pillar, marked "HA2".	Year round.	
227 H3878	Peter Island	S. entrance to Grand Passage. 44 15 25.7 066 20 13.1	LFl G 6s	6	Square skeleton tower, red and white rectangular daymark, green square in centre.	Year round. Flash 2 s; eclipse 4 s.	
227.5	Peter Island North	Grand Passage. 44 15 37.4 066 20 15.3	Q G 1s	Green cylindrical mast. 6.4	Year round. Radar reflector.	
228 H3880	Westport	On outer end of public wharf and breakwater. 44 15 53.2 066 20 51.9	Fl G 4s	5.0	6	Pipe swing pole. 3.3	Year round. Flash 1 s; eclipse 3 s.	
228.5 H3875	Freeport South Breakwater	On breakwater. 44 16 00.4 066 19 44.5	Fl W 4s	4.2	6	Pipe swing pole. 3.3	Year round. Flash 1 s; eclipse 3 s.	
229 H3876	Freeport	On outer end of public wharf. 44 16 27.8 066 20 08.5	F R	8.7	7	Pipe swing pole. 6.8	Year round.

St. Marys Bay

230 H3864	Little River	On outer end of wharf. 44 26 37.4 066 07 44.7	LFl G 6s	7.5	7	Cylindrical mast, green and white square daymark. 6.8	Year round. Flash 2 s; eclipse 4 s.
230.2	East Sandy Cove	On outer end of wharf. 44 29 10.8 066 05 04.3	Fl R 4s	4.3	5	Pipe swing pole, red and white triangular daymark. 3.7	Year round. Flash 1 s; eclipse 3 s.
232.1	Sissiboo Outer light buoy HJ1	Weymouth Harbour. 44 26 54.6 066 01 15.9	Fl G 4s	Green, spar, marked "HJ1".	Year round.

List of Lights, Buoys and Fog Signals – Atlantic Coast

No. ----- Intl No.	Name ----- RACON	Location ----- Latitude N. Longitude W.	Light Characteristics	Focal Height Above Water (m)	Nominal Range (NM)	Description ----- Height of Structure Above Ground Level (m)	Remarks ----- Audible Signals ----- AIS
BAY OF FUNDY, N.S.							
234.3	East Sandy Cove light buoy HK3	44 28 48.5 066 04 39.0	Fl G 4s	Green, spar, marked "HK3".	Year round.
236.5 H3858	Comeauville Wharf	On wharf. 44 17 31.2 066 07 56.3	Fl R 4s	5.4	4	Square skeleton tower. 3.5	Private aid. Year round.
237	Saulnierville light buoy HE	Approach to Saulnierville wharf. 44 16 00.0 066 09 24.0	Mo(A) W 6s	Red-white, pillar, marked "HE".	Year round.
237.5 H3855	Saulnierville Breakwater	Near end of breakwater. 44 15 51.2 066 08 18.3	Fl R 4s	8.5	7	Square skeleton tower, red and white triangular daymark. 8.6	Year round. Flash 1 s; eclipse 3 s.
238 H3852	Meteghan River	At inner end of breakwater. 44 13 11.8 066 08 37.2	Fl W 4s	7.5	6	Pipe swing pole.	Year round.
239	Meteghan light buoy HC2	NW. of Meteghan breakwater. 44 11 43.0 066 12 00.0	Fl R 4s	Red, conical, marked "HC2".	Year round.
239.3	Meteghan Outer light buoy HC3	44 11 51.0 066 10 54.0	Fl G 4s	Green, spar, marked "HC3".	Year round.
239.4	Meteghan Inner light buoy HC4	44 11 50.0 066 10 12.0	Fl R 4s	Red, spar, marked "HC4".	Year round.
239.5 H3851	Meteghan Breakwater	On outer end of breakwater. 44 11 44.1 066 10 00.1	LFl R 6s	6	Square skeleton tower, red and white rectangular daymark. 4.8	Year round. Flash 2 s; eclipse 4 s.
241 H3848	Cape St. Marys	E. side of bay. 44 05 09.2 066 12 39.6	Fl W 5s	31.8	15	White rectangular tower with red top. 8.7	Private aid. Year round. Operates 24 h. Flash 0.5 s; eclipse 4.5 s.
242	Cape St. Marys light buoy NV	S. of cape. 44 04 10.3 066 12 35.0	Mo(A) W 6s	Red-white, pillar, marked "NV".	Year round.
243 H3846	Cape St. Marys Breakwater	On rubble breakwater. 44 05 03.5 066 12 15.0	Fl G 4s	8.0	4	Pipe Swing Pole, green, white and black square daymark.	Year round. Flash 1 s; eclipse 3 s. Radar reflector.
245	Trinity Ledge bifurcation light buoy NP	S. of ledge. 43 58 47.3 066 18 26.0	Fl(2+1) R 6s	Red-green-red, pillar, marked "NP".	Year round.
246	Port Maitland light buoy NU	N. of Port Maitland breakwater. 43 59 36.3 066 10 18.0	Mo(A) W 6s	Red-white, spar, marked "NU".	Year round.

List of Lights, Buoys and Fog Signals – Atlantic Coast

No. ----- Intl No.	Name ----- RACON	Location ----- Latitude N. Longitude W.	Light Characteristics	Focal Height Above Water (m)	Nominal Range (NM)	Description ----- Height of Structure Above Ground Level (m)	Remarks ----- Audible Signals ----- AIS
BAY OF FUNDY, N.S.							
247 H3840	Port Maitland Wharf Light	43 59 09.5 066 09 32.9	LFI G 6s	6.1	5	Square skeleton tower, green and white rectangular daymark. 6.9	Year round. Flash 2 s; eclipse 4 s. Radar reflector.
250.1	Port Maitland West Breakwater light	43 59 09.6 066 09 39.6	FI R 4s	4	Cylindrical mast, red and white triangular daymark. 3.0	Year round.
251	<i>Lurcher Shoal</i> <i>bifurcation light buoy</i> <i>NM</i> Racon K (- -) X Band	<i>W. of Southwest</i> <i>Shoal.</i> 43 48 57.2 066 29 58.0	<i>FI(2+1)</i> R 6s	<i>Red-green-red, pillar,</i> <i>marked "NM".</i>	<i>Year round.</i>
251.5	<i>Lurcher Northeast</i> <i>Shoal light buoy N9</i>	43 53 00.3 066 26 10.0	FI G 4s	<i>Green, pillar, marked "N9".</i>	<i>Year round.</i>
252	<i>Sandford light buoy</i> <i>NT2</i>	<i>Off Sandford.</i> 43 55 50.8 066 10 53.0	FI R 4s	<i>Red, pillar, marked "NT2".</i>	<i>Year round.</i>
253 H3838	Sandford Sector	43 55 07.6 066 09 14.7	Iso R 2s W G	8.3	12	Square skeleton tower, white rectangular daymark with red horizontal band. 6.9	Year round. Operates 24 h. R 090°57'-134°57'; W 134°57'-136°57'; G 136°57' to 180°57'.
255.7 H3837	Cheggoggin Point Breakwater	On end of breakwater. 43 51 09.5 066 09 40.2	FI G 4s	7	Square skeleton tower, green and white rectangular daymark. 6.1	Year round. Flash 1 s; eclipse 3 s.
256	<i>Cheggoggin Point light</i> <i>buoy NQ1</i>	<i>Off SW. extreme of</i> <i>Cheggoggin Point.</i> 43 50 35.2 066 10 38.5	FI G 4s	<i>Green, pillar, marked</i> <i>"NQ1".</i>	<i>Year round.</i>
Yarmouth Harbour and Approaches							
259	<i>Cat Rock light buoy</i> <i>Y3</i>	<i>S. of Cape Forchu.</i> 43 46 57.3 066 09 29.5	FI G 4s	<i>Green, pillar, marked "Y3".</i>	<i>Year round.</i> Audible signal: Whistle
260 H3820	Cape Forchu Racon B (- . .) X Band	E. Cape, S. point, Yarmouth Sound. 43 47 38.8 066 09 19.3	LFI W 12s	34.6	12	White hexagonal tower with red vertical stripe. 23.5	Private aid. Year round. Flash 2 s; eclipse 10 s.
260.5	<i>Johns Cove light buoy</i> <i>Y5</i>	43 47 50.3 066 08 44.9	FI G 4s	<i>Green, spar, marked "Y5".</i>	<i>Year round.</i>
261 H3822	Ships Stern	On N. end of Ships Stern. 43 48 31.7 066 08 45.9	FI W 4s	4	Pipe swing pole. 3.5	Year round.
262	<i>Privateer Rock light</i> <i>buoy Y12</i>	<i>E. of Ships Stern.</i> 43 48 34.0 066 08 38.8	FI R 4s	<i>Red, spar, marked "Y12".</i>	<i>Year round.</i>

List of Lights, Buoys and Fog Signals – Atlantic Coast

No. ----- Intl No.	Name ----- RACON	Location ----- Latitude N. Longitude W.	Light Characteristics	Focal Height Above Water (m)	Nominal Range (NM)	Description ----- Height of Structure Above Ground Level (m)	Remarks ----- Audible Signals ----- AIS
--------------------------	------------------------	--	--------------------------	--	--------------------------	--	---

BAY OF FUNDY, N.S.

263 H3826	Bunker Island	SW. point of island. 43 48 44.6 066 08 36.2	Iso R 4s	9.8	White square tower with red vertical stripe. 9.1	Year round.
264	Sollows Rock East light buoy Y17	SE. of rock. 43 48 50.2 066 08 40.1	Q G 1s	Green, spar, marked "Y17".	Year round.
265	Yarmouth Main Channel light buoy Y24	S. of Elders Head. 43 49 33.7 066 07 54.2	Fl R 4s	Red, spar, marked "Y24".	Year round.
266	Yarmouth South Channel light buoy Y26	43 49 51.6 066 07 38.8	Fl R 4s	Red, spar, marked "Y26".	Year round.
267	Hen and Chickens light buoy Y4	On W. side of shoal. 43 47 41.5 066 08 36.4	Fl R 4s	Red, pillar, marked "Y4".	Year round.
268	Roaring Bull light buoy Y2	43 45 10.3 066 09 41.0	Fl R 4s	Red, pillar, marked "Y2".	Year round.