

List of Lights, Buoys and Fog Signals – Atlantic Coast

No. ----- Intl No.	Name ----- RACON	Location ----- Latitude N. Longitude W.	Light Characteristics	Focal Height Above Water (m)	Nominal Range (NM)	Description ----- Height of Structure Above Ground Level (m)	Remarks ----- Audible Signals ----- AIS
NOVA SCOTIA, SOUTHEAST COAST							
327 H3784	Cape Sable Racon C (- . -) X Band	On cape. 43 23 24.0 065 37 16.9	Fl W 5s	29.7	18	White octagonal tower with red top. 30.0	Year round. Operates 24 h. Flash 1 s; eclipse 4 s. Emergency light: Fl(6) W 15s. Fog Horn Blast 4 s; sil. 56 s.
328	<i>Hawk Channel light buoy JS53</i>	<i>E. entrance of channel. 43 23 58.0 065 35 20.0</i>	<i>Fl G 4s</i>	<i>.....</i>	<i>.....</i>	<i>Green, pillar, marked "JS53".</i>	<i>Year round.</i>
329	<i>White Knoll Ledge light buoy JS55</i>	<i>SE. of ledge. 43 25 13.0 065 34 17.5</i>	<i>Fl G 4s</i>	<i>.....</i>	<i>.....</i>	<i>Green, pillar, marked "JS55".</i>	<i>Year round.</i>
329.5 H3784.4	Daniels Head	End of rubble breakwater. 43 26 54.6 065 35 09.7	Fl G 4s	9.4	4	Square skeleton tower, red and white rectangular daymark, green square in centre. 6.6	Year round.
329.6	<i>Daniels Head light buoy JU50</i>	<i>43 26 57.0 065 34 55.0</i>	<i>Fl R 4s</i>	<i>.....</i>	<i>.....</i>	<i>Red, spar, marked "JU50".</i>	<i>Year round.</i>
330	<i>Stoney Island light buoy JQ</i>	<i>N. of Stoney Island Shoal. 43 27 24.5 065 32 44.5</i>	<i>Mo(A) W 6s</i>	<i>.....</i>	<i>.....</i>	<i>Red-white, pillar, marked "JQ".</i>	<i>Year round.</i>
331	<i>Congress Shoal light buoy JS59</i>	<i>E. of shoal. 43 27 58.0 065 32 48.0</i>	<i>Fl G 4s</i>	<i>.....</i>	<i>.....</i>	<i>Green, spar, marked "JS59".</i>	<i>Year round.</i>
331.2 H3787.41	Stoney Island Outer Breakwater	On outer end of breakwater. 43 28 06.4 065 33 56.2	Fl G 3s	9.6	Square skeleton tower, red and white rectangular daymark, green square in centre. 6.7	Year round. Flash 1 s; eclipse 2 s.
331.44	<i>Stoney Island light buoy JQ52</i>	<i>Barrington Bay. 43 27 57.5 065 33 40.3</i>	<i>Fl R 4s</i>	<i>.....</i>	<i>.....</i>	<i>Red, pillar, marked "JQ52".</i>	<i>Year round.</i>
331.5 H3787.5	Cripple Creek Breakwater Light	43 29 22.5 065 33 35.3	Iso G 4s	2	Pipe swing pole. 3.5	Year round.
331.6	<i>Cripple Creek light buoy JS61</i>	<i>43 29 21.0 065 33 18.0</i>	<i>Fl G 4s</i>	<i>.....</i>	<i>.....</i>	<i>Green, spar, marked "JS61".</i>	<i>Year round.</i>
333.5	<i>Wesses Ledge light buoy JS70</i>	<i>43 31 02.5 065 34 58.0</i>	<i>Q R 1s</i>	<i>.....</i>	<i>.....</i>	<i>Red, spar, marked "JS70".</i>	<i>Year round.</i>
334	<i>Barrington Passage Channel light buoy JS76</i>	<i>Entrance to channel. 43 31 26.0 065 35 51.0</i>	<i>Fl R 4s</i>	<i>.....</i>	<i>.....</i>	<i>Red, pillar, marked "JS76".</i>	<i>Year round.</i>

List of Lights, Buoys and Fog Signals – Atlantic Coast

No. ----- Intl No.	Name ----- RACON	Location ----- Latitude N. Longitude W.	Light Characteristics	Focal Height Above Water (m)	Nominal Range (NM)	Description ----- Height of Structure Above Ground Level (m)	Remarks ----- Audible Signals ----- AIS
NOVA SCOTIA, SOUTHEAST COAST							
336 H3782	Baccaro Point	E. side of entrance to Barrington Bay. 43 26 59.0 065 28 15.0	Mo(D) W 10s	15.0	15	White square tower with red upper portion. 14.0	Year round. Flash 5 s; eclipse 1 s; flash 1 s; eclipse 1 s; flash 1 s; eclipse 1 s. Visible 207°-127°. Fog Horn Blast 2 s; sil. 18 s.
337	<i>Bantam Rocks light buoy JS56</i>	<i>W. of the rocks.</i> 43 25 42.0 065 29 16.0	<i>Fl R 4s</i>	<i>Red, pillar, marked "JS56".</i>	<i>Year round.</i>
338	<i>Brazil Rock South Cardinal light buoy J</i>	<i>S. of rock.</i> 43 21 00.0 065 26 44.0	<i>Q(6) + W LFI</i>	15s	<i>Yellow-black, pillar, marked "J".</i>	<i>Year round.</i>
339	<i>Cuckold Rock light buoy JJ51</i>	<i>SE. of rock, entrance to Port La Tour.</i> 43 27 06.0 065 27 18.0	<i>Fl G 4s</i>	<i>Green, spar, marked "JJ51".</i>	<i>Year round.</i>
340	<i>Port La Tour light buoy JN</i>	<i>SE. of Whale Back.</i> 43 29 27.0 065 26 42.0	<i>Mo(A) W 6s</i>	<i>Red-white, pillar, marked "JN".</i>	<i>Year round.</i>
340.01	<i>Outer Rock South Cardinal light buoy JJ</i>	43 26 00.0 065 26 35.0	<i>Q(6) + W LFI</i>	15s	<i>Yellow-black, spar, marked "JJ".</i>	<i>Year round.</i>
340.03	<i>Port La Tour light buoy JJ56</i>	43 27 51.7 065 26 59.2	<i>Fl R 4s</i>	<i>Red, spar, marked "JJ56".</i>	<i>Year round.</i>
340.04	<i>Port La Tour light buoy JJ57</i>	43 28 33.0 065 27 08.5	<i>Fl G 4s</i>	<i>Green, spar, marked "JJ57".</i>	<i>Year round.</i>
342	<i>Port La Tour Inner light buoy JN53</i>	<i>Off Mohawk Ledge.</i> 43 30 20.8 065 27 08.2	<i>Fl G 4s</i>	<i>Green, spar, marked "JN53".</i>	<i>Year round.</i>
343 H3781	Upper Port La Tour	Outer end of E. breakwater. 43 30 16.9 065 28 12.7	LFI R 6s	7.3	5	Pipe swing pole, red and white triangular daymark. 6.8	Year round. Flash 2 s; eclipse 4 s.
344 H3780	Port La Tour	On outer end of breakwater. 43 29 58.0 065 28 14.2	Fl G 4s	6.3	Cylindrical mast, green and white square daymark. 3.8	Year round. Flash 1 s; eclipse 3 s.
345 H3779	Port Latour Harbour	On Whale Back Rock. 43 29 34.0 065 26 58.8	Fl G 4s	5.5	2	Cylindrical mast, green, white and black square daymark. 3.8	Year round.
346	<i>Barrel Rock light buoy JA56</i>	<i>SW. of rock.</i> 43 29 44.0 065 27 06.0	<i>Q R 1s</i>	<i>Red, spar, marked "JA56".</i>	<i>Year round.</i>
346.01	<i>Port La Tour light buoy JN51</i>	43 29 55.5 065 26 39.4	<i>Q G 1s</i>	<i>Green, spar, marked "JN51".</i>	<i>Year round.</i>

List of Lights, Buoys and Fog Signals – Atlantic Coast

No. ----- Intl No.	Name ----- RACON	Location ----- Latitude N. Longitude W.	Light Characteristics	Focal Height Above Water (m)	Nominal Range (NM)	Description ----- Height of Structure Above Ground Level (m)	Remarks ----- Audible Signals ----- AIS
NOVA SCOTIA, SOUTHEAST COAST							
347	Port La Tour light buoy JA	S. of Blanche Island. 43 26 33.0 065 24 09.0	Mo(A) W 6s	Red-white, pillar, marked "JA".	Year round.
348 H3778	The Salvages	SE. end of island. 43 28 08.1 065 22 44.0	LFI W 12s 15.6	10		White rectangular tower with red top. 12.0	Year round. Flash 2 s; eclipse 10 s. Fog Horn Blast 2 s; sil. 3 s; blast 2 s; sil. 3 s; blast 2 s; sil. 48 s.
349 H3774	Long Rock Light and Fog Signal	On SE. end of island. 43 30 26.2 065 20 44.2	LFI W 6s 28.3	11		White octagonal tower with red top. 12.0	Year round. Flash 2 s; eclipse 4 s. Visible 187°-106°30'. Fog Horn Blast 6 s; sil. 54 s.
350	Budget Rock light and bell buoy SN51	At entrance to Negro Harbour. 43 31 35.0 065 20 41.5	FI G 4s	Green, pillar, marked "SN51".	Year round. Audible signal: Bell
350.02	East Point light buoy SN52	Port La Tour. 43 31 48.9 065 20 53.0	FI R 4s	Red, spar, marked "SN52".	Year round.
350.5	The Nubble North Cardinal light buoy SNC	43 32 00.0 065 23 30.0	Q W 1s	Black-yellow, pillar, marked "SNC".	Year round.
351	Grog Rock light buoy SP54	SW. of rock. 43 32 20.6 065 21 51.5	FI R 4s	Red, pillar, marked "SP54".	Year round.
351.02	Apple Island light buoy SP56	Port La Tour. 43 32 36.4 065 21 51.5	FI R 4s	Red, spar, marked "SP56".	Year round.
351.04	North East Harbour light buoy SP59	Port La Tour. 43 33 08.0 065 22 04.0	FI G 4s	Green, spar, marked "SP59".	Year round.
352 H3776	Ingomar Wharf	On outer end of wharf. 43 33 45.7 065 21 46.8	LFI R 6s 5.5	5		Cylindrical mast, red and white triangular daymark. 3.7	Year round. Flash 2 s; eclipse 4 s.
352.5 H0665	Shingle Point light buoy SN60	Off point. 43 32 49.0 065 24 15.0	FI R 4s	Red, pillar, marked "SN60".	Year round.
353	East Entrance fairway light and whistle buoy SN	At E. entrance to harbour. 43 31 01.5 065 18 50.0	Mo(A) W 6s	Red-white, pillar, marked "SN".	Year round. Audible signal: Whistle
354	Jig Rock light buoy S51	Off rock. 43 35 58.3 065 15 51.4	FI G 4s	Green, pillar, marked "S51".	Year round.

List of Lights, Buoys and Fog Signals – Atlantic Coast

No. ----- Intl No.	Name ----- RACON	Location ----- Latitude N. Longitude W.	Light Characteristics	Focal Height Above Water (m)	Nominal Range (NM)	Description ----- Height of Structure Above Ground Level (m)	Remarks ----- Audible Signals ----- AIS	
NOVA SCOTIA, SOUTHEAST COAST								
355 H3762	Cape Roseway	Near SE. point of McNutt Island. 43 37 21.4 065 15 50.0	Fl W 10s	33.1	10	White octagonal tower with red top. 17.3	Year round. Flash 1 s; eclipse 9 s. Visible 187°- 055°.	
357	Shelburne light buoy S	Off entrance to Shelburne Harbour. 43 37 36.0 065 13 51.0	Mo(A) W 6s	Red-white, pillar, marked "S".	Year round.	
357.5	Old Cow Reef bifurcation light buoy SAC	43 38 18.0 065 13 12.0	Fl(2+1) R 6s	Red-green-red, pillar, marked "SAC".	Year round.	
357.8	Strap Tub South Cardinal light buoy KSA	Shelburne. 43 39 00.0 065 14 07.8	Q(6) + W LFI	15s	Yellow-black, spar, marked "KSA".	Year round.
359 H3763	Lower Sandy Point	On outer end of wharf. 43 40 48.7 065 18 10.8	Fl W 4s	4.3	5	Pipe swing pole. 3.7	Year round.	
360.01	Gunning Cove light buoy SA51	43 41 01.5 065 20 18.0	Fl G 4s	Green, spar, marked "SA51".	Year round.	
360.02	Sandy Point Inner light buoy S56	Shelburne. 43 42 22.8 065 19 38.4	Fl R 4s	Red, pillar, marked "S56".	Year round.	
360.1	Middle Rock light buoy S52	Shelburne. 43 40 34.8 065 18 50.4	Fl R 4s	Red, pillar, marked "S52".	Year round.	
360.11	Irving Oil Wharf Ruins light buoy SD52	Shelburne. 43 45 23.3 065 19 26.9	Fl R 4s	Red, spar, marked "SD52".	Year round.	
360.8	Lower Sandy Point South Breakwater Light	43 40 44.0 065 18 07.1	Fl R 5s	2	Pipe tower, red and white triangular daymark.	Year round. Flash 1 s; eclipse 4 s.	
361 H3765	Gunning Cove	On large rock, N. end of shoal. 43 40 53.3 065 20 06.9	Fl W 4s	4.3	6	Cylindrical mast. 3.8	Private aid. Year round.	
362.8	Sandy Point light buoy S54	SE. coast, Shelburne Harbour. 43 41 25.3 065 19 39.9	Q R 1s	Red, pillar, marked "S54".	Year round.	
363 H3766	Sandy Point	Shelburne. 43 41 29.3 065 19 31.5	F R	14.3	6	White square tower. 13.4	Private aid. Year round. Operates 24 h. Visible 310°-188°.
366.01	Lower Jordan Bay Outer light buoy KS57	Shelburne. 43 40 45.2 065 13 59.6	Fl G 4s	Green, pillar, marked "KS57".	Year round.	
366.02	Lower Jordan Bay Outer light buoy KS56	Shelburne. 43 40 46.2 065 13 58.8	Fl R 4s	Red, pillar, marked "KS56".	Year round.	

List of Lights, Buoys and Fog Signals – Atlantic Coast

No. ----- Intl No.	Name ----- RACON	Location ----- Latitude N. Longitude W.	Light Characteristics	Focal Height Above Water (m)	Nominal Range (NM)	Description ----- Height of Structure Above Ground Level (m)	Remarks ----- Audible Signals ----- AIS
NOVA SCOTIA, SOUTHEAST COAST							
366.03	Lower Jordan Bay Inner light buoy KS59	Shelburne. 43 40 49.7 065 14 08.9	Fl G 4s	Green, pillar, marked "KS59".	Year round.
366.04	Lower Jordan Bay Inner light buoy KS58	Shelburne. 43 40 50.1 065 14 08.5	Fl R 4s	Red, pillar, marked "KS58".	Year round.
366.05	Lower Jordan Bay light buoy KS54	43 40 43.3 065 13 52.0	Fl R 4s	Red, spar, marked "KS54".	Year round.
366.06	Lower Jordan Bay light buoy KS55	Jordan Bay and Green Harbour. 43 40 41.6 065 13 53.6	Fl G 4s	Green, spar, marked "KS55".	Year round.
366.1	Lower Jordan Bay Fairway light buoy KS	43 39 44.7 065 13 05.0	Mo(A) W 6s	Red-white, pillar, marked "KS".	Year round.
366.35	Lower Jordan Bay light buoy KS53	43 40 38.2 065 13 45.1	Q G 1s	Green, spar, marked "KS53".	Year round.
366.8	Lower Jordan Bay light buoy KS61	Jordan Bay and Green Harbour. 43 40 56.3 065 14 14.9	Fl G 4s	Green, pillar, marked "KS61".	Year round.
367 H3759.4	Lower Jordan Bay Wharf	On most northerly end of wharf. 43 40 52.0 065 14 23.0	LFl W 6s	3.0	Cylindrical mast, red and white rectangular daymark. 3.8	Year round. Flash 2 s; eclipse 4 s.
367.7	Green Harbour light buoy KPA	NE. of Jenkins Island. 43 43 14.0 065 09 37.5	Mo(A) W 6s	Red-white, spar, marked "KPA".	Year round.
368	Green Harbour light and bell buoy KP	43 40 14.6 065 09 33.0	Mo(A) W 6s	Red-white, pillar, marked "KP".	Year round. Audible signal: Bell
368.02	West Green Harbour Outer light buoy KP56	Shelburne. 43 43 14.8 065 09 48.2	Fl R 4s	Red, pillar, marked "KP56".	Year round.
369	Bull Rock light buoy KK51	SW. of rock. 43 37 32.0 065 08 11.5	Fl G 4s	Green, pillar, marked "KK51".	Year round.
369.04	Southwest Rock light buoy KK57	43 40 00.3 065 06 13.9	Q G 1s	Green, spar, marked "KK57".	Year round.
Lockeport							
370 H3750	Lockeport	On Gull Rock, entrance to harbour. 43 39 18.3 065 05 55.9	LFl W 15s	16.7	12	White rectangular tower with red top. 12.1	Year round. Flash 4 s; eclipse 11 s. Fog Horn Blast 3 s; sil. 27 s.
371	Laurier Rock light buoy KK61	SW. of rock. 43 41 01.8 065 05 45.9	Fl G 4s	Green, spar, marked "KK61".	Year round.

List of Lights, Buoys and Fog Signals – Atlantic Coast

No. ----- Intl No.	Name ----- RACON	Location ----- Latitude N. Longitude W.	Light Characteristics	Focal Height Above Water (m)	Nominal Range (NM)	Description ----- Height of Structure Above Ground Level (m)	Remarks ----- Audible Signals ----- AIS
NOVA SCOTIA, SOUTHEAST COAST							
371.02	Laurier Rock light buoy KK64	43 41 16.3 065 05 47.9	Fl R 4s	Red, spar, marked "KK64".	Year round.
372	Carter Island light buoy KK69	S. of island. 43 42 08.3 065 05 58.9	Q G 1s	Green, spar, marked "KK69".	Year round.
372.03	Lockeport Inner Harbour light buoy KK72	43 42 06.8 065 06 33.9	Fl R 4s	Red, spar, marked "KK72".	Year round.
373.5 H3758	Osborne Harbour	On outer end of wharf. 43 42 52.6 065 06 33.6	LFl R 6s	4.7	5	Cylindrical mast, red and white triangular daymark.	Year round. Flash 2 s; eclipse 4 s.
374 H3753	Carter Island	On S. end of island. 43 42 19.3 065 06 04.0	Fl W 6s	16.4	7	White cylindrical tower, red horizontal band. 11.5	Year round. Flash 1 s; eclipse 5 s.
375 H3754	Lockeport Breakwater	Near outer end of S. breakwater. 43 42 05.6 065 06 25.8	Fl G 5s	3.0	4	Cylindrical mast, green and white square daymark. 3.0	Year round. Flash 1 s; eclipse 4 s.
380 H3755	Lockeport North	On outer end of N. breakwater. 43 42 09.0 065 06 25.9	Q R 1s	3.0	3	Cylindrical mast, red and white triangular daymark. 3.0	Year round.
382.01	Outer Farm Ledge light buoy KE52	43 38 27.0 065 02 15.0	Fl R 4s	Red, pillar, marked "KE52".	Year round.
383.1	Black Point Fairway light buoy KE	43 39 31.3 065 04 18.9	Mo(A) W 6s	Red-white, pillar, marked "KE".	Year round.
383.5	Lockeport West Cardinal light buoy KEA	43 40 14.3 065 04 57.9	Q(9) W 15s	Yellow-black-yellow, pillar, marked "KEA".	Year round.
384 H3748	Little Harbour Wharf	On outer end of wharf. 43 42 57.5 065 01 48.1	Fl R 4s	3.0	7	Pipe swing pole.	Year round. Flash 1 s; eclipse 3 s.
384.5	Little Harbour light buoy KC53	Port Joli. 43 42 54.0 065 00 51.0	Q G 1s	Green, spar, marked "KC53".	Year round.
386	Little Harbour East Cardinal light buoy KC	43 42 29.4 064 59 42.0	Q(3) W 10s	Black-yellow-black, pillar, marked "KC".	Year round.
386.01	Bantam Rock light buoy KA51	43 43 12.0 064 58 00.0	Fl G 4s	Green, pillar, marked "KA51".	Year round.
387	Port Hebert light buoy UX	SW. of Thrum Point. 43 46 19.0 064 54 47.0	Mo(A) W 6s	Red-white, pillar, marked "UX".	Year round.
387.01	Shingle Point light buoy UX53	43 48 30.0 064 55 24.0	Fl G 4s	Green, spar, marked "UX53".	Year round.

List of Lights, Buoys and Fog Signals – Atlantic Coast

No. ----- Intl No.	Name ----- RACON	Location ----- Latitude N. Longitude W.	Light Characteristics	Focal Height Above Water (m)	Nominal Range (NM)	Description ----- Height of Structure Above Ground Level (m)	Remarks ----- Audible Signals ----- AIS
NOVA SCOTIA, SOUTHEAST COAST							
387.04	Port Hebert light buoy UX56	43 48 49.0 064 55 42.0	Fl R 4s	Red, conical, marked "UX56".	Year round.
387.5	Shingle Point light buoy UX55	Port Joli. 43 48 42.5 064 55 33.0	Q G 1s	Green, pillar, marked "UX55".	Year round.
388 H3746	Port Hebert	On Shingle Point, E. side of harbour. 43 48 46.9 064 55 30.4	Fl R 5s	8.0	4	Square skeleton tower, red and white rectangular daymark, red triangle in centre. 6.6	Year round. Flash 1 s; eclipse 4 s.
391	Little Hope Shoal light buoy UV52	S. of Shoal. 43 47 15.0 064 49 53.0	Fl R 4s	Red, pillar, marked "UV52".	Year round.
394.01	Little Hope Island East Cardinal light buoy UEF	43 48 12.6 064 46 27.2	Q(3) W 10s	Black-yellow-black, pillar, marked "UEF".	Year round.
394.5	Mouton Head light buoy US51	E. of Port Mouton Light. 43 51 45.0 064 46 16.8	Fl G 4s	Green, pillar, marked "US51".	Year round.
395	Port Mouton light buoy UN	E. of Mouton Island. 43 53 31.0 064 42 30.0	Mo(A) W 6s	Red-white, pillar, marked "UN".	Year round.
396 H3742	Port Mouton	NE. point, Spectacle Island. 43 55 05.6 064 48 14.4	LFl W 12s	16.8	6	White square tower with red top. 7.5	Year round. Flash 2 s; eclipse 10 s. Visible 069°30'-291°30'.
396.1	Willow Cove Entrance light buoy UT52	Port Mouton. 43 54 59.8 064 50 11.7	Fl R 4s	Red, spar, marked "UT52".	Year round.
396.2	Willow Cove Entrance light buoy UT53	Port Mouton. 43 54 58.2 064 50 10.9	Fl G 4s	Green, spar, marked "UT53".	Year round.
396.3	Willow Cove Entrance light buoy UT54	Port Mouton. 43 54 56.8 064 50 11.8	Q R 1s	Red, spar, marked "UT54".	Year round.
396.4 H3742.04	Spectacle Islands West	Off W. side of islands. 43 54 32.0 064 48 42.4	Fl R 4s	4	Red cylindrical mast, red and white rectangular daymark. 3.1	Year round. Flash 1 s; eclipse 3 s.
396.5	Wobamkek Beach light buoy US57	Port Mouton. 43 54 20.0 064 48 14.0	Fl G 4s	Green, pillar, marked "US57".	Year round.
397.5	Middle Rock East Cardinal light buoy US	Port Mouton. 43 53 37.5 064 47 03.0	Q(3) W 10s	Black-yellow-black, pillar, marked "US".	Year round.
398	Willow Cove light buoy UT	N. of cove. 43 55 07.2 064 50 09.8	Mo(A) W 6s	Red-white, spar, marked "UT".	Year round.

List of Lights, Buoys and Fog Signals – Atlantic Coast

No. ----- Intl No.	Name ----- RACON	Location ----- Latitude N. Longitude W.	Light Characteristics	Focal Height Above Water (m)	Nominal Range (NM)	Description ----- Height of Structure Above Ground Level (m)	Remarks ----- Audible Signals ----- AIS
NOVA SCOTIA, SOUTHEAST COAST							
399.5 H3742.5	Port Mouton Inner	On fish plant wharf. 43 55 10.0 064 50 49.8	LFI R 6s	4.3	5	Cylindrical mast, triangular daymark. 3.5	Year round. Flash 2 s; eclipse 4 s.
400	Charley Island light buoy UN59	Port Mouton. 43 55 22.5 064 50 10.4	FI G 4s	Green, spar, marked "UN59".	Year round.
400.5	Port Mouton Channel light buoy UN66	Port Mouton. 43 55 29.2 064 50 25.3	FI R 4s	Red, pillar, marked "UN66".	Year round.
400.7	Port Mouton light buoy UN74	Port Mouton. 43 55 17.0 064 50 34.8	Q R 1s	Red, pillar, marked "UN74".	Year round.
401	Port Mouton light buoy UN80	Port Mouton. 43 55 12.9 064 50 43.6	FI R 4s	Red, pillar, marked "UN80".	Year round.
401.5 H3472.3	Port Mouton Breakwater Light	43 55 16.0 064 50 33.0	FI G 4s	3	Cylindrical mast.	Year round.
402	Spectacle Ledge light buoy UN55	N. of ledge. 43 56 09.0 064 47 28.5	FI G 4s	Green, pillar, marked "UN55".	Year round.
403 H3742.6	Hunts Landing	On outer end of breakwater. 43 57 05.3 064 46 07.5	Iso R 4s	7.6	4	Square skeleton tower, red and white rectangular daymark, red triangle in centre. 3.5	Year round. Visible 060°30'-291°30'.
403.4	Brazil Rocks light buoy UN54	43 54 54.5 064 44 42.0	Q R 1s	Red, pillar, marked "UN54".	Year round.
404	White Point Rock light buoy UQ52	S. of rock. 43 55 36.5 064 43 02.0	FI R 4s	Red, pillar, marked "UQ52".	Year round.
405 H3740	Western Head	W. side of entrance to Liverpool Bay. 43 59 20.8 064 39 44.5	FI W 15s	16.8	15	White octagonal tower with red top. 13.8	Year round. Operates 24 h. Flash 0.5 s; eclipse 14 .5 s. Visible 180° - 062°.
407 H3735	Coffin Island	44 02 03.5 064 37 42.5	FI W 4s	14.9	6	White cylindrical tower with red top.	Year round. Flash 1 s; eclipse 3 s.
408.1	Moose Harbour light buoy UB1	44 01 17.8 064 39 35.8	FI G 4s	Green, spar, marked "UB1".	Year round.
408.2 H3736	Moose Point	Outer end of breakwater. 44 01 10.2 064 39 45.5	Iso G 2s	5	Cylindrical mast.	Year round.
408.5	Brooklyn Pier light buoy UM52	44 02 38.4 064 41 32.3	FI R 4s	Red, pillar, marked "UM52".	Year round.
409 H3730	Brooklyn Pier	Near outer end of breakwater. 44 02 40.4 064 41 30.3	FI R 4s	7	Cylindrical mast.	Year round. Flash 1 s; eclipse 3 s.

List of Lights, Buoys and Fog Signals – Atlantic Coast

No. ----- Intl No.	Name ----- RACON	Location ----- Latitude N. Longitude W.	Light Characteristics	Focal Height Above Water (m)	Nominal Range (NM)	Description ----- Height of Structure Above Ground Level (m)	Remarks ----- Audible Signals ----- AIS
NOVA SCOTIA, SOUTHEAST COAST							
410	Fort Point Shoal light buoy UM53	44 02 46.3 064 42 03.9	Q G 1s	Green, pillar, marked "UM53".	Year round.
410.5	Liverpool Harbour light buoy UM58	44 02 47.5 064 42 26.4	Fl R 4s	Red, spar, marked "UM58".	Year round.
411	Liverpool Harbour light buoy UM59	44 02 43.7 064 42 30.5	Fl G 4s	Green, spar, marked "UM59".	Year round.
411.5	Liverpool Harbour light buoy UM60	44 02 43.8 064 42 36.0	Fl R 4s	Red, spar, marked "UM60".	Year round.
412.2	West Berlin light buoy UJ	Medway Harbour. 44 03 40.3 064 35 18.8	Mo(A) W 6s	Red-white, spar, marked "UJ".	Year round.
412.3	Liverpool Harbour light buoy UM64	44 02 33.3 064 42 49.3	Fl R 4s	Red, spar, marked "UM64".	Year round.
412.5	Blueberry Bay light buoy UJ52	Medway Harbour. 44 04 01.3 064 35 10.8	Fl R 4s	Red, spar, marked "UJ52".	Year round.
413	Port Medway light buoy UA51	44 03 23.3 064 31 28.8	Fl G 4s	Green, pillar, marked "UA51".	Year round.
414	Medway South Cardinal light and whistle buoy UA	SW. of Southwest Breaker. 44 04 58.3 064 31 24.8	Q(6) + LFI W 15s	Yellow-black, pillar, marked "UA".	Year round. Audible signal: Whistle
414.5	Long Cove East Cardinal light and bell buoy UC	44 05 12.0 064 32 14.0	Q(3) W 10s	Black-yellow-black, pillar, marked "UC".	Year round. Audible signal: Bell
415 H3722	Medway Head	W. side of entrance. 44 06 10.6 064 32 23.3	Fl W 12s	24.3	11	White square tower with red upper portion. 8.7	Year round. Operates 24 h. Flash 4 s; eclipse 8 s.
415.3 H0577	Fosters Islets light buoy UA64	Medway Harbour. 44 08 02.3 064 34 25.8	Fl R 4s	Red, pillar, marked "UA64".	Year round.
415.5 H3721	Frying Pan Island	44 06 04.2 064 31 23.8	LFI R 12s	10.5	8	Triangular skeleton tower, red and white rectangular daymark. 5.4	Year round. Flash 2 s; eclipse 10 s.
416.3	Great Island bifurcation light buoy UAA	Off Island. 44 07 48.3 064 32 28.8	Fl(2+1) R 6s	Red-green-red, pillar, marked "UAA".	Year round.
416.4	Medway Harbour light buoy UE51	44 08 33.3 064 32 28.8	Fl G 4s	Green, spar, marked "UE51".	Year round.
416.5 H3725	Voglers Cove West Direction	On outer end of breakwater. 44 09 09.7 064 32 43.4	Fl R 3s	4.5	4	Cylindrical mast. 3.6	Year round. Flash 1 s; eclipse 2 s.
416.51	Medway Harbour (West Berlin) light buoy UJ54	Liverpool. 44 04 02.7 064 35 05.6	Fl R 4s	Red, spar, marked "UJ54".	Year round.

List of Lights, Buoys and Fog Signals – Atlantic Coast

No. ----- Intl No.	Name ----- RACON	Location ----- Latitude N. Longitude W.	Light Characteristics	Focal Height Above Water (m)	Nominal Range (NM)	Description ----- Height of Structure Above Ground Level (m)	Remarks ----- Audible Signals ----- AIS
NOVA SCOTIA, SOUTHEAST COAST							
416.515	Medway Harbour (West Berlin) light buoy UJ55	44 04 02.0 064 35 06.2	Fl G 4s	Green, spar, marked "UJ55".	Year round.
416.52	Medway Harbour (West Berlin) light buoy UJ56	Liverpool. 44 04 04.6 064 35 03.7	Fl R 4s	Red, spar, marked "UJ56".	Year round.
416.525	West Berlin light buoy UJ57	44 04 04.9 064 35 02.0	Q G 1s	Green, spar, marked "UJ57".	Year round. Operates 24 h.
416.53	Medway Harbour (West Berlin) light buoy UJ58	Liverpool. 44 04 06.7 064 35 05.2	Fl R 4s	Red, spar, marked "UJ58".	Year round.
416.54	Medway Harbour (West Berlin) light buoy UJ59	Liverpool. 44 04 07.6 064 35 02.7	Fl G 4s	Green, spar, marked "UJ59".	Year round.
416.55	Medway Harbour (West Berlin) light buoy UJ61	Liverpool. 44 04 10.3 064 35 00.8	Fl G 4s	Green, spar, marked "UJ61".	Year round.
417.5 H3718	Cherry Cove	On point of land between Little Harbour and Back Cove. 44 09 29.8 064 28 53.2	Iso G 4s	6.7	5	Cylindrical mast. 3.7	Year round.
417.81	Little Harbour (Cherry Cove) light buoy TU53	Liverpool. 44 09 36.8 064 28 40.3	Fl G 4s	Green, spar, marked "TU53".	Year round.
418	Little Harbour Cherry Cove light buoy TU	44 09 31.6 064 28 00.3	Mo(A) W 6s	Red-white, pillar, marked "TU".	Year round.
419	Little Harbour (Cherry Cove) light buoy TU54	Medway Harbour. 44 09 37.7 064 28 48.2	Fl R 4s	Red, spar, marked "TU54".	Year round.
419.5	Seal Point light and bell buoy TS52	S. of point. 44 10 23.3 064 23 51.8	Fl R 4s	Red, pillar, marked "TS52".	Year round. Audible signal: Bell
420	Cape LaHave Island South light and whistle buoy TS51	SE. of island. 44 09 18.3 064 22 13.8	Fl G 4s	Green, pillar, marked "TS51".	Year round. Audible signal: Whistle
420.5	Black Rock East Cardinal light and whistle buoy T	44 09 38.7 064 18 43.7	Q(3) W 10s	Black-yellow-black, pillar, marked "T".	Year round. Audible signal: Whistle
421.2	Crooked Channel light buoy TS56	44 13 31.9 064 22 51.3	Fl R 4s	Red, spar, marked "TS56".	Year round.
421.5	Crooked Channel light buoy TS61	44 13 50.9 064 22 29.9	Fl G 4s	Green, spar, marked "TS61".	Year round.
422	False LaHave light and bell buoy T51	E. of Cape LaHave Island. 44 12 36.3 064 19 03.7	Fl G 4s	Green, pillar, marked "T51".	Year round. Audible signal: Bell

List of Lights, Buoys and Fog Signals – Atlantic Coast

No. ----- Intl No.	Name ----- RACON	Location ----- Latitude N. Longitude W.	Light Characteristics	Focal Height Above Water (m)	Nominal Range (NM)	Description ----- Height of Structure Above Ground Level (m)	Remarks ----- Audible Signals ----- AIS
NOVA SCOTIA, SOUTHEAST COAST							
423 H3710	Moshers Island	On island, W. side of entrance to LaHave River. 44 14 14.6 064 18 59.1	F W	23.3	13	White cylindrical tower with red top. 11.4	Year round. Visible 106°-351°.
423.8	<i>Crooked Channel light buoy TS64</i>	44 14 03.9 064 22 08.3	Fl R 4s	Red, pillar, marked "TS64".	Year round.
424.1	<i>West Dublin light buoy TS65</i>	44 14 22.5 064 21 58.5	Fl G 4s	Green, spar, marked "TS65".	Year round.
424.7	<i>West Dublin light buoy TS70</i>	Liverpool. 44 14 28.4 064 22 11.8	Fl R 4s	Red, spar, marked "TS70".	Year round.
425	<i>La Have light and bell buoy TA</i>	Entrance to La Have River. 44 14 57.4 064 18 39.3	Mo(A) W 6s	Red-white, pillar, marked "TA".	Year round. Audible signal: Bell
426.25	<i>Cockawee Shoal bifurcation light and bell buoy TD</i>	N. of East Spectacle Island. 44 15 30.4 064 20 15.8	F(2+1) R 6s	Red-green-red, pillar, marked "TD".	Year round. Audible signal: Bell
426.5	<i>Cockawee Shoal light buoy T54/2</i>	44 15 41.8 064 21 26.3	Fl R 4s	Red, spar, marked "T54/2".	Year round.
427	<i>Cockawee Shoal West light buoy T56</i>	W. of shoal. 44 15 50.6 064 21 32.8	Q R 1s	Red, pillar, marked "T56".	Year round.
428 H3711	Dublin Shore South Cardinal Light	On wharf. 44 16 01.2 064 21 50.2	Q(6) + LFl W 15s	8.4	5	Black cylindrical mast with yellow band at top. 3.4	Year round. Radar reflector.
429	<i>Dublin Shore light buoy T59</i>	44 16 14.4 064 21 17.2	Fl G 4s	Green, pillar, marked "T59".	Year round.
429.2	<i>Dublin Shore East light T60</i>	44 16 13.3 064 21 14.7	Fl R 4s	Red, pillar, marked "T60".	Year round.
430	<i>Bull Rock light buoy T63</i>	Entrance to La Have River. 44 16 22.4 064 20 54.8	Q G 1s	Green, pillar, marked "T63".	Year round. Audible signal: Bell
431.5 H3710.5	Krout Point	44 17 24.9 064 20 47.1	Fl R 5s	4	Square skeleton tower.	Year round. Flash 1 s; eclipse 4 s.
432 H3708	West Ironbound Island	On S. side of island, entrance to LaHave River. 44 13 43.7 064 16 28.0	LFl W 12s	23.6	8	Square skeleton tower, white rectangular daymark with red horizontal band. 10.0	Year round. Flash 2 s; eclipse 10 s.
432.2	<i>West Ironbound light and bell buoy T52</i>	SW. of Ironbound breaker. 44 13 24.9 064 17 12.8	Fl R 4s	Red, pillar, marked "T52".	Year round. Audible signal: Bell

List of Lights, Buoys and Fog Signals – Atlantic Coast

No. ----- Intl No.	Name ----- RACON	Location ----- Latitude N. Longitude W.	Light Characteristics	Focal Height Above Water (m)	Nominal Range (NM)	Description ----- Height of Structure Above Ground Level (m)	Remarks ----- Audible Signals ----- AIS
NOVA SCOTIA, SOUTHEAST COAST							
433	Pollock Shoal light and bell buoy TC52	S. of Shoal. 44 14 38.3 064 14 28.7	Fl R 4s	Red, pillar, marked "TC52".	Year round. Audible signal: Bell
434	Cross Island light and whistle buoy E50	44 17 28.9 064 11 01.3	Fl R 4s	Red, pillar, marked "E50".	Year round. Audible signal: Whistle
435 H3700	Feltzen South	At end of breakwater. 44 19 47.6 064 16 49.7	Fl G 6s	6.1	4	Cylindrical mast. 3.6	Year round. Flash 1 s; eclipse 5 s.
435.5	Lunenburg Bay light buoy EF	44 19 56.5 064 13 22.6	Fl(2) W 5s	Black-red-black, spar, marked "EF".	Year round. Flash 0.4 s; eclipse 0.6 s; flash 0.4 s; eclipse 3.6 s.
436	Sculpin Shoal light and bell buoy E52	SW. of shoal. 44 20 08.3 064 15 13.3	Fl R 4s	Red, pillar, marked "E52".	Year round. Audible signal: Bell
437	Long Shoal light buoy E57	E. of shoal. 44 21 13.7 064 17 18.1	Fl G 4s	Green, pillar, marked "E57".	Year round.
437.5	Lower South Cove Entrance light buoy EM55	44 20 43.1 064 18 50.3	Fl G 4s	Green, spar, marked "EM55".	Year round.
438 H3702	Battery Point Breakwater	Near outer end of breakwater. 44 21 37.0 064 17 46.7	Iso R 4s	7.5	White square tower with red upper portion. 8.0	Year round. Operates 24 h. Fog Horn Blast 2 s; sil. 18 s. Mariners requiring the operation of the fog signal will have to press the button of the VHF radio five (5) consecutive times at 1 second intervals on channel 65A (156,275 MHz). The signal will be in operation for 30 minutes. After this delay, the same operation must be repeated.
439	Lunenburg Harbour Outer light buoy E64	44 21 54.6 064 18 02.1	Fl R 4s	Red, spar, marked "E64".	Year round.
439.8	Lunenburg Harbour Marine Railway light buoy E66	SW. of marine railway wharf. 44 22 19.3 064 18 16.5	Q R 1s	Red, spar, marked "E66".	Year round.
441	Lunenburg Harbour light buoy E77	44 22 28.0 064 18 37.6	Fl G 4s	Green, spar, marked "E77".	Year round.
442	Lunenburg bifurcation light and bell buoy EDA	N. entrance to Lunenburg Bay. 44 20 21.7 064 11 10.9	Fl(2+1) G 6s	Green-red-green, pillar, marked "EDA".	Year round. Audible signal: Bell
443 H3698	Cross Island	E. point of island. 44 18 43.7 064 10 06.4	Fl W 10s	24.9	10	White cylindrical tower with red top. 8.7	Year round. Flash 1 s; eclipse 9 s.

List of Lights, Buoys and Fog Signals – Atlantic Coast

No. ----- Intl No.	Name ----- RACON	Location ----- Latitude N. Longitude W.	Light Characteristics	Focal Height Above Water (m)	Nominal Range (NM)	Description ----- Height of Structure Above Ground Level (m)	Remarks ----- Audible Signals ----- AIS
--------------------------	------------------------	--	--------------------------	--	--------------------------	--	---

NOVA SCOTIA, SOUTHEAST COAST

444 H3699	East Point Island	44 20 59.2 064 12 15.0	LFI G 6s	9.6	6	Square skeleton tower, red and white square daymark with green square in centre. 6.9	Year round. Flash 2 s; eclipse 4 s.
Mahone Bay							
445	Tanner Pass light and whistle buoy EA51	Tanner Pass entrance. 44 22 01.9 064 11 32.6	FI G 4s	Green, pillar, marked "EA51".	Year round. Audible signal: Whistle
446 H3694	Gunning Point Island (Tanner Island)	On E. end of island. 44 22 01.5 064 12 04.3	LFI W 6s	6	Skeleton tower, red and white daymark.	Year round. Flash 2 s; eclipse 4 s.
447	Middle Ledge light and whistle buoy M52	W. of ledge. 44 22 31.2 064 07 52.8	FI R 4s	Red, pillar, marked "M52".	Year round. Audible signal: Whistle
448	Bull Rock light and bell buoy M54	S. of rock. 44 24 30.4 064 09 23.7	FI R 4s	Red, pillar, marked "M54".	Year round. Audible signal: Bell
448.5	Chockle Cap light and bell buoy M55	44 24 36.4 064 12 39.7	FI G 4s	Green, pillar, marked "M55".	Year round. Audible signal: Bell
449.25	Hobsons Island North Cardinal light buoy ME	44 25 19.0 064 13 38.6	Q W 1s	Black-yellow, pillar, marked "ME".	Year round.
449.4	Middle Patch light buoy M	44 25 27.4 064 15 05.4	FI(2) W 5s	Black-red-black, can, marked "M".	Year round. Flash 0.4 s; eclipse 0.6 s; flash 0.4 s; eclipse 3.6 s.
449.5	Southwest Ledge light buoy M60	S. of ledge. 44 25 47.4 064 16 18.7	FI R 4s	Red, spar, marked "M60".	Year round.
450	Covey Ledge light buoy M61	NE. of ledge. 44 25 48.4 064 17 30.7	FI G 4s	Green, spar, marked "M61".	Year round.
450.8	Westhaver Island light buoy M67	SE. of island. 44 26 18.4 064 20 33.7	Q G 1s	Green, spar, marked "M67".	Year round.
451 H3688	Westhaver Island	Mahone Harbour entrance. 44 26 09.8 064 20 15.3	FI W 5s	9.6	7	White pyramidal tower with red top. 7.6	Year round. Flash 1 s; eclipse 4 s.
452.5	Mahone Harbour light buoy M72	44 26 43.3 064 21 59.3	FI R 4s	Red, pillar, marked "M72".	Year round.
452.7	East Shoal light and bell buoy MC55	44 27 12.4 064 12 36.7	FI G 4s	Green, pillar, marked "MC55".	Year round. Audible signal: Bell

List of Lights, Buoys and Fog Signals – Atlantic Coast

No. ----- Intl No.	Name ----- RACON	Location ----- Latitude N. Longitude W.	Light Characteristics	Focal Height Above Water (m)	Nominal Range (NM)	Description ----- Height of Structure Above Ground Level (m)	Remarks ----- Audible Signals ----- AIS
NOVA SCOTIA, SOUTHEAST COAST							
453 H3682	Kaulback Island front range light	N. end of island. 44 28 11.3 064 16 53.3	F W	10.2	12	White square tower with red top and red vertical stripe. 6.1	Year round. Operates 24 h.
454 H3682.1	Kaulback Island rear range light	44 28 11.2 064 16 58.4 268°03' 113.1 m from front.	F W	19.8	12	White square tower with red top and red vertical stripe. 6.1	Year round.
454.2	<i>Martins Point light Buoy MS56</i>	44 28 53.2 064 17 37.4	FI R 4s	<i>Red, spar, marked "MS56".</i>	<i>Seasonal.</i>
454.4	<i>Beacon Shoal light buoy MS57</i>	44 28 50.0 064 17 49.7	Q G 1s	<i>Green, spar, marked "MS57".</i>	<i>Seasonal.</i>
454.5 H3683	Western Shore Breakwater	On seaward end of breakwater. 44 31 21.5 064 18 16.1	LFI G 6s	4.0	3	Square skeleton tower, green, white and black square daymark. 3.6	Year round. Flash 2 s; eclipse 4 s.
454.51 H3683.2	Western Shore Inner	44 31 20.9 064 18 18.0	LFI R 6s	5.2	3	Cylindrical mast with enclosed lower portion. 3.6	Year round. Flash 2 s; eclipse 4 s.
454.55	<i>Little Fish Island light buoy MC70</i>	<i>N. of island. 44 32 12.9 064 15 02.7</i>	<i>FI R 4s</i>	<i>.....</i>	<i>.....</i>	<i>Red, spar, marked "MC70".</i>	<i>Year round.</i>
454.6	<i>Dauphinee Point light buoy MC66</i>	<i>S. of point. 44 32 09.4 064 15 39.7</i>	<i>FI R 4s</i>	<i>.....</i>	<i>.....</i>	<i>Red, spar, marked "MC66".</i>	<i>Year round.</i>
454.62	<i>Gold Ledges light buoy MU57</i>	44 32 26.4 064 18 28.7	FI G 4s	<i>Green, spar, marked "MU57".</i>	<i>Year round.</i>
454.63	<i>Middle Rock light buoy MU53</i>	44 32 09.4 064 17 25.7	Q G 1s	<i>Green, spar, marked "MU53".</i>	<i>Year round.</i>
454.65	<i>South Gooseberry Shoal bifurcation light buoy MCA</i>	<i>Off S. end of shoal. 44 31 16.9 064 15 58.7</i>	<i>FI(2+1) R 6s</i>	<i>.....</i>	<i>.....</i>	<i>Red-green-red, pillar, marked "MCA".</i>	<i>Year round.</i>
454.7	<i>Sheep Ledge light and bell buoy MC59</i>	44 30 06.4 064 15 51.7	FI G 4s	<i>Green, pillar, marked "MC59".</i>	<i>Year round. Audible signal: Bell</i>
455	<i>Lynch Shoal light and bell buoy MA57</i>	<i>SE. of Quaker Island. 44 30 30.4 064 12 48.7</i>	FI G 4s	<i>Green, pillar, marked "MA57".</i>	<i>Year round. Audible signal: Bell</i>
456 H3680	Quaker Island	Off Chester Harbour. 44 30 53.7 064 13 57.2	LFI W 6s	30.8	4	White pyramidal tower with red at top. 6.2	Year round. Flash 2 s; eclipse 4 s.
457	<i>Coachman Ledge light and whistle buoy MA55</i>	<i>N. of ledge. 44 30 01.4 064 10 36.7</i>	<i>FI G 4s</i>	<i>.....</i>	<i>.....</i>	<i>Green, pillar, marked "MA55".</i>	<i>Year round. Audible signal: Whistle</i>
457.2	<i>Shoal Cove light buoy MK53</i>	44 29 51.9 064 07 21.2	FI G 4s	<i>Green, spar, marked "MK53".</i>	<i>Year round.</i>

List of Lights, Buoys and Fog Signals – Atlantic Coast

No. ----- Intl No.	Name ----- RACON	Location ----- Latitude N. Longitude W.	Light Characteristics	Focal Height Above Water (m)	Nominal Range (NM)	Description ----- Height of Structure Above Ground Level (m)	Remarks ----- Audible Signals ----- AIS
NOVA SCOTIA, SOUTHEAST COAST							
457.4	Blandford light buoy MK58	44 29 44.9 064 06 42.4	Fl R 4s	Red, spar, marked "MK58".	Year round.
459	Blandford light and bell buoy MK52	NW. of Blandford Shoal. 44 29 43.4 064 08 14.7	Fl R 4s	Red, pillar, marked "MK52".	Year round. Audible signal: Bell
460	Big Tancook Island light and bell buoy MN51	N. of island. 44 28 19.4 064 10 45.7	Fl G 4s	Green, pillar, marked "MN51".	Year round. Audible signal: Bell
461 H3677	Little Tancook Island Wharf Outer	On outer end of wharf. 44 28 18.2 064 08 30.7	LFl W 6s	7.1	5	Square skeleton tower, red and white rectangular daymark.	Year round. Flash 2 s; eclipse 4 s.
463 H3676	Big Tancook Island	On outer end of wharf, Northwest Cove. 44 27 52.3 064 10 17.9	Fl G 4s	4	Pipe Swing Pole, green, white and black square daymark. 6.1	Year round. Flash 1 s; eclipse 3 s.
464	Reef Point light and whistle buoy MD55	E. of point. 44 27 25.4 064 08 36.7	Fl G 4s	Green, pillar, marked "MD55".	Year round. Audible signal: Whistle
466	New Harbour light and bell buoy MA	W. of New Harbour Point. 44 28 14.4 064 06 48.7	Mo(A) W 6s	Red-white, pillar, marked "MA".	Year round. Audible signal: Bell
467 H3674	New Harbour	On S. side of entrance. 44 28 21.3 064 05 31.9	Fl R 5s	4	Cylindrical mast. 3.6	Year round. Flash 1 s; eclipse 4 s.
468	West Head light and bell buoy MD53	N. of East Ironbound Island. 44 26 44.4 064 06 27.7	Fl G 4s	Green, pillar, marked "MD53".	Year round. Audible signal: Bell
469 H3672	East Ironbound Island	Near centre of island. 44 26 22.4 064 04 59.7	Iso W 6s	44.5	13	White rectangular tower with red top. 13.9	Year round.
470	East Ironbound South light and bell buoy MC52	S. of island. 44 25 37.4 064 05 08.7	Fl R 4s	Red, pillar, marked "MC52".	Year round. Audible signal: Bell
471 H3670	Pearl Island	Off St. Margaret's and Mahone Bays. 44 22 57.2 064 02 54.0	Fl W 10s	19.0	8	White square tower. 11.6	Year round. Flash 0.5 s; eclipse 9.5 s.
473	Northeast Shoal light and bell buoy DA51	E. of shoal. 44 24 59.4 064 01 19.7	Fl G 4s	Green, pillar, marked "DA51".	Year round. Audible signal: Bell
474	Horseshoe Ledge light and whistle buoy DA53	Off S. end of ledge. 44 28 15.3 063 58 21.8	Fl G 4s	Green, pillar, marked "DA53".	Year round. Audible signal: Whistle

List of Lights, Buoys and Fog Signals – Atlantic Coast

No. ----- Intl No.	Name ----- RACON	Location ----- Latitude N. Longitude W.	Light Characteristics	Focal Height Above Water (m)	Nominal Range (NM)	Description ----- Height of Structure Above Ground Level (m)	Remarks ----- Audible Signals ----- AIS	
NOVA SCOTIA, SOUTHEAST COAST								
475	Seal Ledge light and whistle buoy MA54	E. of East Ironbound Island. 44 27 19.4 064 02 36.7	Fl R 4s	Red, pillar, marked "MA54".	Year round. Audible signal: Whistle	
476	Aspotogan light and bell buoy DF	SE. approach to Aspotogan Harbour. 44 29 27.3 064 00 13.8	Mo(A) W 6s	Red-white, pillar, marked "DF".	Year round. Audible signal: Bell	
St. Margarets Bay								
477.2	Horse Island light buoy DP51	St. Margaret's Bay. 44 32 05.3 064 00 38.8	Fl G 4s	Green, pillar, marked "DP51".	Year round.	
477.4	Northwest Cove light buoy DP54	E. of wharf. 44 32 01.0 064 01 20.0	Fl R 4s	Red, spar, marked "DP54".	Year round.	
478 H3665	Hubbards Cove	On Green Point, W. side of entrance. 44 37 16.1 064 03 14.6	Fl G 6s	11.5	6	Square skeleton tower, green and white rectangular daymark. 6.9	Year round. Flash 1 s; eclipse 5 s.	
478.2	Fox Cove Wharf Light	44 36 49.4 064 03 28.3	Q W 1s	3	Pipe swing pole, black, white and black triangular daymark.	Year round. Operates 24 h.	
478.4	Mill Cove Wharf Light	44 34 53.7 064 03 16.0	Fl G 4s	3	Pipe Swing Pole, green, white and black square daymark.	Year round. Operates 24 h. Flash 1 s; eclipse 3 s.	
479	Slaughenwhite Ledge light buoy DY52	SW. of ledge. 44 37 01.7 064 02 21.8	Fl R 4s	Red, spar, marked "DY52".	Year round.	
479.01	Slaughenwhite Ledge light buoy DY54	44 37 24.4 064 02 43.7	Fl R 4s	Red, spar, marked "DY54".	Year round.	
480 H3664	Croucher Island	44 38 23.3 063 57 29.7	LFl W 12s	29.2	6	Triangular skeleton mast, red and white rectangular daymark. 11.3	Year round. Flash 2 s; eclipse 10 s.	
480.1	Redmond Cove light buoy DV52	44 36 02.3 063 56 11.7	Fl R 4s	Red, spar, marked "DV52".	Year round.	
480.2	Ringdove Shoal light and bell buoy DA58	W. of shoal. 44 35 45.3 063 58 03.8	Fl R 4s	Red, pillar, marked "DA58".	Year round. Audible signal: Bell	
481 H3667	Northwest Cove Wharf	On outer end of wharf. 44 32 01.2 064 01 24.8	LFl R 6s	4.7	4	Pipe swing pole. 3.7	Year round. Flash 2 s; eclipse 4 s.	
482 H3663	Paddy Head Island Light	On SE. extremity of island. 44 31 20.3 063 56 45.7	F W	11.0	9	White square tower with red upper portion. 9.4	Year round.

List of Lights, Buoys and Fog Signals – Atlantic Coast

No. ----- Intl No.	Name ----- RACON	Location ----- Latitude N. Longitude W.	Light Characteristics	Focal Height Above Water (m)	Nominal Range (NM)	Description ----- Height of Structure Above Ground Level (m)	Remarks ----- Audible Signals ----- AIS
NOVA SCOTIA, SOUTHEAST COAST							
484	Crawford Ledge light and bell buoy DA56	W. extremity of shoal. 44 30 46.3 063 57 25.7	Fl R 4s	Red, pillar, marked "DA56". 3.7	Year round. Audible signal: Bell
486 H3661	Peggy's Cove Wharf	On outer end of wharf. 44 29 36.4 063 54 59.6	Fl G 3s	4.6	4	Pipe Swing Pole, green, white and black square daymark. 3.7	Year round. Flash 1 s; eclipse 2 s.
487 H3660	Peggy's Point	E. side of entrance to St. Margaret's Bay. 44 29 30.4 063 55 07.2	Fl R 5s	22.0	10	White octagonal tower with red top. 13.2	Year round. Operates 24 h. Flash 1.5 s; eclipse 3.5 s. Visible 290°-136°.
487.5 H3659	Dover West	On wharf. 44 29 34.7 063 52 05.4	LFl G 6s	5.2	4	Pipe swing pole. 3.7	Year round. Flash 2 s; eclipse 4 s.
488 H3658	West Dover Light	On S. end of Callahan Island. 44 29 24.3 063 51 40.7	Fl(2+1) G 6s	15.2	4	Pipe swing pole, red and white rectangular daymark with red diamond and green square in the centre. 6.1	Year round.
488.5	Flemming Ledge light buoy AT60	44 29 09.2 063 51 15.9	Fl R 4s	Red, spar, marked "AT60". 3.7	Year round.
489 H3657	East Dover Wharf	44 29 44.6 063 50 41.6	LFl R 6s	4.5	4	Pipe swing pole, red and white triangular daymark. 3.7	Year round. Flash 2 s; eclipse 4 s.
489.5	White Island light buoy AY53	Off Island. 44 29 16.8 063 49 58.8	Fl G 4s	Green, pillar, marked "AY53". 3.7	Year round.
490	Dover Castle light buoy AT	S. of Dover Island. 44 26 42.5 063 53 33.5	Mo(A) W 6s	Red-white, pillar, marked "AT". 3.7	Year round.
491	Shag Bay Breakers light buoy AT50	Off SW. extremity of shoal. 44 28 03.3 063 50 10.7	Fl R 4s	Red, pillar, marked "AT50". 3.7	Year round. Audible signal: Bell
492 H3655	Prospect Wharf	On outer end of public wharf. 44 28 07.9 063 47 03.3	Fl G 4s	4.5	4	Pipe swing pole. 3.7	Year round. Flash 1 s; eclipse 3 s.
494	Prospect light and bell buoy AM62	SE. of Saul Point. 44 27 53.3 063 46 33.7	Fl R 4s	Red, pillar, marked "AM62". 3.7	Year round. Audible signal: Bell
494.01	Saul Island light buoy AM64	Terence Bay. 44 28 03.3 063 46 49.8	Fl R 4s	Red, spar, marked "AM64". 3.7	Year round.
495 H3652	Betty Island	On Brig Point. 44 26 19.7 063 46 00.4	LFl W 6s	19.2	13	Square skeleton tower, white rectangular daymark with red horizontal band. 3.7	Year round. Flash 2 s; eclipse 4 s. Visible from all points of marine approach from the S.

List of Lights, Buoys and Fog Signals – Atlantic Coast

No. ----- Intl No.	Name ----- RACON	Location ----- Latitude N. Longitude W.	Light Characteristics	Focal Height Above Water (m)	Nominal Range (NM)	Description ----- Height of Structure Above Ground Level (m)	Remarks ----- Audible Signals ----- AIS
--------------------------	------------------------	--	--------------------------	--	--------------------------	--	---

NOVA SCOTIA, SOUTHEAST COAST

496	Grampus Rock light and bell buoy AM52	Off the rock. 44 25 31.4 063 43 39.1	Fl R 4s	Red, pillar, marked "AM52".	Year round. Audible signal: Bell
496.5 H3651.4	Lower Prospect	On wharf. 44 27 03.4 063 43 32.1	Fl W 4s	3.0	4	Pipe swing pole. 3.7	Year round. Flash 1 s; eclipse 3 s.
497	Terence Bay light and bell buoy AD	44 26 53.5 063 40 36.8	Mo(A) W 6s	Red-white, pillar, marked "AD".	Year round. Audible signal: Bell
498 H3650	Terence Bay	On Tennant Point. 44 27 36.6 063 42 20.4	LFl W 6s	8	White pyramid tower with red top.	Year round. Flash 2 s; eclipse 4 s.
498.2	Tennant Point light buoy AD56	E. of Terence Rock. 44 27 23.2 063 41 19.3	Fl R 4s	Red, spar, marked "AD56".	Year round.
499 H3651	Terence Bay Wharf	On outer end of wharf. 44 28 04.4 063 42 52.2	LFl W 6s	4.7	4	Pipe swing pole. 3.7	Year round. Flash 2 s; eclipse 4 s.

Halifax Harbour and Approaches

499.9	Stapleton Rock West Cardinal light buoy AAB	44 27 32.9 063 39 33.7	Q(9) W 15s	Yellow-black-yellow, spar, marked "AAB".	Year round.
501.1	Fawson Rock light buoy AA57	44 28 01.9 063 38 15.1	Fl G 4s	Green, spar, marked "AA57".	Year round.
501.2	Pennant Harbour light buoy AA55	44 27 48.3 063 38 28.2	Fl G 4s	Green, can, marked "AA55".	Year round.
501.3	Pennant Harbour light buoy AA54	44 27 38.0 063 38 30.8	Fl R 4s	Red, conical, marked "AA54".	Year round.
501.4	Pennant Harbour bifurcation light buoy AAA	44 27 09.9 063 38 55.9	Fl(2+1) G 6s	Green-red-green, spar, marked "AAA".	Year round.
501.5	Pennant Harbour light buoy AA53	44 26 48.2 063 39 23.6	Fl G 4s	Green, spar, marked "AA53".	Year round.
501.6	Pennant Harbour light buoy AA51	44 26 32.6 063 39 48.0	Fl G 4s	Green, spar, marked "AA51".	Year round.
501.7	Pennant Harbour light buoy AA52	44 26 10.3 063 39 36.6	Fl R 4s	Red, spar, marked "AA52".	Year round.
502	Pennant Point light and bell buoy AA50	SW. of point. 44 25 33.3 063 39 07.0	Fl R 4s	Red, pillar, marked "AA50".	Year round. Audible signal: Bell
503	Smithson Rock light and bell buoy HE2	SW. of the rock. 44 24 16.4 063 36 59.4	Fl R 4s	Red, pillar, marked "HE2".	Year round. Audible signal: Bell

List of Lights, Buoys and Fog Signals – Atlantic Coast

No. ----- Intl No.	Name ----- RACON	Location ----- Latitude N. Longitude W.	Light Characteristics	Focal Height Above Water (m)	Nominal Range (NM)	Description ----- Height of Structure Above Ground Level (m)	Remarks ----- Audible Signals ----- AIS
NOVA SCOTIA, SOUTHEAST COAST							
503.03	Sambro light buoy HE7	44 26 14.5 063 35 52.8	Fl G 4s	Green, spar, marked "HE7".	Year round.
503.05	Sambro light buoy HE10	44 26 51.0 063 34 50.5	Fl R 4s	Red, spar, marked "HE10".	Year round.
503.1	Nick Shoal light buoy HE16	Sambro. 44 27 40.6 063 32 49.6	Fl R 4s	Red, spar, marked "HE16".	Year round.
503.11	Morris Point light buoy HE17	Sambro. 44 28 00.6 063 32 40.9	Fl G 4s	Green, spar, marked "HE17".	Year round.
503.5	Thrumcap Rock light buoy HE3	44 25 25.0 063 36 41.6	Fl G 4s	Green, pillar, marked "HE3".	Year round.
503.52	Sambro Red Spar light buoy HE6	44 25 17.1 063 36 15.6	Fl R 4s	Red, spar, marked "HE6".	Year round.
504	Inner Sambro light and bell buoy HS6	SW. of W. end of Inner Sambro Island. 44 27 05.0 063 35 48.0	Q R 1s	Red, pillar, marked "HS6".	Year round. Audible signal: Bell
504.01	Inner Sambro Island light buoy HA2	Sambro. 44 27 22.0 063 35 09.0	Fl R 4s	Red, pillar, marked "HA2".	Year round.
504.02	Cowley Rock bifurcation light buoy HSA	Sambro. 44 27 32.0 063 35 46.5	F(2+1) R 6s	Red-green-red, spar, marked "HSA".	Year round.
504.5	Cronie Reef light buoy HS12	44 28 21.4 063 35 35.3	Fl R 4s	Red, spar, marked "HS12".	Year round.
504.7	Bull Point light buoy HS13	44 28 19.0 063 35 42.8	Fl G 4s	Green, spar, marked "HS13".	Year round.
505 H3644	Sambro Harbour	On extremity of Bull Point. 44 28 30.0 063 35 45.5	F G	10.5	7 White pyramid tower with red top. 8.4	Year round.
505.1	Big Island light buoy HR2	44 28 41.3 063 35 22.1	Q R 1s	Red, conical, marked "HR2".	Year round.
505.2	Big Island light buoy HR4	44 28 47.8 063 35 13.4	Fl R 4s	Red, conical, marked "HR4".	Year round.
505.3	Big Island light buoy HR5	44 28 51.2 063 35 10.7	Fl G 4s	Green, can, marked "HR5".	Year round.
505.8	Sambro light buoy HS19	44 28 37.0 063 35 50.3	Fl G 4s	Green, spar, marked "HS19".	Year round.
505.81	Sambro Harbour light buoy HS20	44 28 38.0 063 35 45.5	Fl R 4s	Red, spar, marked "HS20".	Year round.
505.82	Sambro Harbour light buoy HS22	44 28 41.0 063 35 49.0	Fl R 4s	Red, spar, marked "HS22".	Year round.

List of Lights, Buoys and Fog Signals – Atlantic Coast

No. ----- Intl No.	Name ----- RACON	Location ----- Latitude N. Longitude W.	Light Characteristics	Focal Height Above Water (m)	Nominal Range (NM)	Description ----- Height of Structure Above Ground Level (m)	Remarks ----- Audible Signals ----- AIS
NOVA SCOTIA, SOUTHEAST COAST							
505.83	Sambro Harbour light buoy HS24	44 28 43.1 063 35 53.0	Fl R 4s	Red, spar, marked "HS24".	Year round.
506.6	Lobster Claw light buoy HE13	S. of Lobster Claw. 44 27 18.0 063 34 06.5	Fl G 4s	Green, pillar, marked "HE13".	Year round.
507 H3632	Sambro	Centre of island. 44 26 12.0 063 33 48.0	Fl W 6s	42.7	23	White octagonal tower with red horizontal bands. 20.7	Year round. Operates 24 h. Flash 1 s; eclipse 5 s.
508	Sambro Harbour light and whistle buoy HS	S. of Southwest Breaker. 44 24 30.0 063 33 36.5	Mo(A) W 6s	Red-white, pillar, marked "HS".	Year round. Audible signal: Whistle
508.2	Pennel Shoal light buoy HS2	Sambro. 44 25 15.8 063 33 49.6	Fl R 4s	Red, spar, marked "HS2".	Year round.
508.22	Shag Rock light buoy HS2/2	Sambro. 44 25 38.5 063 34 16.3	Fl R 4s	Red, conical, marked "HS2/2".	Year round.
508.4	Sambro Island West light buoy HS4	Sambro. 44 26 00.0 063 34 42.0	Fl R 4s	Red, spar, marked "HS4".	Year round.
508.42	Four Fathom Shoal light buoy HS4/2	Sambro. 44 26 23.6 063 35 08.0	Q R 1s	Red, conical, marked "HS4/2".	Year round.
508.44	Fairweather Rock East Cardinal light buoy HSE	Sambro. 44 26 44.0 063 35 42.4	Q(3) W 10s	Black-yellow-black, can, marked "HSE".	Year round.
509	Sisters light and bell buoy HD3	S. of The Sisters. 44 26 14.0 063 31 26.0	Fl G 4s	Green, pillar, marked "HD3".	Year round. Audible signal: Bell
509.5	Halifax Bravo light buoy HB	44 26 37.0 063 27 33.0	Mo(A) W 6s	Red-white, pillar, marked "HB".	Year round.
510	Halifax Alpha light and whistle buoy HA	44 21 45.0 063 24 15.0	Mo(A) W 6s	Red-white, pillar, marked "HA".	Year round. Audible signal: Whistle
511	Ketch Harbour light buoy HE19	Ketch Harbour entrance. 44 28 19.6 063 32 16.0	Fl G 4s	Green, pillar, marked "HE19".	Year round.
512	Bell Rock light buoy HD5	E. of Ketch Head. 44 29 00.0 063 31 03.0	Fl G 4s	Green, pillar, marked "HD5".	Year round.
512.5	Duncan Reef light buoy H1	44 29 36.0 063 30 34.0	Q G 1s	Green, pillar, marked "H1".	Year round.
513 H3600	Chebucto Head Racon Z (- - -) X Band	On summit. 44 30 26.6 063 31 21.8	Fl W 20s	47.8	10	White octagonal tower with red top. 12.9	Year round. Operates 24 h. Flash 0.5 s; eclipse 19.5 s.

List of Lights, Buoys and Fog Signals – Atlantic Coast

No. ----- Intl No.	Name ----- RACON	Location ----- Latitude N. Longitude W.	Light Characteristics	Focal Height Above Water (m)	Nominal Range (NM)	Description ----- Height of Structure Above Ground Level (m)	Remarks ----- Audible Signals ----- AIS
NOVA SCOTIA, SOUTHEAST COAST							
514	Halifax Charlie light and bell buoy HC	44 30 06.2 063 29 57.7	Mo(A) W 6s	Red-white, pillar, marked "HC".	Year round. Audible signal: Bell
515	Navy West Cautionary light and whistle buoy HNWC	44 32 41.0 063 25 15.0	Fl Y 4s	Yellow, pillar, marked "HNWC".	Year round. Audible signal: Whistle
516	Inner Automatic light buoy H4	NE. of Chebucto Head. 44 31 39.5 063 30 03.6	Fl R 4s	Red, pillar, marked "H4".	Year round.
517	Bear Cove light and bell buoy H6 Racon N (-.) X Band	NE. of cove. 44 32 36.3 063 31 19.6	Q R 1s	Red, pillar, marked "H6".	Year round. Audible signal: Bell Physical AIS AtoN MMSI: 993161063
517.5	Bear Cove bifurcation light buoy HK	NW. of shoal. 44 32 41.2 063 32 00.6	Fl(2+1) G 6s	Green-red-green, pillar, marked "HK".	Year round.
518	Neverfail Shoal light and bell buoy H8	44 33 15.5 063 31 27.6	Fl R 4s	Red, pillar, marked "H8".	Year round. Audible signal: Bell
519	Lichfield Shoal light and whistle buoy H7	E. end of shoal. 44 33 22.5 063 31 59.5	Fl G 4s	Green, pillar, marked "H7".	Year round. Audible signal: Whistle
519.5	Neverfail Shoal North light buoy HN7	44 33 30.8 063 31 03.8	Fl G 4s	Green, pillar, marked "HN7".	Year round.
520	Thrumcap light and bell buoy HN6	S. of Thrumcap Shoal. 44 33 49.3 063 30 11.6	Fl R 4s	Red, pillar, marked "HN6".	Year round. Audible signal: Bell
521	Herring Cove light and bell buoy HM1	SE. of Tribune Head. 44 33 52.2 063 32 54.7	Fl G 4s	Green, pillar, marked "HM1".	Year round. Audible signal: Bell
521.3	Herring Cove light buoy HM4	Near breakwater. 44 34 09.2 063 33 25.8	Q R 1s	Red, spar, marked "HM4".	Year round. Operates 24 h.
521.5	Halifax Harbour Smart buoy	44 33 21.3 063 32 38.7	Fl(5) Y 20s	Yellow, ODAS.	Year round. Operates 24 h.
522 H3604	Herring Cove Light	Tribune Head. 44 34 00.7 063 33 19.8	F G	19.5	6 Triangular skeleton tower, red and white rectangular daymark. 10.3	Year round.
523	Mars Rock light buoy H9	Off SE. side of rock. 44 34 19.1 063 32 11.3	Q G 1s	Green, pillar, marked "H9".	Year round.
523.1	Mars Rock North light buoy H11	44 34 58.8 063 32 15.1	Fl G 4s	Green, pillar, marked "H11".	Year round. Operates 24 h.

List of Lights, Buoys and Fog Signals – Atlantic Coast

No. ----- Intl No.	Name ----- RACON	Location ----- Latitude N. Longitude W.	Light Characteristics	Focal Height Above Water (m)	Nominal Range (NM)	Description ----- Height of Structure Above Ground Level (m)	Remarks ----- Audible Signals ----- AIS
NOVA SCOTIA, SOUTHEAST COAST							
523.4 H3602	Sandwich Point front range light	44 34 56.6 063 32 56.7	F G	38.4	Triangular skeleton tower, white daymark with red vertical stripe. 6.1	Year round. Operates 24 h.
523.5 H3602.1	Sandwich Point rear range light	44 35 11.4 063 33 05.7 336°29' 489.5 m from front.	Oc G 10s	50.8	18	Triangular skeleton tower, white daymark with red vertical stripe.	Year round. Operates 24 h. Flash 8 s; eclipse 2 s.
524	Lighthouse Bank light and bell buoy H12	W. of bank. 44 35 36.3 063 31 59.5	Fl R 4s	Red, pillar, marked "H12".	Year round. Audible signal: Bell
524.3	Outer Middle Ground West Cardinal light buoy HKB	44 35 50.0 063 32 33.8	Q(9) W 15s	Yellow-black-yellow, pillar, marked "HKB".	Year round. Operates 24 h.
525	Outer Middle Ground bifurcation light buoy HAC	N. of Lighthouse bank. 44 35 54.8 063 32 24.0	Fl(2+1) G 6s	Green-red-green, pillar, marked "HAC".	Year round.
525.2	Southeast Middle Ground light buoy H15	44 36 11.3 063 32 33.6	Fl G 4s	Green, pillar, marked "H15".	Year round.
526	Maugher Beach light buoy H14	SW. of beach. 44 35 58.3 063 32 12.6	Q R 1s	Red, pillar, marked "H14".	Year round.
526.5	Middle Ground South Cardinal light buoy HKC	44 36 07.6 063 32 52.0	Q(6) + LFI W 15s	Yellow-black, pillar, marked "HKC".	Year round. Operates 24 h.
526.6	Fergusons Cove light buoy HK17	44 36 30.1 063 33 22.0	Fl G 4s	Green, pillar, marked "HK17".	Year round. Operates 24 h.
526.7	Middle Ground West Cardinal light buoy HKD	44 36 35.4 063 32 56.3	Q(9) W 15s	Yellow-black-yellow, pillar, marked "HKD".	Year round. Operates 24 h.
527 H3607	Maugher Beach	Near W. end of beach. 44 36 08.2 063 32 00.9	Iso W 4s	17.4	10	White octagonal tower with red top. 17.8	Year round.
527.5	Northeast Middle Ground light buoy H17	44 36 41.2 063 32 49.6	Fl G 4s	Green, pillar, marked "H17".	Year round. Operates 24 h.
528 H3606	Halifax Harbour Middle front range light	NW. end of McNabs Island. 44 36 50.5 063 32 11.0	F R	18.0	18	Tripod skeleton tower, white daymark with red vertical stripe.	Year round. Operates 24 h.
528.1 H3606.1	Halifax Harbour Middle rear range light	44 37 01.0 063 32 12.1 356°13' 322.0 m from front.	Oc R 10s	29.0	18	Triangular skeleton tower, white daymark with red vertical stripe. 21.9	Year round. Operates 24 h. Flash 8 s; eclipse 2 s.

List of Lights, Buoys and Fog Signals – Atlantic Coast

No. ----- Intl No.	Name ----- RACON	Location ----- Latitude N. Longitude W.	Light Characteristics	Focal Height Above Water (m)	Nominal Range (NM)	Description ----- Height of Structure Above Ground Level (m)	Remarks ----- Audible Signals ----- AIS	
NOVA SCOTIA, SOUTHEAST COAST								
529	Pleasant Shoal light buoy H19	Off E. extremity of shoal. 44 37 00.2 063 33 06.4	Q G 1s	Green, pillar, marked "H19".	Year round. Audible signal: Bell	
531	Hens and Chickens light buoy HQ2	SE. of Hens and Chickens. 44 36 50.0 063 33 44.0	Fl R 4s	Red, spar, marked "HQ2".	Year round.	
532	Purcells Cove light buoy HQ1	E. of cove. 44 36 41.9 063 33 56.9	Fl G 4s	Green, spar, marked "HQ1".	Year round.	
532.5	Northwest Arm light buoy HQD	44 37 02.6 063 34 22.7	Fl(2) W 5s	Black-red-black, spar, marked "HQD".	Year round. Flash 0.4 s; eclipse 0.6 s; flash 0.4 s; eclipse 3.6 s.	
533	Imperial Oil Wharf No. 1 light buoy HP22	44 38 02.3 063 31 56.6	Fl R 4s	Red, spar, marked "HP22".	Year round.	
534	Eastern Passage light buoy HP21	44 37 46.5 063 31 56.8	Q G 1s	Green, spar, marked "HP21".	Year round.	
535	Ives Knoll light buoy H22	W. of Knoll. 44 37 39.4 063 32 54.0	Fl R 4s	Red, pillar, marked "H22".	Year round.	
536	Ives Knoll light buoy HT2	N. of the Knoll. 44 37 50.2 063 32 44.7	Q R 1s	Red, pillar, marked "HT2".	Year round.	
538 H3618	Halifax Harbour Inner front range light	On W. side of Georges Island. 44 38 26.2 063 33 37.2	F W F W 17.7	15 15	White octagonal tower, red vertical stripe with red upper portion. 16.4	Year round. Operates 24 h. Increased intensity on line of range. W 290°-181°.
539 H3618.1	Halifax Harbour Inner rear range light	44 40 01.7 063 34 28.2 339°08' 3153.7 m from front.	Oc W	10s	37.7	24	Triangular skeleton tower, white daymark with red vertical stripe. 17.4	Year round. Operates 24 h. Flash 7 s; eclipse 3 s.
540.1	Dartmouth Cove West Entrance light buoy HU1	44 39 42.0 063 33 38.4	Fl G 4s	Green, spar, marked "HU1".	Year round.	
544	Barrie Beach light and bell buoy HP2/2	NW. of Devils Island. 44 35 11.2 063 28 47.3	Fl R 4s	Red, pillar, marked "HP2/2".	Year round. Audible signal: Bell	
545 H3596	Devils Island	SE. end of island. 44 34 49.5 063 27 35.3	LFl R 6s	6.0	7	Square skeleton tower, red and white rectangular daymark, red triangle in centre. 6.6	Year round. Flash 2 s; eclipse 4 s.	
546	Eastern Passage light and whistle buoy HP	SW. of Devils Island. 44 34 05.0 063 27 23.0	Mo(A) W 6s	Red-white, pillar, marked "HP".	Year round. Audible signal: Whistle	

List of Lights, Buoys and Fog Signals – Atlantic Coast

No. ----- Intl No.	Name ----- RACON	Location ----- Latitude N. Longitude W.	Light Characteristics	Focal Height Above Water (m)	Nominal Range (NM)	Description ----- Height of Structure Above Ground Level (m)	Remarks ----- Audible Signals ----- AIS
NOVA SCOTIA, SOUTHEAST COAST							
546.5	Lawlor Island light buoy HP3	E. of island. 44 35 56.1 063 29 08.0	Fl G 4s	Green, spar, marked "HP3".	Year round.
547 H3609	Lawlor Island Sector	On E. side of island. 44 36 21.8 063 29 45.4	F R W G	4.8	10 Triangular skeleton mast. 3.8	Year round. Operates 24 h. G 133°-140°30'; W 140°30'-142°30'; R 142°30'-155°.
547.2	Lawlor Island light buoy HP11	NE. of island. 44 36 31.8 063 29 58.4	Fl G 4s	Green, spar, marked "HP11".	Year round.
547.3	Eastern Passage Wharf Light	44 36 41.3 063 29 50.1	Fl Y 4s	Pipe swing pole.	Year round. Operates 24 h.
549	Eastern Passage light buoy HP13	44 36 40.4 063 30 20.9	Q G 1s	Green, spar, marked "HP13".	Year round.
550	Eastern Passage light buoy HP15	Opposite Texaco Co. wharf. 44 36 45.3 063 30 35.6	Fl G 4s	Green, spar, marked "HP15".	Year round.
551	Eastern Passage light buoy HP16	44 37 03.0 063 30 32.8	Fl R 4s	Red, spar, marked "HP16".	Year round.
552	Eastern Passage light buoy HP17	44 37 05.8 063 30 50.6	Fl G 4s	Green, spar, marked "HP17".	Year round.
555	Macdonald Bridge (V- AIS)	44 39 46.5 063 35 07.8	Year round. Virtual AIS AtoN MMSI: 993166016 Reference point
556	MacKay Bridge (V- AIS)	44 40 38.3 063 36 44.0	Year round. Virtual AIS AtoN MMSI: 993166017 Reference point
557	Seaview Point light buoy H39	44 40 37.6 063 37 14.0	Fl G 4s	Green, spar, marked "H39".	Year round.
559	Wrights Point light buoy H42	44 41 19.8 063 37 22.6	Q R 1s	Red, spar, marked "H42".	Year round.
560	Dartmouth Yacht Club light buoy HY6	44 41 59.0 063 36 48.0	Fl R 4s	Red, pillar, marked "HY6".	Private aid. Seasonal.
560.5 H3631	Dartmouth Yacht Club	On breakwater. 44 42 01.3 063 36 49.1	Fl G 4s	5.2	4	Square tower. 3.0	Private aid. Seasonal.
560.6	Navy Island Cautionary light buoy HYC	W. of island. 44 41 43.8 063 37 06.6	Fl Y 4s	Yellow, spar, marked "HYC".	Year round. Operates 24 h.
561	Wrights Cove light buoy HY2	NW. of Navy Island. 44 42 00.3 063 37 23.6	Fl R 4s	Red, spar, marked "HY2".	Year round.

List of Lights, Buoys and Fog Signals – Atlantic Coast

No. ----- Intl No.	Name ----- RACON	Location ----- Latitude N. Longitude W.	Light Characteristics	Focal Height Above Water (m)	Nominal Range (NM)	Description ----- Height of Structure Above Ground Level (m)	Remarks ----- Audible Signals ----- AIS
NOVA SCOTIA, SOUTHEAST COAST							
561.5	Bedford Basin light buoy H45	44 42 25.3 063 39 07.6	Q G 1s	Green, spar, marked "H45".	Year round.
562	Wellesley Rock light buoy H46	S. of the rock. 44 42 37.3 063 39 26.1	Fl R 4s	Red, spar, marked "H46".	Year round.
562.3	Spruce Island light buoy H48	W. of island. 44 43 00.3 063 39 54.6	Fl R 4s	Red, spar, marked "H48".	Year round.
563	Shut-in Island light and bell buoy HX	SE. of island. 44 36 39.8 063 16 01.2	Mo(A) W 6s	Red-white, pillar, marked "HX".	Year round. Audible signal: Bell
563.04	Three Fathom Harbour light buoy HX7	44 38 05.9 063 16 35.2	Fl G 4s	Green, spar, marked "HX7".	Year round.
563.05	Three Fathom Harbour light buoy HX8	44 38 16.1 063 16 38.0	Fl R 4s	Red, spar, marked "HX8".	Year round.
563.2	Bull Rock light buoy HX2	44 37 20.0 063 16 14.0	Fl R 4s	Red, spar, marked "HX2".	Year round.
564	Chezzetcook Harbour light and bell buoy HJ2	Off Story Head. 44 39 42.6 063 13 40.5	Fl R 4s	Red, pillar, marked "HJ2".	Year round. Audible signal: Bell
564.03	East Chezzetcook light buoy HJ4	E. shore. 44 41 18.8 063 13 47.7	Q R 1s	Red, spar, marked "HJ4".	Seasonal.
564.22	East Chezzetcook light buoy HJ2/2	Eastern shore. 44 41 16.4 063 13 52.7	Fl R 4s	Red, spar, marked "HJ2/2".	Seasonal.
565	Codroy Shoal light and bell buoy HH2	SW. of shoal. 44 40 24.5 063 10 38.6	Fl R 4s	Red, pillar, marked "HH2".	Year round. Audible signal: Bell
565.04	Petpeswick light buoy HH8	Eastern shore. 44 42 14.6 063 10 09.8	Fl R 4s	Red, spar, marked "HH8".	Seasonal.
565.05	Petpeswick light buoy HH9	Eastern shore. 44 42 27.1 063 10 03.9	Fl G 4s	Green, spar, marked "HH9".	Seasonal.
566.02	Musquodoboit light buoy YV7	44 40 44.0 063 04 23.4	Q G 1s	Green, spar, marked "YV7".	Year round.
566.03	Musquodoboit Harbour light buoy YV10	44 41 09.6 063 04 45.6	Q R 1s	Red, spar, marked "YV10".	Year round.
566.04	Musquodoboit Harbour green lighted spar buoy YV11	44 41 26.2 063 04 47.5	Fl G 4s	Green, spar, marked "YV11".	Year round.

List of Lights, Buoys and Fog Signals – Atlantic Coast

No. ----- Intl No.	Name ----- RACON	Location ----- Latitude N. Longitude W.	Light Characteristics	Focal Height Above Water (m)	Nominal Range (NM)	Description ----- Height of Structure Above Ground Level (m)	Remarks ----- Audible Signals ----- AIS
NOVA SCOTIA, SOUTHEAST COAST							
566.05	Musquodoboit Harbour light buoy YV12	44 41 26.2 063 04 42.8	Fl R 4s	Red, spar, marked "YV12".	Year round.
566.06	Musquodoboit Harbour light buoy YV13	44 41 34.0 063 04 43.7	Fl G 4s	Green, spar, marked "YV13".	Year round.
566.08	Musquodoboit (Flat Rock) light buoy YV15	Eastern shore. 44 41 41.4 063 04 45.0	Q G 1s	Green, spar, marked "YV15".	Year round.
566.11	Musquodoboit (French Pt) lighted red spar YV18	Eastern shore. 44 42 31.2 063 04 57.0	Q R 1s	Red, spar, marked "YV18".	Year round.
566.12	Musquodoboit (Francis Nose Is) light buoy YV21	E. shore. 44 42 52.9 063 05 03.1	Q G 1s	Green, spar, marked "YV21".	Year round.
566.5	Musquodoboit Ledge light and bell buoy YV3	W. side of ledge. 44 39 36.0 063 04 16.0	Fl G 4s	Green, pillar, marked "YV3".	Year round. Audible signal: Bell
568 H3578	Musquodoboit Harbour Light	On pier on Shag Ledge. 44 41 41.7 063 04 41.6	Q R 1s	5.5	Red cylindrical mast, red and white triangular daymark. 3.6	Year round.
569 H3579	French Point	44 42 21.0 063 04 33.3	F R	8 White pyramid tower with red top. 9.4	Year round. Visible 278°-090°.
570 H3570	Jeddore Rock	On summit of rock. 44 39 47.1 063 00 37.3	LFl W 12s	29.5	8	Skeleton tower.	Year round. Flash 2 s; eclipse 10 s.
570.5	Arnold Rock light and bell buoy YT3	S. of rock. 44 39 04.2 063 00 29.5	Fl G 4s	Green, pillar, marked "YT3".	Year round. Audible signal: Bell
572	Thorn Shoal light and bell buoy YT5	On alignment of Jeddore Harbour range. 44 41 24.0 063 00 10.0	Fl G 4s	Green, pillar, marked "YT5".	Year round. Audible signal: Bell
572.3	Jeddore Harbour light buoy YT7	44 42 18.6 063 00 46.8	Q G 1s	Green, spar, marked "YT7".	Year round.
572.6	Jeddore Harbour light buoy YT9	44 43 10.7 063 00 16.9	Fl G 4s	Green, can, marked "YT9".	Year round.
573	Marsh Point light buoy YT11	44 43 23.6 063 00 11.7	Q G 1s	Green, pillar, marked "YT11".	Year round.
576	Bar Shoal light buoy YT8	44 42 31.3 063 00 36.8	Fl R 4s	Red, spar, marked "YT8".	Year round.
577	Brig Rock light and bell buoy YT2	W. of rock. 44 37 08.4 062 56 18.7	Fl R 4s	Red, pillar, marked "YT2".	Year round. Audible signal: Bell

List of Lights, Buoys and Fog Signals – Atlantic Coast

No. ----- Intl No.	Name ----- RACON	Location ----- Latitude N. Longitude W.	Light Characteristics	Focal Height Above Water (m)	Nominal Range (NM)	Description ----- Height of Structure Above Ground Level (m)	Remarks ----- Audible Signals ----- AIS
NOVA SCOTIA, SOUTHEAST COAST							
578	Porter Island West light and bell buoy YS6	44 41 29.0 062 51 46.1	Fl R 4s	Red, pillar, marked "YS6".	Year round. Audible signal: Bell
579	Little Harbour Head light buoy YS9	N. of head. 44 42 22.3 062 50 29.9	Fl G 4s	Green, pillar, marked "YS9".	Year round.
580 H3568	Egg Island	Centre of island. 44 39 52.8 062 51 48.4	LFl W 6s	7.6	12	Square skeleton tower, white rectangular daymark with red horizontal band.	Year round. Flash 2 s; eclipse 4 s.
580.3	Pyches Rock East Cardinal light buoy YS	44 39 50.3 062 50 30.6	Q(3) W 10s	Black-yellow-black, pillar, marked "YS".	Year round.
582	Owls Head Harbour light and bell buoy YP2	SE. of head. 44 41 20.0 062 45 01.4	Fl R 4s	Red, pillar, marked "YP2".	Year round. Audible signal: Bell
583 H3566	Owls Head	On extremity of head. 44 43 14.6 062 47 59.5	LFl W 6s	25.8	6	Square skeleton tower, white rectangular daymark with red horizontal band. 9.7	Year round. Flash 2 s; eclipse 4 s.
584	Ship Harbour light and whistle buoy YM1	SE. of Little Rock. 44 41 06.3 062 42 07.1	Fl G 4s	Green, pillar, marked "YM1".	Year round. Audible signal: Whistle
585 H3564	Ship Harbour	On Wolfes Point. 44 44 55.5 062 45 23.7	LFl G 6s	4	Skeleton tower, white and red rectangular daymark. 6.6	Year round. Flash 2 s; eclipse 4 s.
586	Bull Rock bifurcation light and bell buoy YM	S. of rock. 44 44 05.6 062 41 29.6	Fl(2+1) R 6s	Red-green-red, pillar, marked "YM".	Year round. Audible signal: Bell
586.01	Black Rock light buoy YM8	44 46 18.5 062 47 55.0	Fl R 4s	Red, spar, marked "YM8".	Seasonal.
586.03	Ship Harbour light buoy YM12	44 46 57.0 062 49 09.3	Fl R 4s	Red, spar, marked "YM12".	Seasonal.
586.04	Ship Harbour light buoy YM14	44 47 57.2 062 50 10.0	Fl R 4s	Red, spar, marked "YM14".	Seasonal.
586.07	Ship Harbour light buoy YM17	44 48 08.0 062 50 30.1	Q G 1s	Green, spar, marked "YM17".	Seasonal.
587	Tangier Harbour light and whistle buoy YJ	SE. of Mooseback Point. 44 44 06.2 062 37 38.3	Mo(A) W 6s	Red-white, pillar, marked "YJ".	Year round. Audible signal: Whistle
588	Popes Harbour light and bell buoy YE2	W. of Popes Head. 44 46 23.9 062 36 47.8	Fl R 4s	Red, pillar, marked "YE2".	Year round. Audible signal: Bell
588.03	Brig Rock light buoy YE5	44 46 56.5 062 38 22.0	Fl G 4s	Green, spar, marked "YE5".	Year round.

List of Lights, Buoys and Fog Signals – Atlantic Coast

No. ----- Intl No.	Name ----- RACON	Location ----- Latitude N. Longitude W.	Light Characteristics	Focal Height Above Water (m)	Nominal Range (NM)	Description ----- Height of Structure Above Ground Level (m)	Remarks ----- Audible Signals ----- AIS
NOVA SCOTIA, SOUTHEAST COAST							
589 H3560	Popes Harbour	On W. point of Harbour Island. 44 47 40.3 062 39 01.4	Fl R 4s	9.4	8	Pipe swing pole, red and white triangular daymark.	Year round. Flash 1 s; eclipse 3 s.
590	Spry Bay light and bell buoy YA2	Off entrance. 44 45 37.2 062 33 28.6	Fl R 4s	Red, pillar, marked "YA2".	Year round. Audible signal: Bell
590.01	Maloney Shoal light buoy YA3	44 46 42.1 062 34 41.8	Fl G 4s	Green, spar, marked "YA3".	Year round.
590.02	Mad Moll Reef light buoy YA4	44 46 42.3 062 33 48.6	Fl R 4s	Red, spar, marked "YA4".	Year round.
590.03	Neverfail Shoal light buoy YA5	44 47 24.3 062 34 29.4	Q G 1s	Green, spar, marked "YA5".	Year round. Operates 24 h.
590.04	Spry Bay light buoy YA6	44 47 28.0 062 34 01.3	Fl R 4s	Red, spar, marked "YA6".	Year round. Operates 24 h.
590.05	Ram Rock light buoy YA7	44 48 36.8 062 35 56.3	Fl G 4s	Green, spar, marked "YA7".	Year round. Operates 24 h.
590.06	Bald Rock light buoy YA8	44 48 42.9 062 35 34.9	Fl R 4s	Red, spar, marked "YA8".	Year round. Operates 24 h.
593	Geddes Shoal light and whistle buoy X26	SW. of shoal. 44 44 28.0 062 28 09.0	Fl R 4s	Red, pillar, marked "X26".	Year round. Audible signal: Whistle
593.6	MacDonald Rock light buoy XU4	44 48 54.0 062 28 41.0	Fl R 4s	Red, pillar, marked "XU4".	Year round.
594 H3541	Sheet Rock	Entrance to harbour. 44 49 50.4 062 29 30.6	Fl W 4s	25.7	7	White cylindrical tower with red horizontal band. 9.7	Year round.
595	White Rock light buoy XU10	44 51 00.5 062 29 38.0	Q R 1s	Red, spar, marked "XU10".	Year round.
596	Watt Point light buoy XU14	44 53 49.5 062 29 16.0	Fl R 4s	Red, spar, marked "XU14".	Year round.
596.01	Northeast Arm light buoy XX1	44 55 06.0 062 30 56.0	Fl G 4s	Green, pillar, marked "XX1".	Year round.
596.04	Mussel Shoal light buoy XU18	E. shore. 44 54 36.5 062 31 09.0	Fl R 4s	Red, spar, marked "XU18".	Year round.
597	Sheet Harbour Passage light and bell buoy XP7	S. of Hardwood Island. 44 49 06.0 062 25 54.0	Fl G 4s	Green, pillar, marked "XP7".	Year round. Audible signal: Bell
600	Beaver Harbour light and whistle buoy XK1	Off harbour. 44 47 55.0 062 17 03.0	Fl G 4s	Green, pillar, marked "XK1".	Year round. Audible signal: Whistle

List of Lights, Buoys and Fog Signals – Atlantic Coast

No. ----- Intl No.	Name ----- RACON	Location ----- Latitude N. Longitude W.	Light Characteristics	Focal Height Above Water (m)	Nominal Range (NM)	Description ----- Height of Structure Above Ground Level (m)	Remarks ----- Audible Signals ----- AIS
NOVA SCOTIA, SOUTHEAST COAST							
601	Beaver Island light and bell buoy XK3	E. of island. 44 49 33.0 062 19 28.0	Fl G 4s	Green, pillar, marked "XK3".	Year round. Audible signal: Bell
602 H3534	Beaver Island	E. end of island. 44 49 29.2 062 20 16.0	Fl W	19.9	14	White cylindrical tower with red top. 8.6	Year round.
605	Bassoon Reefs light and bell buoy XH1	S. extremity of the SE. portion of reefs. 44 50 41.0 062 13 34.0	Fl G 4s	Green, pillar, marked "XH1".	Year round. Audible signal: Bell
606.3	Tuffin Island light buoy XA6	N. of island. 44 54 53.5 062 10 45.5	Q R 1s	Red, pillar, marked "XA6".	Year round.
606.5	Tuffin Island light and bell buoy XA4	SW. of island. 44 54 12.0 062 10 50.5	Fl R 4s	Red, pillar, marked "XA4".	Year round. Audible signal: Bell
606.7	Halibut Island light and bell buoy XA3	44 53 06.0 062 10 55.0	Fl G 4s	Green, pillar, marked "XA3".	Year round. Audible signal: Bell
607	Bowen Ledge light and bell buoy XA2	SW. of ledge. 44 51 59.0 062 10 15.0	Fl R 4s	Red, pillar, marked "XA2".	Year round. Audible signal: Bell
608	White Island light and bell buoy VV1	Off E. extremity of White Island breaker. 44 52 59.8 062 06 16.3	Fl G 4s	Green, pillar, marked "VV1".	Year round. Audible signal: Bell
609	Lockwood Rock light and whistle buoy V24	S. of rock. 44 51 39.0 062 04 21.0	Fl R 4s	Red, pillar, marked "V24".	Year round. Audible signal: Whistle
610	Necum Point light buoy VV12	44 57 16.0 062 08 59.0	Fl R 4s	Red, spar, marked "VV12".	Year round.
610.5	Frenchman Rock light buoy VV8	44 55 56.5 062 07 03.5	Fl R 4s	Red, spar, marked "VV8".	Year round.
611	Seal Ledge light and bell buoy VT5	NE. of ledge. 44 57 28.0 061 59 31.0	Fl G 4s	Green, pillar, marked "VT5".	Year round. Audible signal: Bell
612 H3530	Marie Joseph (Thrumcap Island)	On Islet. 44 57 25.6 062 02 25.7	Fl R 4s	12.2	4	Square skeleton tower, red and white rectangular daymark, red triangle in centre.	Year round.
613	Liscomb light and whistle buoy VP	E. of Hawbolt Rock. 44 55 00.0 061 53 33.0	Mo(A) W 6s	Red-white, pillar, marked "VP".	Year round. Audible signal: Whistle
614	Liscomb Shoal light and bell buoy VP5	SE. of shoal. 44 58 31.0 061 57 50.0	Fl G 4s	Green, pillar, marked "VP5".	Year round. Audible signal: Bell

List of Lights, Buoys and Fog Signals – Atlantic Coast

No. ----- Intl No.	Name ----- RACON	Location ----- Latitude N. Longitude W.	Light Characteristics	Focal Height Above Water (m)	Nominal Range (NM)	Description ----- Height of Structure Above Ground Level (m)	Remarks ----- Audible Signals ----- AIS
NOVA SCOTIA, SOUTHEAST COAST							
615 H3526	Liscomb Island	44 59 15.8 061 57 58.4	FI W 10s	21.9	14	White octagonal tower with red top. 13.7	Year round. Flash 1 s; eclipse 9 s. Fog Horn Blast 3 s; sil. 27 s.
619	Little Liscomb light and bell buoy VM3	SE. of Crook Point. 44 59 10.3 061 53 27.0	FI G 4s	Green, pillar, marked "VM3".	Year round. Audible signal: Bell
621	Saint Marys River light and bell buoy VK	S. of Wedge Island. 44 59 35.9 061 49 41.7	Mo(A) W 6s	Red-white, pillar, marked "VK".	Year round. Audible signal: Bell
621.5	Barachois Point light and bell buoy VK3	Off point. 45 01 16.3 061 51 44.8	FI G 4s	Green, pillar, marked "VK3".	Year round. Audible signal: Bell
622	Horse Shoal light buoy VK11	45 03 05.0 061 53 43.6	Q G 1s	Green, pillar, marked "VK11".	Year round.
623.5	Rude Shoal light and bell buoy VH5	Off shoal. 45 04 12.5 061 48 26.5	Q G 1s	Green, pillar, marked "VH5".	Year round. Audible signal: Bell
625	Nixonmate Shoal light and whistle buoy VH2	SW. of shoal. 45 01 46.6 061 45 14.5	FI R 4s	Red, pillar, marked "VH2".	Year round. Audible signal: Whistle
626.1	Mouton Harbour Outer Channel light buoy VC1	45 05 34.3 061 42 53.7	Q G 1s	Green, spar, marked "VC1".	Seasonal (in place year round).
626.2	Mouton Harbour Outer Channel light buoy VC2	45 05 34.5 061 42 56.0	FI R 4s	Red, spar, marked "VC2".	Seasonal (in place year round).
626.3	Mouton Harbour Outer Channel light buoy VC3	45 05 33.6 061 43 00.4	FI G 4s	Green, spar, marked "VC3".	Seasonal (in place year round).
626.4	Mouton Harbour Inner Channel light buoy VC4	45 05 34.7 061 43 14.2	Q R 1s	Red, spar, marked "VC4".	Seasonal (in place year round).
626.6	Mouton Harbour Inner Channel light buoy VC5	45 05 34.4 061 43 15.8	FI G 4s	Green, spar, marked "VC5".	Seasonal (in place year round).
626.7	Mouton Harbour Inner Channel light buoy VC7	45 05 37.9 061 43 26.0	FI G 4s	Green, spar, marked "VC7".	Seasonal (in place year round).
626.9	Bickerton Island light buoy V1	45 05 02.0 061 42 04.0	FI G 4s	Green, spar, marked "V1".	Seasonal (in place year round).
627.1	Bickerton East Bifurcation light buoy VCC	45 05 36.2 061 42 33.0	FI(2+1) G 6s	Green-red-green, spar, marked "VCC".	Seasonal (in place year round).
627.5	Bickerton East Outer light buoy V3	45 05 42.7 061 42 38.3	FI G 4s	Green, spar, marked "V3".	Seasonal (in place year round).

List of Lights, Buoys and Fog Signals – Atlantic Coast

No. ----- Intl No.	Name ----- RACON	Location ----- Latitude N. Longitude W.	Light Characteristics	Focal Height Above Water (m)	Nominal Range (NM)	Description ----- Height of Structure Above Ground Level (m)	Remarks ----- Audible Signals ----- AIS
NOVA SCOTIA, SOUTHEAST COAST							
628.1	<i>Bickerton East Middle light buoy V4</i>	45 05 55.9 061 43 03.9	Fl R 4s	Red, spar, marked "V4".	Seasonal (in place year round).
628.5	<i>Bickerton East Inner light buoy V6</i>	45 06 12.2 061 43 22.1	Q R 1s	Red, spar, marked "V6".	Seasonal (in place year round).
629 H3514	Port Bickerton	Near W. extremity of Barachois Head. 45 05 24.0 061 42 01.7	Fl W 3s	20.6	17	White square building with red roof and white square tower with red top. 9.2	Year round. Flash 1 s; eclipse 2 s. Visible 280°-136°. Fog Horn Blast 3 s; sil. 3 s; blast 3 s; sil. 51 s.
629.5 H3516	Mouton Harbour Outer front range light	45 05 29.9 061 43 49.6	F W	3.8	14 Square skeleton tower, white daymark with red vertical stripe. 3.6	Year round.
629.6 H3516.1	Mouton Harbour Outer rear range light	45 05 29.4 061 43 56.0 263°39' 141.9 m from front.	F W	7.6	14 Square skeleton tower, white daymark with red vertical stripe. 6.6	Year round.
629.8 H3516.3	Mouton Harbour	On crib. 45 05 40.8 061 43 28.5	Iso R 1s	4.5	4	Square skeleton tower, red and white triangular daymark with red triangle in center. 3.6	Year round.
629.9 H3516.4	Mouton Harbour Wharf Light	45 05 41.8 061 43 35.1	Fl G 4s	4.3	4	Cylindrical mast, green and white square daymark. 3.5	Year round. Flash 1 s; eclipse 3 s.
631.2 H3515	Port Bickerton East wharf Light	On outer end of wharf. 45 06 18.8 061 43 21.9	Iso R 4s	4.3	4	Cylindrical mast. 3.6	Year round.
632	<i>Port Bickerton light and bell buoy V</i>	SW. of Taylor Shoal. 45 01 12.5 061 39 09.0	Mo(A) W 6s	Red-white, pillar, marked "V".	Year round. Audible signal: Bell
633.01	Rose Shoal South Cardinal light buoy TY	45 04 33.0 061 37 20.1	Q(6) + LFI W	15s	Yellow-black, pillar, marked "TY". Year round.
633.02	<i>Bull Rock light buoy TY5</i>	Liscomb. 45 05 11.0 061 38 32.5	Q G 1s	Green, spar, marked "TY5".	Seasonal (in place year round).
634 H3512	Fishermans Harbour	W. extremity of Shingle beach on S. side of harbour. 45 06 42.0 061 40 41.1	Fl G 4s	7.1	7	Square skeleton tower, green, white and green square daymark. 7.9	Seasonal. Flash 1 s; eclipse 3 s.
634.4	<i>South Easter South Cardinal light buoy TU</i>	SW. of South Easter. 45 02 45.0 061 35 12.0	Q(6) + LFI W	15s	Yellow-black, pillar, marked "TU". Year round.

List of Lights, Buoys and Fog Signals – Atlantic Coast

No. ----- Intl No.	Name ----- RACON	Location ----- Latitude N. Longitude W.	Light Characteristics	Focal Height Above Water (m)	Nominal Range (NM)	Description ----- Height of Structure Above Ground Level (m)	Remarks ----- Audible Signals ----- AIS
NOVA SCOTIA, SOUTHEAST COAST							
635	Isaac's Harbour light and bell buoy TT	E. of Jarvis Bank. 45 02 14.9 061 32 35.0	Mo(A) W 6s	Red-white, pillar, marked "TT".	Year round. Audible signal: Bell
635.5	Tom Cod light buoy TT2	45 04 27.3 061 33 00.7	Fl R 4s	Red, pillar, marked "TT2".	Year round.
636	Goose Island light buoy TT4	S. extremity of island. 45 05 54.5 061 34 36.2	Q R 1s	Red, pillar, marked "TT4".	Year round.
636.04	Isaac's Harbour light buoy TT7	Liscomb. 45 09 34.0 061 39 20.0	Q G 1s	Green, spar, marked "TT7".	Year round.
636.1	Avondale Reef light buoy TT10	45 09 43.0 061 39 02.0	Fl R 4s	Red, pillar, marked "TT10".	Year round.
636.2	Middle Ground light buoy TX1	Off Saladin Point. 45 07 32.0 061 35 21.0	Fl G 4s	Green, spar, marked "TX1".	Year round.
638 H3508	Drum Head	On outer end of breakwater. 45 08 43.2 061 36 09.2	Fl R 4s	4.2	5	Cylindrical mast, red and white triangular daymark. 3.6	Seasonal. Flash 1 s; eclipse 3 s.
639 H3504	Country Island	S. side of island. 45 05 59.8 061 32 31.9	Fl W 20s	16.5	White octagonal tower with red top. 13.7	Year round. Flash 2 s; eclipse 18 s.
639.5	Split Rock light and whistle buoy TS2	SW. of rock. 45 07 08.0 061 29 45.4	Q R 1s	Red, pillar, marked "TS2".	Year round. Audible signal: Whistle
639.7	Brandy Ledge light and bell buoy TQ2	S. of ledge. 45 06 54.4 061 26 56.2	Fl R 4s	Red, pillar, marked "TQ2".	Year round. Audible signal: Bell
640	Coddles Harbour light and bell buoy TS6	Off S. extremity of Coddles Island. 45 08 33.8 061 30 48.0	Fl R 4s	Red, pillar, marked "TS6".	Year round. Audible signal: Bell
641 H3502	Coddles Harbour	On Thrumcap Island, entrance to harbour. 45 09 21.3 061 31 01.0	Fl W 4s	9.8	6	Pipe swing pole, red and white rectangular daymark.	Seasonal. Flash 1 s; eclipse 3 s.
642	Shoal Point light and bell buoy TP1	S. of Eastern Head. 45 09 02.0 061 25 28.0	Fl G 4s	Green, pillar, marked "TP1".	Year round. Audible signal: Bell
643	Eastern Head light buoy TP2	NE. of point. 45 10 00.8 061 26 14.4	Fl R 4s	Red, spar, marked "TP2".	Year round.
644 H3500	New Harbour Cove	On outer end of breakwater. 45 10 13.5 061 27 01.6	Fl(2) G 6s	8.2	4	Skeleton tower, enclosed lower portion. 3.5	Seasonal. Flash 1 s; eclipse 1 s; flash 1 s; eclipse 3 s.

List of Lights, Buoys and Fog Signals – Atlantic Coast

No. ----- Intl No.	Name ----- RACON	Location ----- Latitude N. Longitude W.	Light Characteristics	Focal Height Above Water (m)	Nominal Range (NM)	Description ----- Height of Structure Above Ground Level (m)	Remarks ----- Audible Signals ----- AIS
NOVA SCOTIA, SOUTHEAST COAST							
645.6	Larry's River light buoy TK1	45 11 54.2 061 21 07.1	Fl G 4s	Green, pillar, marked "TK1".	Seasonal.
646 H3484	Berry Head	On E. point of head, W. side of entrance to harbour. 45 11 28.8 061 18 39.9	LFl W 6s	12	White rectangular tower with red top. 6.2	Year round. Flash 2 s; eclipse 4 s.
646.1	Torbay light and bell buoy TH	45 10 48.7 061 16 24.2	Mo(A) W 6s	Red-white, pillar, marked "TH".	Year round. Audible signal: Bell
646.2	Torbay French Rock light buoy TH2	45 11 14.2 061 16 47.0	Q R 1s	Red, spar, marked "TH2".	Seasonal (in place year round).
646.3	Torbay Ledges light buoy TH3	45 11 37.0 061 17 21.0	Q G 1s	Green, spar, marked "TH3".	Year round.
646.4	Torbay Ledges light buoy TH4	45 11 44.6 061 17 13.7	Fl R 4s	Red, spar, marked "TH4".	Seasonal (in place year round).
646.7	Webber Shoal light buoy TH7	Torbay. 45 12 40.3 061 19 28.3	Fl G 4s	Green, spar, marked "TH7".	Seasonal (in place year round).
646.9	Larrys River light buoy TH10	45 12 54.6 061 22 02.7	Fl R 4s	Red, spar, marked "TH10".	Year round.
647.2 H3497	Larry's River Northeast Breakwater	On outer end of breakwater. 45 12 58.1 061 22 06.3	Iso R 4s	3.9	10	Square skeleton tower, red and white rectangular daymark, red triangle in centre. 3.3	Year round.
648.1	Charlos Harbour Fairway light buoy TN	45 14 22.5 061 18 45.5	Mo(A) W 6s	Red-white, spar, marked "TN".	Year round.
654 H3478	Hog Island	E. end of island. 45 13 43.6 061 13 11.0	Fl W 4s	10.6	Square skeleton tower, red and white rectangular daymark. 9.9	Seasonal. Visible 196°-062°. Fog Horn Blast 2 s; sil. 18 s.
655	Flying Point Shoals light and whistle buoy TA4	W. of shoals. 45 11 59.5 061 13 09.3	Fl R 4s	Red, pillar, marked "TA4".	Year round. Audible signal: Whistle
656	Port Felix light and bell buoy TA7	S. of Hog Island. 45 13 16.3 061 13 11.2	Fl G 4s	Green, pillar, marked "TA7".	Year round. Audible signal: Bell
656.6	Whitehaven Harbour light buoy PU15	S. of Kelp Shoal. 45 14 04.3 061 10 41.5	Fl G 4s	Green, spar, marked "PU15".	Year round.
657 H3476	Three Top Island	SE. point of island, entrance to Whitehead. 45 12 28.9 061 09 31.9	Fl G 4s	16.9	8	Square skeleton tower, red and white rectangular daymark. 9.7	Year round. Flash 1 s; eclipse 3 s. Visible 150°-033°.

List of Lights, Buoys and Fog Signals – Atlantic Coast

No. ----- Intl No.	Name ----- RACON	Location ----- Latitude N. Longitude W.	Light Characteristics	Focal Height Above Water (m)	Nominal Range (NM)	Description ----- Height of Structure Above Ground Level (m)	Remarks ----- Audible Signals ----- AIS
NOVA SCOTIA, SOUTHEAST COAST							
657.5	Gammon Islands light buoy PU5	Southern Passage. 45 12 08.0 061 08 35.8	Q G 1s	Green, spar, marked "PU5".	Year round.
658	Southwest Bull light and bell buoy PU1	SE. of rock. 45 11 09.1 061 08 20.3	Fl G 4s	Green, pillar, marked "PU1".	Year round. Audible signal: Bell
659 H3474	White Head Island	SW. side of island. 45 11 49.1 061 08 10.8	LFI W 6s	18.2	10	Square tower, red, white and red rectangular daymark. 10.6	Year round. Flash 2 s; eclipse 4 s.
661.2	White Point Ledges South Cardinal light and whistle buoy PQ	45 13 28.2 060 58 46.6	Q(6) + LFI W 15s	Yellow-black, pillar, marked "PQ".	Year round. Audible signal: Whistle
662	Horne Shoal light and bell buoy PQ4	W. side of Horne Shoal. 45 15 27.4 061 01 03.4	Fl R 4s	Red, pillar, marked "PQ4".	Year round. Audible signal: Bell
662.2	Dover Bay light buoy PQ6	45 16 25.9 061 01 03.6	Q R 1s	Red, spar, marked "PQ6".	Year round.
662.5 H3473	Walsh Point Fog Signal	45 16 17.2 061 01 27.0	Triangular skeleton mast.	Seasonal. Fog Horn Blast 2 s; sil. 18 s. Mariners requiring the operation of the fog signal will have to select VHF channel 65 (156.275Mhz) and key their microphones five (5) times within 10 secs. The signal will be in operation for 30 min. After this delay the same operation must be repeated.
662.9	Dover Harbour light buoy PQ11	45 16 50.5 061 01 34.0	Q G 1s	Green, spar, marked "PQ11".	Year round.
662.91	Dover Harbour light buoy PQ12	45 16 51.7 061 01 34.9	Fl R 4s	Red, spar, marked "PQ12".	Year round.
662.94	Dover Harbour light buoy PQ15	45 17 13.9 061 02 09.1	Fl G 4s	Green, spar, marked "PQ15".	Year round.
663 H3472	Dover Harbour	Burnt Island. 45 16 41.5 061 01 12.4	Fl W 4s	8.1	7	Square skeleton tower, red and white rectangular daymark. 6.7	Year round.
663.2 H3471	Rock Island	45 16 58.1 061 01 42.6	LFI R 6s	5	Cylindrical mast, red and white triangular daymark.	Seasonal. Flash 2 s; eclipse 4 s.
664.03	Little Dover Run light buoy PP7	45 16 08.5 060 59 02.0	Fl G 4s	Green, spar, marked "PP7".	Year round.
664.032	Little Dover Run light buoy PP11	45 16 19.2 060 59 22.0	Fl G 4s	Green, pillar, marked "PP11".	Year round.
664.034	Little Dover Run light buoy PP15	45 16 25.9 060 59 36.6	Fl G 4s	Green, spar, marked "PP15".	Year round.

List of Lights, Buoys and Fog Signals – Atlantic Coast

No. ----- Intl No.	Name ----- RACON	Location ----- Latitude N. Longitude W.	Light Characteristics	Focal Height Above Water (m)	Nominal Range (NM)	Description ----- Height of Structure Above Ground Level (m)	Remarks ----- Audible Signals ----- AIS
NOVA SCOTIA, SOUTHEAST COAST							
664.035	Little Dover Run light buoy PP22	45 16 39.4 061 00 15.1	Fl R 4s	Red, spar, marked "PP22".	Year round.
664.037	Little Dover Run light buoy PP25	45 16 52.4 061 00 44.3	Fl G 4s	Green, spar, marked "PP25".	Year round.
664.038	Little Dover Run light buoy PP26	45 17 13.5 061 01 28.1	Fl R 4s	Red, spar, marked "PP26".	Year round.
664.039	Little Dover Run light buoy PP29	Canso. 45 17 22.1 061 01 50.7	Q G 1s	Green, spar, marked "PP29".	Year round.
664.1	Little Dover Harbour Fairway light and bell buoy P	E. of Thrumcap Island. 45 16 00.0 060 57 18.8	Mo(A) W 6s	Red-white, pillar, marked "P".	Year round. Audible signal: Bell
664.5	Banquereau ODAS light buoy 44139	44 14 03.0 057 05 44.4	Fl(5) Y 20s	Yellow, ODAS, marked "44139".	Year round.
664.7	East Scotia Slope ODAS light buoy 44137	42 15 42.0 061 59 54.0	Fl(5) Y 20s	Yellow, ODAS, marked "44137".	Year round. Operates 24 h.
664.8	Southwest Grand Banks ODAS light buoy 44138	44 13 00.0 053 36 00.0	Fl(5) Y 20s	Yellow, ODAS.	Year round.
666.8	Andrew Island East Cardinal light and whistle buoy PK	E. of island. 45 17 36.0 060 52 58.0	Q(3) W 10s	Black-yellow-black, pillar, marked "PK".	Year round. Audible signal: Whistle
667.015	Pink Rock light buoy PK2	Canso. 45 19 04.3 060 55 35.7	Fl R 4s	Red, spar, marked "PK2".	Year round.
668 H3458	Cranberry Islands Racon B (- . . .) X Band	S. part of island, off Cape Canso. 45 19 29.6 060 55 38.2	Fl W 15s	16.9	21	Square skeleton tower, red and white rectangular daymark.	Year round. Flash 1 s; eclipse 14 s. Fog Horn Blast 3 s; sil. 3 s; blast 3 s; sil. 51 s.
669	Grime Shoal light and whistle buoy CV1	E. of Grime Rock. 45 21 05.3 060 50 44.6	Fl G 4s	Green, pillar, marked "CV1".	Year round. Audible signal: Whistle
669.5	Bass Rock light and bell buoy PJ2	S. of rock. 45 20 38.4 060 52 54.7	Fl R 4s	Red, pillar, marked "PJ2".	Year round. Audible signal: Bell
669.8	Frying Pan Shoal light and bell buoy PJ3	E. of shoal. 45 19 58.2 060 55 41.1	Fl G 4s	Green, pillar, marked "PJ3".	Year round. Audible signal: Bell
670	Man of War Rock light and bell buoy PK7	E. of rock. 45 19 41.4 060 56 56.4	Fl G 4s	Green, pillar, marked "PK7".	Year round. Audible signal: Bell
670.5	Pas Reef light buoy PJ6	45 20 02.7 060 56 56.5	Fl R 4s	Red, spar, marked "PJ6".	Year round.

List of Lights, Buoys and Fog Signals – Atlantic Coast

No. ----- Intl No.	Name ----- RACON	Location ----- Latitude N. Longitude W.	Light Characteristics	Focal Height Above Water (m)	Nominal Range (NM)	Description ----- Height of Structure Above Ground Level (m)	Remarks ----- Audible Signals ----- AIS
NOVA SCOTIA, SOUTHEAST COAST							
671	Grassy Island light buoy PJ12	S. of island. 45 19 58.3 060 58 10.7	Q R 1s	Red, spar, marked "PJ12".	Year round.
672 H3460	Canso front range light	S. of Lanigan Beach, near S. entrance to harbour. 45 19 56.2 060 58 46.5	F R	11.9	13	White square tower with red upper portion and red vertical stripe. 10.1	Year round.
673 H3460.1	Canso rear range light	45 19 55.4 060 59 03.2 266°29' 365.8 m from front.	F R	28.5	13	White square tower with red upper portion and red vertical stripe. 13.8	Year round.
674 H3462	Canso Harbour front range light	On N. end of breakwater. 45 20 14.3 060 59 03.9	F G	4.5	7	Square skeleton tower, white daymark with red vertical stripe. 3.0	Year round.
674.2 H3462.1	Canso Harbour rear range light	45 20 12.4 060 59 03.1 164°28' 62.0 m from front.	F G	6.6	7	Square skeleton tower, white daymark with red vertical stripe. 5.1	Year round.
675.1	Canso Harbour Turn light buoy PC14	45 20 19.4 060 59 08.5	Q R 1s	Red, spar, marked "PC14".	Year round.
677 H3464.5	Starling Rock	On crib. 45 20 23.6 060 59 04.6	Q G 1s	6.3	4	White cylindrical tower with green horizontal band, green and white square daymark facing S., W., and N. with black square in centre. 3.6	Year round.
678 H3464	Piscatiqui Island	W. shore of island. 45 20 33.6 060 59 09.1	Fl W 5s	6	Square skeleton tower, red and white rectangular daymark.	Year round. Flash 2 s; eclipse 3 s.
679 H3465	Hart Island front range light	45 20 37.6 060 59 25.3	F R	4.1	17	Square skeleton tower, white daymark with red vertical stripe. 3.6	Year round.
679.1 H3465.1	Hart Island rear range light	45 20 33.9 060 59 24.3 169°45' 116.7 m from front.	F R	9.3	17	Square skeleton tower, white daymark with red vertical stripe. 8.2	Year round.
679.5 H3468	Harbour Shoal	On crib. 45 20 20.5 060 59 38.6	Fl G 4s	6.4	6	White cylindrical tower with green horizontal band, green and white square daymark facing E., W., and N. with black square in centre. 3.6	Year round.
680.2	Hart Island light buoy PC6	NW. of island. 45 20 45.7 060 59 28.2	Q R 1s	Red, spar, marked "PC6".	Year round.

List of Lights, Buoys and Fog Signals – Atlantic Coast

No. ----- Intl No.	Name ----- RACON	Location ----- Latitude N. Longitude W.	Light Characteristics	Focal Height Above Water (m)	Nominal Range (NM)	Description ----- Height of Structure Above Ground Level (m)	Remarks ----- Audible Signals ----- AIS
--------------------------	------------------------	--	--------------------------	--	--------------------------	--	---

NOVA SCOTIA, SOUTHEAST COAST

680.5	Piscatiqui Island light buoy PC5	NW. of island. 45 20 53.8 060 59 27.8	Fl G 4s	Green, spar, marked "PC5".	Year round.
681	Bald Rock light and bell buoy PC2	N. entrance to Canso Harbour. 45 21 10.8 060 59 36.1	Fl R 4s	Red, pillar, marked "PC2".	Year round. Audible signal: Bell
682	Canso Harbour light and whistle buoy PC	N. entrance to harbour. 45 21 42.9 060 59 41.5	Mo(A) W 6s	Red-white, pillar, marked "PC".	Year round. Audible signal: Whistle
683 H3456	Queensport	On Rook Island, Chedabucto Bay. 45 20 52.6 061 16 18.9	Fl W 4s	16.5	7	White house with red top. 10.7	Year round.
683.1	Guysborough Harbour light buoy CQ2	45 22 29.1 061 29 06.6	Fl R 4s	Red, conical, marked "CQ2".	Seasonal.
684.02	Guysborough Harbour light buoy CQ5	45 22 55.3 061 29 20.3	Fl G 4s	Green, can, marked "CQ5".	Seasonal.