

List of Lights, Buoys and Fog Signals – Atlantic Coast

No. ----- Intl No.	Name ----- RACON	Location ----- Latitude N. Longitude W.	Light Characteristics	Focal Height Above Water (m)	Nominal Range (NM)	Description ----- Height of Structure Above Ground Level (m)	Remarks ----- Audible Signals ----- AIS
NOVA SCOTIA AND CAPE BRETON ISLAND							
Chedabucto Bay							
686.5	Chedabucto Bay light buoy CF	45 23 54.4 061 03 00.5	Mo(A) W 6s	Red-white, pillar, marked "CF".	Year round.
686.7	Chedabucto Bay light buoy C2	45 25 38.1 061 06 17.7	Q R 1s	Red, pillar, marked "C2".	Year round.
686.8	Chedabucto Bay light buoy CGB	45 28 24.3 061 10 23.7	Mo(A) W 6s	Red-white, pillar, marked "CGB".	Year round.
Strait of Canso							
687.1	Argos Shoal light buoy CS1	45 29 11.3 061 12 16.6	Q G 1s	Green, pillar, marked "CS1".	Year round.
687.2	Chedabucto Bay light and bell buoy C7	45 28 07.2 061 10 49.8	Fl G 4s	Green, pillar, marked "C7".	Year round. Audible signal: Bell
687.3	Chedabucto Bay light and bell buoy C8	45 28 42.2 061 09 55.7	Fl R 4s	Red, pillar, marked "C8".	Year round. Audible signal: Bell
687.35	Chedabucto Bay West ODAS light buoy 4400489	45 29 13.0 061 08 28.0	Fl(5) Y 20s	Yellow, ODAS, marked "4400489".	Year round.
687.4	Chedabucto Bay light buoy C10	45 30 40.3 061 12 18.4	Fl R 4s	Red, pillar, marked "C10".	Year round.
687.5	Chedabucto Bay light and bell buoy C11	45 31 48.4 061 14 17.8	Fl G 4s	Green, pillar, marked "C11".	Year round. Audible signal: Bell
687.7	Chedabucto Bay light buoy C13	45 32 17.8 061 15 28.6	Q G 1s	Green, pillar, marked "C13".	Year round.
687.8	Chedabucto Bay light buoy C14	45 32 37.3 061 15 45.6	Fl R 4s	Red, pillar, marked "C14".	Year round.
688	Chedabucto Bay light buoy C16	45 32 31.3 061 17 30.6	Q R 1s	Red, pillar, marked "C16".	Year round.
688.1	Chedabucto Bay light buoy C17	45 32 39.3 061 18 27.6	Fl G 4s	Green, pillar, marked "C17".	Year round.
688.2	Chedabucto Bay light buoy C18	45 33 29.3 061 19 17.6	Fl R 4s	Red, pillar, marked "C18".	Year round.
688.4	Chedabucto Bay light buoy C20	45 33 44.3 061 19 57.6	Q R 1s	Red, pillar, marked "C20".	Year round.
688.5	Chedabucto Bay light buoy C21	45 34 58.8 061 22 01.6	Fl G 4s	Green, pillar, marked "C21".	Year round.
689.1	Eddy Point Cautionary light buoy CY	45 31 27.7 061 14 37.5	Fl Y 4s	Yellow, spar, marked "CY".	Year round.

List of Lights, Buoys and Fog Signals – Atlantic Coast

No. ----- Intl No.	Name ----- RACON	Location ----- Latitude N. Longitude W.	Light Characteristics	Focal Height Above Water (m)	Nominal Range (NM)	Description ----- Height of Structure Above Ground Level (m)	Remarks ----- Audible Signals ----- AIS
NOVA SCOTIA AND CAPE BRETON ISLAND							
689.3 H3421	Eddy Point front range light	SE. entrance, Strait of Canso. 45 31 12.2 061 15 07.4	Oc G 11s	11.9	15	Triangular skeleton tower, white daymark with red vertical stripe. 12.3	Year round. Operates 24 h. Flash 10 s; eclipse 1 s.
689.4 H3421.1	Eddy Point rear range light	45 31 05.6 061 14 53.7 124°51' 361.0 m from front.	F G	26.1	15	Triangular skeleton tower, white daymark with red vertical stripe. 19.0	Year round. Operates 24 h.
689.7 H3419	Port Malcolm front range light	Seacoal Bay Entrance. 45 34 32.7 061 17 16.9	F W	19.7	25	Triangular skeleton tower, white daymark with red vertical stripe. 9.6	Year round. Operates 24 h.
689.8 H3419.1	Port Malcolm rear range light	45 34 52.3 061 17 40.4 319°50' 790.7 m from front.	F W	46.6	25	Triangular skeleton tower, white daymark with red vertical stripe. 19.1	Year round. Operates 24 h.
690.3 H3425	Middle Melford front range light	45 32 21.7 061 18 53.2	F G	13.7	15	Triangular skeleton tower, white daymark with red vertical stripe. 7.8	Year round. Operates 24 h. Locator light: Fl W 4s.
690.4 H3425.1	Middle Melford rear range light	45 32 21.6 061 18 57.6 268°05' 92.4 m from front.	F G	20.7	15	Triangular skeleton tower, white daymark with red vertical stripe. 13.8	Year round. Operates 24 h. Locator light: Fl W 4s.
692 H3426	Park Point front range light	On point, W. side of Strait. 45 32 35.8 061 19 16.0	F G	12.3	17	Triangular skeleton tower, white daymark with red vertical stripe. 11.1	Year round. Operates 24 h.
693 H3426.1	Park Point rear range light	45 32 27.3 061 19 07.9 146°18' 316.9 m from front.	F G	25.1	17	Triangular skeleton tower, white daymark with red vertical stripe. 19.3	Year round. Operates 24 h.
694.4 H3427	Laceys Rocks (Cahil Rock) front range light	SE. of rocks. 45 34 13.2 061 21 17.5	F G	12.9	18	Triangular skeleton tower, white daymark with red vertical stripe. 12.7	Year round. Operates 24 h.
694.5 H3427.1	Laceys Rocks (Cahil Rock) rear range light	45 34 16.5 061 21 24.2 304°46' 176.1 m from front.	Oc G 11s	27.5	18	Triangular skeleton tower, white daymark with red vertical stripe. 12.3	Year round. Operates 24 h. Flash 10 s; eclipse 1 s.
695	<i>Point Tupper light buoy C26</i>	45 36 20.8 061 22 33.1	Fl R 4s	<i>Red, pillar, marked "C26".</i>	<i>Year round.</i>
696 H3430	Point Tupper	Canso. 45 36 27.4 061 22 27.0	F R	29.6	Mast on small shed.	Private aid. Year round.
696.5	<i>Premier Shoal light buoy CL4</i>	45 36 47.3 061 22 10.6	Fl R 4s	<i>Red, spar, marked "CL4".</i>	<i>Year round.</i>

List of Lights, Buoys and Fog Signals – Atlantic Coast

No. ----- Intl No.	Name ----- RACON	Location ----- Latitude N. Longitude W.	Light Characteristics	Focal Height Above Water (m)	Nominal Range (NM)	Description ----- Height of Structure Above Ground Level (m)	Remarks ----- Audible Signals ----- AIS
--------------------------	------------------------	--	--------------------------	--	--------------------------	--	---

NOVA SCOTIA AND CAPE BRETON ISLAND

697 H3434	Cape Porcupine front range light	S. side of Canso Causeway. 45 38 41.9 061 25 05.8	F G	9.9	16	Triangular skeleton tower, white daymark with red vertical stripe. 6.1	Seasonal.
698 H3434.1	Cape Porcupine rear range light	45 38 00.3 061 24 22.7 144°06' 1583.3 m from front.	F G	21.8	18	Triangular skeleton tower, white daymark with red vertical stripe. 13.8	Seasonal.
699	<i>Dixon Rock light buoy C28</i>	45 38 31.3 061 24 11.6	Fl R 4s	<i>Red, pillar, marked "C28".</i>	<i>Year round.</i>
700 H3432	Canso Canal SE.	45 38 46.6 061 24 32.0	Fl Y 4s	4.8	Cylindrical mast.	Private aid. Year round.
700.5 H3432.5	Canso Causeway	45 38 50.8 061 24 45.6	Fl R 4s	16.2	Private aid. Year round. Operates 24 h. Secondary light: F R. Secondary light: F W. Preparing to open bridge. FR - Bridge completely closed. FW - Bridge completely open.
701 H3436	Balache Point front range light	N. end of Canso Lock. 45 38 57.7 061 24 59.4	Oc R 11s	6.0	Square skeleton tower, white daymark with red vertical stripe. 3.5	Seasonal. Operates 24 h. Flash 10 s; eclipse 1 s.
702 H3436.1	Balache Point rear range light	45 38 53.0 061 24 51.8 131°30' 219.8 m from front.	Oc R 11s	13.0	White pyramid tower with red vertical stripe. 7.5	Seasonal. Operates 24 h. Flash 10 s; eclipse 1 s.
703 H3433	Canso Canal NE. mooring berth	45 39 11.3 061 25 12.6	Fl Y 4s	5.5	Cylindrical mast.	Private aid. Year round.
704 H3423	Janvrin Island front range light	At Thomas Head. 45 32 31.3 061 12 01.6	F Y	12.6	15	Triangular skeleton tower, white daymark with red vertical stripe. 9.6	Year round. Operates 24 h. Locator light: Fl W 4s.
704.1 H3423.1	Janvrin Island rear range light	45 32 31.6 061 11 47.8 088°10' 300.2 m from front.	F Y	25.0	15	Triangular skeleton tower, white daymark with red vertical stripe. 15.1	Year round. Operates 24 h. Locator light: Fl W 4s.