

List of Lights, Buoys and Fog Signals – Inland Waters

No. ----- Intl No.	Name ----- RACON	Location ----- Latitude N. Longitude W.	Light Characteristics	Focal Height Above Water (m)	Nominal Range (NM)	Description ----- Height of Structure Above Ground Level (m)	Remarks ----- Audible Signals ----- AIS	
WELLAND CANAL								
Port Weller								
551.06	Port Weller Outer	On outer end of W. breakwater. 43 14 41.2 079 13 02.9	Iso R 4s	15.2	9	Red skeleton tower on white building. 12.3	Seasonal.	
551.07	Port Weller East Breakwater	43 14 41.1 079 12 56.6	Fl G 4s	10.2	5	White tower, green upper portion. 7.2	Seasonal. Flash 1 s; eclipse 3 s.	
551.08	Light buoy WC1	43 14 31.3 079 12 57.2	Fl G 4s	Green, spar, marked "WC1".	Seasonal (in place year round).	
551.09	Light buoy WC2	43 14 31.4 079 13 03.2	Fl R 4s	Red, spar, marked "WC2".	Seasonal (in place year round).	
551.11	Light buoy WC7	43 14 01.7 079 12 57.5	Fl G 4s	Green, spar, marked "WC7".	Seasonal (in place year round).	
551.12	Light buoy WC8	43 14 01.7 079 13 04.4	Fl R 4s	Red, spar, marked "WC8".	Seasonal (in place year round).	
551.13	Welland Canal (Mile 0.7) Downbound Steering	W. pier. 43 13 55.8 079 13 08.7	Iso Y 2s	10.0	Mast, orange triangular daymark. 9.0	Seasonal.	
551.14	Welland Canal (Mile 1.2)	E. side. 43 13 33.1 079 12 56.9	F W	9.0	Mast. 8.0	Seasonal.	
551.16	Port Weller front range light	Welland Canal entrance. 43 13 23.4 079 12 59.6	Iso Y 2s	16.5	Orange and white mast. 9.0	Seasonal.	
551.17	Port Weller rear range light	43 12 54.5 079 12 59.6 180°00' 906.8 m from front.	F R Y G	32.0	Orange and white skeleton tower. 15.0	Seasonal. R 177°30'-179°40'; Y 179°40' -180°20'; G 180°20'-182°30'. Yellow sector indicates preferred channel.
551.18	Light buoy WC9	43 12 33.4 079 12 34.9	Fl G 4s	Green, spar, marked "WC9".	Seasonal (in place year round).	
551.19	Welland Canal (Mile 2.3)	E. side. 43 12 21.6 079 12 28.6	F W	7.0	Mast. 6.0	Seasonal.	
551.21	Light buoy WC11	43 12 01.8 079 12 22.3	Fl G 4s	Green, spar, marked "WC11".	Seasonal (in place year round).	
551.22	Welland Canal (Mile 3.3) Steering	E. side, SE. Lock 2. 43 11 27.3 079 11 54.2	Fl R 4s Iso Y 2s	10.0 10.0	Mast. 9.0	Seasonal.	
551.23	Light buoy WC13	43 11 13.4 079 11 52.3	Fl G 4s	Green, spar, marked "WC13".	Seasonal (in place year round).	
551.24	Light buoy WC17	43 11 00.4 079 11 47.3	Fl G 4s	Green, spar, marked "WC17".	Seasonal (in place year round).	

List of Lights, Buoys and Fog Signals – Inland Waters

No. ----- Intl No.	Name ----- RACON	Location ----- Latitude N. Longitude W.	Light Characteristics	Focal Height Above Water (m)	Nominal Range (NM)	Description ----- Height of Structure Above Ground Level (m)	Remarks ----- Audible Signals ----- AIS	
WELLAND CANAL								
551.26	Light buoy WC19	43 10 47.9 079 11 46.2	Fl G 4s	Green, spar, marked "WC19".	Seasonal (in place year round).	
551.27	Light buoy WC21	43 10 22.3 079 11 42.8	Fl G 4s	Green, spar, marked "WC21".	Seasonal (in place year round).	
551.28	Light buoy WC23	43 10 13.1 079 11 42.5	Fl G 4s	Green, spar, marked "WC23".	Seasonal (in place year round).	
551.29	Welland Canal (Mile 6.2) Downbound Steering	E. side, SE. of bridge 5. 43 08 40.9 079 11 28.9	Iso Y 2s	10.0	Mast, orange triangular daymark.	Seasonal.	
551.31	Welland Canal (Mile 8.1) Industrial N.E.	Industrial dock NE. entry. 43 06 46.0 079 11 36.1	Fl W 4s	4.0	4	Mast.	Seasonal.	
551.32	Welland Canal (Mile 8.1) Industrial W.	Industrial dock NW. entry. 43 06 46.0 079 11 43.6	Fl W 4s	4.0	4	Mast.	Seasonal.	
551.33	Light buoy WC31	43 06 42.1 079 11 49.2	Fl G 4s	Green, spar, marked "WC31".	Seasonal (in place year round).	
551.34	Light buoy WC33	43 06 29.2 079 11 57.2	Fl G 4s	Green, spar, marked "WC33".	Seasonal (in place year round).	
551.36	Welland Canal (Mile 9.2) Downbound Steering	W. side, SW. of bridge 10. 43 05 47.9 079 12 26.2	Iso Y 2s	10.0	Mast, orange triangular daymark.	Seasonal.	
551.37	Welland Canal (Mile 9.5) Upbound Steering	W. side, SW. of bridge 10. 43 05 35.0 079 12 31.0	Iso Y 2s	10.0	Mast.	Seasonal.	
551.38	Welland Canal (Mile 10.9)	E. side, S. of bridge 11. 43 04 01.2 079 12 40.5	Fl W 4s	4.0	4	Mast.	Seasonal.	
551.39	Light buoy WC37	43 03 40.0 079 12 42.3	Fl G 4s	Green, spar, marked "WC37".	Seasonal (in place year round).	
551.41	Light buoy WC39	43 02 12.0 079 12 43.3	Fl G 4s	Green, spar, marked "WC39".	Seasonal (in place year round).	
551.42	Welland Canal (Mile 13.0)	W. side, old channel point. 43 01 58.4 079 12 51.1	F Y	6.0	Mast.	Seasonal (in place year round).
551.43	Light buoy WC40	43 01 58.0 079 12 46.5	Fl R 4s	Red, spar, marked "WC40".	Seasonal (in place year round).	
551.44	Welland Canal (Mile 13.6) Downbound Steering	E. side, S. of Syphon Culvert. 43 01 18.2 079 12 39.7	Iso Y 2s	9.0	Mast, orange triangular daymark.	Seasonal.	

List of Lights, Buoys and Fog Signals – Inland Waters

No. ----- Intl No.	Name ----- RACON	Location ----- Latitude N. Longitude W.	Light Characteristics	Focal Height Above Water (m)	Nominal Range (NM)	Description ----- Height of Structure Above Ground Level (m)	Remarks ----- Audible Signals ----- AIS
WELLAND CANAL							
551.46	Welland Canal (Mile 14.3) Upbound Steering	E. side, S. of Syphon Culvert. 43 00 43.5 079 12 42.7	Iso Y 2s	9.0	Mast, orange triangular daymark.	Seasonal.
551.47	Welland Canal (Mile 15.6) Downbound Steering	E. side, N. of Townline Tunnel. 42 59 25.5 079 12 57.7	Iso Y 2s	9.0	Mast, orange triangular daymark.	Seasonal.
551.48	Welland Canal (Mile 16.2) Upbound Steering	E. side, N. of Townline Tunnel. 42 58 46.6 079 13 09.1	Iso Y 2s	9.0	Mast, orange triangular daymark.	Seasonal.
551.49	Welland Canal (Mile 18.7) Downbound Steering	W. side, S. of Townline Tunnel. 42 56 28.3 079 14 11.8	Iso Y 2s	9.0	Mast, orange triangular daymark.	Seasonal.
551.51	Welland Canal (Mile 19.6) Upbound Steering	W. side, N. of Ramey's Bend. 42 55 35.4 079 14 28.6	Iso Y 2s	9.0	Mast, orange triangular daymark.	Seasonal.
551.52	Light buoy WC42	42 55 33.7 079 14 27.1	Fl R 4s	Red, spar, marked "WC42".	Seasonal (in place year round).
551.53	Welland Canal (Mile 19.8)	W. side, Ramey's Bend at old channel. 42 55 22.7 079 14 32.6	F Y	6.0	Mast. Seasonal.
551.54	Light buoy WC43	42 55 06.9 079 14 28.6	Fl G 4s	Green, spar, marked "WC43".	Seasonal (in place year round).
551.56	Welland Canal (Mile 20.8)	W. side of N. end of Lock 8. 42 54 22.6 079 14 42.1	F Y	6.0	Mast. Seasonal.
551.57	Welland Canal (Mile 21.9)	W. breakwall. 42 53 15.1 079 14 56.5	F W	4.0	Mast. Seasonal.
551.58	Welland Canal (Mile 22.0)	W. breakwall. 42 53 08.4 079 14 56.6	F W	6.0	Mast. Seasonal.
551.59	Port Colborne front range light	Wharf 17. 42 52 40.9 079 14 52.2	F R	10.9	15 White cylindrical tower, orange triangular daymark with black vertical stripe. 7.4	Seasonal.
551.61	Port Colborne rear range light	42 52 55.7 079 14 46.8 015°16' 471.0 m from front.	F R	22.0	15 Skeleton tower, orange daymark with black stripe. 18.8	Seasonal.

List of Lights, Buoys and Fog Signals – Inland Waters

No. ----- Intl No.	Name ----- RACON	Location ----- Latitude N. Longitude W.	Light Characteristics	Focal Height Above Water (m)	Nominal Range (NM)	Description ----- Height of Structure Above Ground Level (m)	Remarks ----- Audible Signals ----- AIS
WELLAND CANAL							
551.62	Welland Canal Mile 22.5 Wharf 17	Extreme S. end of wharf. 42 52 40.0 079 14 52.5	Fl Y 4s	3.0	Mast.	Seasonal.
551.63	Light buoy WC53	42 52 30.1 079 14 55.1	Fl G 4s	Green, spar, marked "WC53".	Seasonal (in place year round).
551.64	Light buoy WC55	42 52 20.4 079 14 57.9	Fl G 4s	Green, spar, marked "WC55".	Seasonal (in place year round).
551.66	Light buoy WC57	42 52 11.2 079 15 00.6	Fl G 4s	Green, spar, marked "WC57".	Seasonal (in place year round).
551.67	Light buoy WC59	42 52 02.1 079 15 03.4	Fl G 4s	Green, spar, marked "WC59".	Seasonal (in place year round).
551.68	Port Colborne Inner	E. end of W. breakwater. 42 52 03.2 079 15 10.3	LFl W 10s	15.5	12	White square tower, red upper portion. 13.1	Seasonal.
551.69	Port Colborne, upbound steering Light and Weather Station	On weather station tower. 42 52 01.7 079 14 54.9	Iso Y 2s	9.8	Tower.	Seasonal. Visible 178°45'-180°45'.
551.71	Port Colborne East Breakwater	On outer end of E. breakwater. 42 51 59.7 079 15 02.1	Fl G 4s	11.3	5	White cylindrical tower with green upper portion. 6.2	Seasonal.
551.72	Port Colborne Outer	On S. end of W. breakwater. 42 51 45.6 079 15 17.4	F R	11.3	7	White square tower, red upper portion. 7.7	Seasonal. Intensified over an arc of 030° SSW.
551.73	Port Colborne light buoy E3	On E. side of entrance. 42 51 42.1 079 15 11.8	Fl G 4s	Green, spar, marked "E3".	Seasonal (in place year round).