

List of Lights, Buoys and Fog Signals – Inland Waters

No. ----- Intl No.	Name ----- RACON	Location ----- Latitude N. Longitude W.	Light Characteristics	Focal Height Above Water (m)	Nominal Range (NM)	Description ----- Height of Structure Above Ground Level (m)	Remarks ----- Audible Signals ----- AIS
DETROIT RIVER							
Hackett Reach							
638.2	Light buoy D24	42 00 45.5 083 08 11.9	Fl R 4s	Red, spar, marked "D24".	Year round.
639	Light buoy D31	42 01 44.8 083 08 19.7	Fl G 4s	Green, spar, marked "D31".	Year round (YRLS).
640	Detroit River Pier D30	42 01 36.0 083 08 06.0	Q R 1s	10.2	White cylindrical tower with red upper portion, marked "D30". 7.0	Seasonal (in place year round).
641	Light buoy D32	42 02 10.0 083 07 58.7	Fl R 4s	Red, pillar, marked "D32".	Seasonal. (Winter spar.)
642	Bar Point Pier D33	42 02 24.1 083 08 03.6	LFl R G 10s	14.0	9	White cylindrical tower, marked "D33". 8.3	Seasonal (in place year round). G 190°-090°; R 090°-190°.
Amherstburg Channel							
643	Light buoy D35	42 02 46.3 083 07 54.9	Q G 1s	Green, spar, marked "D35".	Year round.
644	Light buoy D36	42 02 45.5 083 07 51.2	Q R 1s	Red, pillar, marked "D36".	Seasonal. (Winter spar.)
644.8	Light buoy D37	42 03 14.5 083 07 45.0	Fl G 4s	Green, spar, marked "D37".	Year round.
645	Light buoy D38	42 03 13.9 083 07 41.0	Fl R 4s	Red, pillar, marked "D38".	Seasonal. (Winter spar.)
647.5	Light buoy D45	42 03 44.5 083 07 34.0	Fl G 4s	Green, spar, marked "D45".	Year round.
647.6	Light buoy D46	42 03 44.0 083 07 30.3	Fl R 4s	Red, pillar, marked "D46".	Seasonal. (Winter spar.)
648	Bar Point front range light	On end of dike. 42 04 13.5 083 07 25.5	F Y	10.7	15	Square skeleton tower, orange daymark with black vertical stripe. 8.0	Seasonal (in place year round). Operates 24 h.
649	Bar Point rear range light	42 04 37.3 083 07 17.8 013°27' 762.0 m from front.	F Y	19.5	15	Square skeleton tower, orange daymark with black vertical stripe. 16.9	Seasonal (in place year round). Operates 24 h.
650	Light buoy D50	42 04 12.7 083 07 20.1	Fl R 4s	Red, pillar, marked "D50".	Seasonal. (Winter spar.)
652	Light buoy D52	42 04 42.1 083 07 09.6	Fl R 4s	Red, pillar, marked "D52".	Seasonal. (Winter spar.)
653	Light D53	42 05 12.9 083 07 03.9	Fl G 4s	9.4	4	White cylindrical tower with green upper portion, marked "D53". 7.1	Seasonal (in place year round).

List of Lights, Buoys and Fog Signals – Inland Waters

No. ----- Intl No.	Name ----- RACON	Location ----- Latitude N. Longitude W.	Light Characteristics	Focal Height Above Water (m)	Nominal Range (NM)	Description ----- Height of Structure Above Ground Level (m)	Remarks ----- Audible Signals ----- AIS
DETROIT RIVER							
654	Light buoy D56	42 05 23.3 083 06 54.9	Q R 1s	Red, pillar, marked "D56".	Seasonal. (Winter spar.)
655	Light buoy D57	42 05 28.6 083 06 58.8	Q G 1s	Green, pillar, marked "D57".	Seasonal. (Winter spar.)
656	Hackett Reach front range light	42 05 48.0 083 06 47.9	F R	13.7	14 White cylindrical tower, orange triangular daymark with black vertical stripe. 12.5	Year round. Operates 24 h.
657	Hackett Reach rear range light	42 05 57.5 083 06 45.0 014°55' 303.0 m from front.	F R	24.8	14 White skeleton tower, orange triangular daymark with black vertical stripe. 23.2	Year round. Operates 24 h.
658	Light buoy D59	42 05 49.8 083 07 00.7	Fl G 4s	Green, pillar, marked "D59".	Seasonal. (Winter spar.)
659	Light buoy D60	42 05 49.9 083 06 57.0	Fl R 4s	Red, pillar, marked "D60".	Seasonal. (Winter spar.)
660	Light D61	42 06 01.3 083 07 02.7	Fl G 4s	10.7	4	White cylindrical tower with green upper portion, marked "D61". 7.3	Year round.
661	Light buoy D63	42 06 20.5 083 07 03.8	Q G 1s	Green, pillar, marked "D63".	Seasonal. (Winter spar.)
662	Light buoy D64	42 06 20.0 083 07 00.0	Q R 1s	Red, pillar, marked "D64".	Seasonal. (Winter spar.)
663	Amherstburg Light D65 front range light	On end of dyke. 42 06 47.3 083 07 04.5	F Y	9.2	15 White cylindrical tower with green upper portion, orange triangular daymark with black vertical stripe, marked "D65". 7.8	Seasonal (in place year round). Operates 24 h.
664	Amherstburg Light D65 rear range light	42 06 58.1 083 07 06.0 355°47' 346.9 m from front.	F Y	13.7	15 White skeleton tower, orange triangular daymark with black vertical stripe. 11.9	Seasonal (in place year round). Operates 24 h.
665	Light buoy D67	42 06 51.2 083 07 02.1	Fl G 4s	Green, pillar, marked "D67".	Seasonal. (Winter spar.)
666	Light buoy D68	42 06 51.0 083 06 57.9	Fl R 4s	Red, pillar, marked "D68".	Seasonal. (Winter spar.)
667	Fort Malden front range light	E. side of river. 42 06 51.0 083 06 42.9	F R	15.1	15 Square skeleton tower, orange daymark with black vertical stripe. 8.0	Year round. Operates 24 h.
668	Fort Malden rear range light	42 06 47.2 083 06 41.5 162°30' 116.7 m from front.	F R	24.5	15 White skeleton tower, orange daymark with black vertical stripe. 16.9	Year round. Operates 24 h.

List of Lights, Buoys and Fog Signals – Inland Waters

No. ----- Intl No.	Name ----- RACON	Location ----- Latitude N. Longitude W.	Light Characteristics	Focal Height Above Water (m)	Nominal Range (NM)	Description ----- Height of Structure Above Ground Level (m)	Remarks ----- Audible Signals ----- AIS	
DETROIT RIVER								
669	Light D69	42 07 16.3 083 07 01.6	Q G 1s	8.4	3	White cylindrical tower with green upper portion, marked "D69". 7.4	Seasonal (in place year round).	
Ballards Reef Channel								
670	Light D71	42 07 25.8 083 07 03.5	Fl G 4s	10.1	4	White cylindrical tower with green upper portion, marked "D71". 7.3	Seasonal (in place year round).	
671	Light buoy D72	42 07 29.9 083 06 55.1	Q R 1s	Red, pillar, marked "D72".	Seasonal. (Winter spar.)	
672	Limekiln Crossing front range light	42 07 40.3 083 06 56.5	F R	7.5	15	White skeleton tower, orange triangular daymark with black vertical stripe. 6.6	Seasonal (in place year round). Operates 24 h.
673	Limekiln Crossing rear range light	42 07 52.5 083 06 56.0 002°55' 361.2 m from front.	F R	12.2	15	White cylindrical tower, orange triangular daymark with black vertical stripe. 11.2	Year round. Operates 24 h.
675	Light buoy D74	42 07 49.8 083 07 03.6	Fl R 4s	Red, pillar, marked "D74".	Seasonal. (Winter spar.)	
676	Light buoy D76	42 08 08.1 083 07 11.3	Fl R 4s	Red, pillar, marked "D76".	Seasonal. (Winter spar.)	
677	Livingstone Channel Upper Entrance	On pier at head of channel, near intersection of Ballards Reef and Livingstone channels. 42 08 08.9 083 07 20.8	Fl R 10s Fl W 10s	12.5 13.0	5 5	White cylindrical tower on square block.	Seasonal (in place year round). Flash 1 s; eclipse 9 s.	
678	Light D77	On pier. 42 08 27.7 083 07 28.6	Fl G 5s	11.3	8	White square tower with green trim, marked "D77".	Seasonal (in place year round). Flash 1 s; eclipse 4 s.	
679	Light buoy D78	42 08 27.8 083 07 19.6	Fl R 4s	Red, pillar, marked "D78".	Seasonal. (Winter spar.)	
681	Light buoy DFB	42 09 09.8 083 07 37.5	F(2+1) R 6s	Red-green-red, pillar, marked "DFB".	Seasonal. (Winter spar.)	
Fighting Island Channel								
684.3	Fighting Island North	On pier. 42 14 20.7 083 07 39.6	Iso R 4s	10.6	8	White cylindrical tower with red upper portion. 9.4	Seasonal (in place year round).	
684.5	Fighting Island North light buoy D104	Off N. end of island. 42 15 00.0 083 07 05.5	Fl R 4s	Red, pillar, marked "D104".	Seasonal. (Winter spar.)	

List of Lights, Buoys and Fog Signals – Inland Waters

No. ----- Intl No.	Name ----- RACON	Location ----- Latitude N. Longitude W.	Light Characteristics	Focal Height Above Water (m)	Nominal Range (NM)	Description ----- Height of Structure Above Ground Level (m)	Remarks ----- Audible Signals ----- AIS
DETROIT RIVER							
686	<i>Fighting Island Anchorage Area light buoy DQ</i>	42 15 06.5 083 06 51.4	Fl Y 4s	<i>Yellow, spar, marked "DQ".</i>	<i>Year round.</i>
688	Fighting Island North Anchorage	42 15 41.1 083 06 19.3	Fl Y 4s	9.7	Yellow cylindrical mast, yellow square daymark, black anchor symbol in centre. 7.3	Year round.
688.1	Detroit - Windsor Truck Ferry Terminals South	S. end of terminals. 42 15 45.2 083 06 20.0	F R	5.1	Private aid. Year round.
688.2	Detroit - Windsor Truck Ferry Terminals North	N. end of terminals. 42 15 57.4 083 06 14.2	F R	5.1	Private aid. Year round.
688.5	<i>Light buoy D108</i>	<i>NE. of Ambassador bridge. 42 18 48.3 083 04 04.5</i>	<i>Fl R 4s</i>	<i>.....</i>	<i>.....</i>	<i>Red, pillar, marked "D108".</i>	<i>Seasonal. (Winter spar.)</i>
Livingstone Channel							
689	<i>Light buoy DL1</i>	<i>On W. side of channel. 42 02 33.2 083 08 13.4</i>	<i>Fl G 4s</i>	<i>.....</i>	<i>.....</i>	<i>Green, spar, marked "DL1".</i>	<i>Year round.</i>
690	<i>Light buoy DL5</i>	<i>On W. side of channel. 42 03 25.4 083 08 05.1</i>	<i>Fl G 4s</i>	<i>.....</i>	<i>.....</i>	<i>Green, spar, marked "DL5".</i>	<i>Year round.</i>
691	<i>Light buoy DL6</i>	<i>On E. side of channel. 42 03 27.2 083 07 59.1</i>	<i>Fl R 4s</i>	<i>.....</i>	<i>.....</i>	<i>Red, pillar, marked "DL6".</i>	<i>Seasonal. (Winter spar.)</i>
692	Light DL13	W. side of channel, on pier. 42 04 17.4 083 07 58.8	Fl G 4s	10.0	4	White cylindrical tower with green upper portion, marked "DL13". 7.1	Seasonal (in place year round).
693	Light DL14	E. side of channel, on pier. 42 04 16.9 083 07 51.8	Fl R 4s	10.1	4	White cylindrical tower with red upper portion, marked "DL14". 7.3	Seasonal (in place year round).
694	Light DL15	W. side of channel, on pier. 42 05 08.8 083 07 51.9	Iso G 2s	10.9	4	White cylindrical tower with green upper portion, marked "DL15". 7.0	Seasonal (in place year round).
695	Light DL16	E. side of channel, on pier. 42 05 08.3 083 07 45.1	Iso R 2s	11.3	4	White cylindrical tower with red upper portion, marked "DL16". 7.3	Seasonal (in place year round).
696	Light DL17	W. side of channel, on pier. 42 05 58.3 083 07 45.4	Fl G 4s	11.6	White cylindrical tower with green upper portion, marked "DL17". 7.3	Seasonal (in place year round).

List of Lights, Buoys and Fog Signals – Inland Waters

No. ----- Intl No.	Name ----- RACON	Location ----- Latitude N. Longitude W.	Light Characteristics	Focal Height Above Water (m)	Nominal Range (NM)	Description ----- Height of Structure Above Ground Level (m)	Remarks ----- Audible Signals ----- AIS
--------------------------	------------------------	--	--------------------------	--	--------------------------	--	---

DETROIT RIVER

697	Light DL18	E. side of channel, on pier. 42 05 57.8 083 07 38.3	Fl R 4s	11.3	4	White cylindrical tower with red upper portion, marked "DL18". 7.3	Seasonal (in place year round).
699	Light DL20	E. side of channel, on pier. 42 06 25.5 083 07 34.7	Iso R 2s	11.5	4	White cylindrical tower with red upper portion, marked "DL20". 7.3	Seasonal (in place year round).
701	Light DL22	E. side of channel, on pier. 42 06 49.6 083 07 31.6	Fl R 4s	11.6	4	White cylindrical tower with red upper portion, marked "DL22". 7.3	Seasonal (in place year round).

Fleming Channel

705.4	Light buoy D110	42 20 31.7 082 57 05.9	Fl R 4s	Red, pillar, marked "D110".	Seasonal. (Winter spar.)
705.6	Light buoy DPB	W. of W. end of island. 42 20 44.2 082 56 49.7	Fl(2+1) R 6s	Red-green-red, pillar, marked "DPB".	Seasonal. (Winter spar.)

Pecche Island Channel

706.9	Pecche Island Channel light buoy DP2	SW. of island. 42 20 39.1 082 56 37.9	Fl R 4s	Red, pillar, marked "DP2".	Seasonal. (Winter spar.)
707	Light buoy DP5	S. of Pecche Island. 42 20 30.0 082 55 15.7	Fl G 4s	Green, pillar, marked "DP5".	Seasonal. (Winter spar.)
707.2	Little River Breakwater	42 20 26.7 082 55 52.1	F R	7.7	Black square mast.	Private aid. Seasonal.
707.3	Little River Entrance	42 20 26.6 082 55 50.5	F G	5.9	Square mast.	Private aid. Seasonal.
707.4	Lakeview Park Marina	42 20 24.0 082 55 39.9	F W	5.2	Cylindrical mast.	Private aid. Seasonal.
707.5	Pecche Island East light buoy DP7	42 20 50.1 082 54 24.5	Fl G 4s	Green, pillar, marked "DP7".	Seasonal. (Winter spar.)