

## List of Lights, Buoys and Fog Signals – Pacific Coast

No. ----- Intl No.	Name ----- RACON	Location ----- Latitude N. Longitude W.	Light Characteristics	Focal Height Above Water (m)	Nominal Range (NM)	Description ----- Height of Structure Above Ground Level (m)	Remarks ----- Audible Signals ----- AIS	
<b>UPPER AND LOWER ARROW LAKE - COLUMBIA RIVER</b>								
26	Syringa Creek	W. shore. 49 20 16.3 117 52 37.2	FI G 4s	11.8	4	Pipe tower, green, white and black square daymark. 1.9	Year round.	
26.5	Tulip Point	SE. of Tulip Creek, N. shore. 49 21 31.9 117 55 23.0	FI R 4s	18.2	4	Pipe tower. 1.9	Year round.	
27	Cayuse Creek	W. shore. 49 23 32.4 118 01 02.3	FI G 4s	10.5	4	Pipe tower, green, white and black square daymark. 2.0	Year round.	
27.2	Renata South	E. shore. 49 26 08.0 118 04 44.9	FI R 4s	12.3	4	White square tower with red band at top. 8.1	Year round.	
27.3	Renata North	E. shore. 49 26 58.3 118 05 22.4	Q R 1s	9.8	4	Pipe tower, red and white triangular daymark. 2.0	Year round.	
27.5	Bowman Creek	W. shore. 49 31 34.5 118 08 43.0	FI G 4s	11.2	4	Pipe tower, green, white and black square daymark. 2.1	Year round.	
28	Snag Bay	W. shore. 49 36 31.2 118 09 28.3	Q G 1s	11.2	4	Pipe tower, green, white and black square daymark. 2.1	Year round.	
28.5	Johnston Creek East	E. shore. 49 41 31.3 118 07 42.2	FI R 4s	9.1	4	Pipe tower, red and white triangular daymark. 2.0	Year round.	
29	Edgewood East	E. shore. 49 45 59.9 118 06 39.2	Q R 1s	10.0	4	Pipe tower, red and white triangular daymark. 2.1	Year round.	
29.5	Needles Sector Light	W. side of channel at Andres Creek. 49 53 50.8 118 05 04.5	F W G	R .....	11.7	7	Mast, red slatwork daymark with white vertical stripe. 3.5	Year round. R 003°30'-009°15'; W 009°15'-010°15'; G 010°15'-017°30'.
30	Upper Whatshan Sector Light	W. side of channel, S. of power station. 49 54 00.0 118 04 41.8	F W G	R .....	13.7	8	Mast, red slatwork daymark with white vertical stripe. 3.5	Year round. G 220°15'-225°45'; W 225°45'-230°15'; R 230°15'-236°30'.
31	Whatshan Sector Light downstream	W. side of channel, N. of power station. 49 55 22.8 118 03 15.7	F W G	R .....	10.1	7	Mast, red slatwork daymark with white vertical stripe. 3.5	Year round. R 010°45'-016°30'; W 016°30'-021°30'; G 021°30'-027°30'.
31.5	Fern Creek	W. shore, near creek. 49 57 33.7 118 00 46.3	FI G 4s	13.0	4	Square skeleton tower, green, white and black square daymark. 3.5	Year round.	
32.7	Burton Approach	W. shore, opposite shoals off Caribou Creek. 49 58 46.8 117 55 18.9	Q G 1s	12.4	4	Square skeleton tower, green, white and black square daymark. 3.7	Year round.	

## List of Lights, Buoys and Fog Signals – Pacific Coast

No. ----- Intl No.	Name ----- RACON	Location ----- Latitude N. Longitude W.	Light Characteristics	Focal Height Above Water (m)	Nominal Range (NM)	Description ----- Height of Structure Above Ground Level (m)	Remarks ----- Audible Signals ----- AIS
<b>UPPER AND LOWER ARROW LAKE - COLUMBIA RIVER</b>							
33	Burton West	W. side of channel. 49 59 27.2 117 54 24.1	Fl W R	4s	16.0	4	Square skeleton tower, white rectangular daymark. Year round. R 178°-180°18'; W 180°18'-24°27'.
33.5	Sand Island light buoy A18	E. side of channel marking sand bar. 50 02 02.4 117 54 42.0	Fl R	4s	.....	.....	Red, pillar, marked "A18". Year round.
34	Alwen Creek	W. side of channel. 50 05 02.4 117 56 18.6	Fl G	4s	21.7	4	Mast, green, white and black square daymark. 3.6 Year round.
34.5	Arrow Park	W. shore, W. side of cable ferry track. 50 06 36.8 117 54 04.5	Q G	1s	10.0	4	Square skeleton tower, green, white and black square daymark. Year round.
37	Dispatch Island Sector Light	50 07 57.9 117 48 36.1	F R W G	.....	13.0	5	Mast, red slatwork daymark with white vertical stripe and red and white triangular daymark. Year round. G 165°35'-174°35'; W 174°35'-175°35'; R 175°35'-183°35'. Secondary light: Fl R 4s.
38.5	Smith Point	W. shore. 50 12 38.3 117 49 34.3	Fl G	4s	9.6	4	Pipe tower, green, white and black square daymark. 2.0 Year round.
39	Nakusp light buoy A26	50 14 09.7 117 49 29.8	Fl R	4s	.....	.....	Red, pillar, marked "A26". Year round.
39.5	Cape Horn	W. shore, N. of Fosthall Point. 50 21 06.6 117 55 38.6	Fl W	4s	9.5	6	Pipe tower on 3-pile dolphin. Year round.
40	Ann Point	E. shore. 50 28 02.2 117 54 56.5	Fl R	4s	10.3	4	Pipe tower, red and white triangular daymark. 1.9 Year round.
40.5	Albert Point	E. shore. 50 35 29.0 117 54 43.6	Q R	1s	10.6	4	Pipe tower, red and white triangular daymark. 2.0 Year round.
40.6	Bannock Point	E. of Shelter Bay, W. shore. 50 37 54.9 117 55 15.7	Fl G	4s	11.7	4	Pipe tower, green, white and black square daymark. 2.0 Year round.
40.7	Arrowhead light buoy A29	N. end of channel. 50 40 22.4 117 54 31.0	Fl G	4s	.....	.....	Green, pillar, marked "A29". Year round.
41	Whiskey Point	N. shore, Beaton Arm. 50 42 21.4 117 49 21.6	Fl G	4s	9.6	4	Pipe tower, green, white and black square daymark. 2.0 Year round.