

List of Lights, Buoys and Fog Signals – Pacific Coast

No. ----- Intl No.	Name ----- RACON	Location ----- Latitude N. Longitude W.	Light Characteristics	Focal Height Above Water (m)	Nominal Range (NM)	Description ----- Height of Structure Above Ground Level (m)	Remarks ----- Audible Signals ----- AIS
VANCOUVER HARBOUR							
385.3	English Bay Entrance ODAS light buoy 46304	49 18 06.0 123 21 19.9	Fl(5) Y 20s	Yellow, ODAS, marked "46304".	Year round.
385.5	Vancouver Approach Cautionary light buoy QA Racon G (- -) X Band	W. of Point Grey, traffic separation zone. 49 16 31.6 123 19 13.8	Fl Y 4s	Yellow, pillar, marked "QA".	Year round.
386 G5426	Point Atkinson	N. point of entrance to Burrard Inlet. 49 19 49.4 123 15 52.9	Fl(2) W 5s	32.9	15	White hexagonal tower with red top.	Year round. Flash 0.25 s; eclipse 0.75 s; flash 0.25 s; eclipse 3.75 s.
386.3 G5426.8	Spanish Bank No. 2	Entrance to English Bay. 49 17 21.1 123 14 51.9	Fl(2) R 6s	6.7	5	White cylindrical tower with red band at top.	Year round. Flash 0.5 s; eclipse 1 s; flash 0.5 s; eclipse 4 s.
387	Point Grey light and bell buoy Q62	N. of point, entrance to harbour. 49 17 20.4 123 15 58.8	Q R 1s	Red, pillar, marked "Q62".	Year round. Audible signal: Bell
387.01 G5426.6	Spanish Bank	49 17 12.9 123 13 34.8	Fl W 4s	6.9	6	White cylindrical tower with red band at top on 9-pile dolphin.	Year round.
387.2 G5427.2	English Bay Anchorage East	Seaward end of breakwater. 49 16 31.8 123 11 18.1	Q Y 1s	4.9	8	Mast on rail.	Private aid. Year round.
388	Burrard Inlet Cautionary light buoy QB Racon K (- -) X & S Bands	E. end of Traffic Lane Separator. 49 19 17.4 123 12 06.8	Fl Y 4s	Yellow, pillar, marked "QB".	Year round.
388.1	Kitsilano light buoy Q52	Entrance to False Creek, English Bay. 49 16 53.3 123 08 58.7	Q R 1s	Red, pillar, marked "Q52".	Year round.
388.6	English Bay Beach light buoy Q41	Entrance to False Creek, English Bay. 49 17 06.7 123 08 55.5	Q G 1s	Green, pillar, marked "Q41".	Year round.
389 G5429.8	Kitsilano Base	SW. approach to False Creek at end of floating breakwater. 49 16 33.8 123 08 17.5	Fl R 4s	4.3	3	On 1-pile dolphin.	Year round.
390 G5430	False Creek Sector Light	On N. pier of Burrard Bridge. 49 16 32.7 123 08 10.7	F R W G	5.7	11 Mast.	Year round. Operates 24 h. R 128°-131°; W 131°-132°; G 132°-135°.

List of Lights, Buoys and Fog Signals – Pacific Coast

No. ----- Intl No.	Name ----- RACON	Location ----- Latitude N. Longitude W.	Light Characteristics	Focal Height Above Water (m)	Nominal Range (NM)	Description ----- Height of Structure Above Ground Level (m)	Remarks ----- Audible Signals ----- AIS	
VANCOUVER HARBOUR								
390.5	Ferguson Point West Cardinal light buoy QC	W. of point, N. end of English Bay. 49 18 12.4 123 10 00.7	Q(9) W 15s	Yellow-black-yellow, pillar, marked "QC".	Year round.	
391	Burrard Inlet Cautionary light buoy QD	N. boundary of Traffic Lane. 49 19 22.1 123 09 31.9	Fl Y 4s	Yellow, pillar, marked "QD".	Year round.	
392 G5434	Prospect Point	Under bluff at point. 49 18 50.4 123 08 29.1	Iso R 2s	11.5	10	White tower with red band at top.	Year round. Operates 24 h.	
392.6	Lions Gate Bridge Inbound Sector Light	Centre span, W. side. 49 18 55.4 123 08 19.4	F R W G	63.5	4	On bridge.	Year round. Operates 24 h. R 107°-108°; AI RW 108°-109°; W 109°-113°; AI GW 113°-114°; G 114°-116°.
392.7	Lions Gate Bridge Southwest Inbound Bridge Wing	S. span, W. side. 49 18 53.4 123 08 21.2	Iso Y 1s	61.5	2	On bridge.	Year round. Operates 24 h.	
392.8	Lions Gate Bridge Northwest Inbound Bridge Wing	N. span, W. side. 49 18 57.4 123 08 17.6	Iso Y 1s	61.4	2	On bridge.	Year round. Operates 24 h.	
393.5	Lions Gate Bridge Outbound Sector Light	Centre span, E. side. 49 18 55.1 123 08 18.7	F R W G	63.7	4	On bridge.	Year round. Operates 24 h. G 300°-302°; AI GW 302°-303°; W 303°-307°; AI RW 307°-308°; R 308°-310°.
393.6	Lions Gate Bridge Southeast Outbound Bridge Wing	S. span, E. side. 49 18 53.2 123 08 20.5	Iso Y 1s	61.6	2	On bridge.	Year round. Operates 24 h.	
393.7	Lions Gate Bridge Northeast Outbound Bridge Wing	N. span, E. side. 49 18 57.1 123 08 16.9	Iso Y 1s	61.4	2	On bridge.	Year round. Operates 24 h.	
394 G5435	First Narrows	Entrance to narrows. 49 19 09.1 123 08 46.7	Iso G 2s	7.5	7	White cylindrical tower with green band at top on 4-pile dolphin.	Year round. Radar reflector.	
395 G5442	Calamity Point	49 18 45.2 123 07 39.6	Fl W 4s	5.1	9	White cylindrical tower with green band at top on 16- pile dolphin.	Year round. Radar reflector.	
395.3	Calamity Shoal light buoy Q65	S. of point. 49 18 40.4 123 07 36.7	Fl G 4s	Green, pillar, marked "Q65".	Year round.	
403 G5448	Burnaby Shoal	On shoal. 49 17 54.4 123 06 38.4	Q R 1s	9.8	10	White cylindrical tower with red band at top.	Year round.	

List of Lights, Buoys and Fog Signals – Pacific Coast

No. ----- Intl No.	Name ----- RACON	Location ----- Latitude N. Longitude W.	Light Characteristics	Focal Height Above Water (m)	Nominal Range (NM)	Description ----- Height of Structure Above Ground Level (m)	Remarks ----- Audible Signals ----- AIS
VANCOUVER HARBOUR							
403.5 G5455	Deadman Island	S. of island. 49 17 33.6 123 07 23.9	Q R 1s	6.7	4	White cylindrical tower with red band at top on 3-pile dolphin. 4.6	Year round. Radar reflector.
404 G5456	Coal Harbour	49 17 36.5 123 07 32.7	Fl R 4s	6.7	4	White cylindrical tower with red band at top on 9-pile dolphin.	Year round. Radar reflector.
408.5 G5465	Terminal Dock East	49 17 38.3 123 03 02.8	Fl R 4s	2.4	7	Mast on pilings.	Year round.
408.51 G5465.5	Second Narrows West Directional	49 17 37.4 123 02 45.6	F R	8.3	10	White square tower on 3-pile dolphin.	Year round. Operates 24 h. Visible on a bearing of 266°.
408.53 G5468.33	Second Narrows Highway Bridge (Southeast)	On bridge. 49 17 39.3 123 01 33.8	F W	60.3	On bridge.	Year round. Visible from E. approach.
408.54 G5468.32	Second Narrows Highway Bridge (Southwest)	On bridge. 49 17 39.3 123 01 35.1	F W	60.3	On bridge.	Year round. Visible from W. approach.
408.55 G5468.31	Second Narrows Highway Bridge East	On bridge. 49 17 40.9 123 01 34.1	F W	On bridge.	Year round. Center light located on bottom of span. Floodlight pointed down. Visible from E. approach.
408.6 G5468	Second Narrows Highway Bridge West	On bridge, bottom of span. 49 17 40.9 123 01 34.9	F W	45.2	On bridge.	Year round. Indicates centre of navigation channel as visible from W. approach. Center light located on bottom of span. Floodlight pointed down.
408.7 G5468.3	Second Narrows Highway Bridge (Northeast)	On bridge, NE. at road level. 49 17 42.5 123 01 33.9	F W	60.3	On bridge.	Year round. Visible from E. approach.
408.8 G5468.2	Second Narrows Highway Bridge (Northwest)	W. side of bridge. 49 17 42.5 123 01 35.2	F W	60.3	On bridge.	Year round. Visible from W. approach.
409 G5469	CN Railway Bridge Northeast	On bridge abutment. 49 17 43.3 123 01 27.6	F G	4.9	5	On bridge.	Year round. Visible from E. approach.
409.1 G5469.2	CN Railway Bridge Southeast	On bridge abutment. 49 17 38.6 123 01 27.8	F R	4.9	4	On bridge.	Year round. Visible from E. approach.
409.2 G5469.3	CN Railway Bridge Southwest	On bridge abutment. 49 17 38.6 123 01 28.7	F R	4.9	4	On bridge.	Year round. Visible from W. approach.

List of Lights, Buoys and Fog Signals – Pacific Coast

No. ----- Intl No.	Name ----- RACON	Location ----- Latitude N. Longitude W.	Light Characteristics	Focal Height Above Water (m)	Nominal Range (NM)	Description ----- Height of Structure Above Ground Level (m)	Remarks ----- Audible Signals ----- AIS
VANCOUVER HARBOUR							
409.3 G5469.4	CN Railway Bridge Northwest	On bridge abutment. 49 17 43.3 123 01 28.6	F G	4.9	5	On bridge.	Year round. Visible from W. approach.
409.35 G5469.9	CN Railway Bridge Sector Light	Second Narrows rail bridge. 49 17 40.9 123 01 27.9	F R	10	On bridge.	Year round. Operates 24 h. G 263°-264°; AI GW 264°-265°; W 265°-267°; AI RW 267°-268°; R 268°-270°.
409.4 G5469.6	CN Railway Bridge Centre Span Northeast	On bridge. 49 17 41.0 123 01 27.9	F R	On bridge.	Private aid. Year round. Visible from E. approach. Characteristics of light: Fixed or flashing (Occasional).
409.5 G5469.8	CN Railway Bridge Centre Span Northwest	On bridge. 49 17 41.1 123 01 28.5	F R	On bridge.	Private aid. Year round. Visible from W. approach. Secondary light: Q R 1s. Characteristics of light: Fixed or flashing (Occasional).
409.6 G5470	CN Railway Bridge Centre Span East	On bridge. 49 17 40.9 123 01 27.9	F G	On bridge.	Private aid. Year round. Visible from E. approach. Indicates that span is raised. Characteristics of light: Fixed or flashing (Occasional).
409.7 G5470.2	CN Railway Bridge Centre Span West	On bridge. 49 17 41.0 123 01 28.5	F G	On bridge.	Private aid. Year round. Visible from W. approach. Indicates that span is raised. Characteristics of light: Fixed or flashing (Occasional).
409.8 G5470.4	CN Railway Bridge Centre Span Southeast	On bridge. 49 17 40.8 123 01 28.9	Q R 1s	On bridge.	Private aid. Year round. Visible from E. approach. Characteristics of light: Fixed or flashing (Occasional).
409.9 G5470.6	CN Railway Bridge Centre Span Southwest	On bridge. 49 17 40.8 123 01 28.5	Q R 1s	On bridge.	Private aid. Year round. Visible from W. approach. Characteristics of light: Fixed or flashing (Occasional).
409.95 G5471.3	Riverside East	49 17 45.5 123 01 04.6	Fl G 4s	8.3	7	White square skeleton tower with green band at top on 6-pile dolphin.	Year round.
410 G5473	Second Narrows	E. of railway bridge. 49 17 46.4 123 00 36.0	Q G 1s	8.1	6	White square skeleton tower with green band at top on 3-pile dolphin.	Year round.
410.5 G5473.4	Second Narrows East	NW. of Berry Point. 49 17 56.1 122 59 47.7	Fl G 4s	3.3	7	On centre pile of 19-pile dolphin.	Year round. Radar reflector.

List of Lights, Buoys and Fog Signals – Pacific Coast

No. ----- Intl No.	Name ----- RACON	Location ----- Latitude N. Longitude W.	Light Characteristics	Focal Height Above Water (m)	Nominal Range (NM)	Description ----- Height of Structure Above Ground Level (m)	Remarks ----- Audible Signals ----- AIS
VANCOUVER HARBOUR							
410.7	Berry Point front range light	On N. extremity of point. 49 17 45.2 122 59 24.9	F Y	11		Square skeleton tower, white daymark with red vertical stripe.	Private aid. Year round. Operates 24 h. Radar reflector.
410.8	Berry Point rear range light	49 17 45.7 122 59 10.0 087°05' 300.0 m from front.	F Y	12		Square skeleton tower, white daymark with red vertical stripe.	Private aid. Year round. Operates 24 h. Radar reflector.
411 G5474	Berry Point	On N. extremity of point. 49 17 43.1 122 59 13.1	Fl R 4s 9.0	8		Triangular skeleton tower on 9-pile dolphin.	Year round.
411.2	Berry Point 1	On N. extremity of point, attached to front range tower. 49 17 45.2 122 59 24.9		Square skeleton tower.	Private aid. Year round. Obscured 083°-091°. Secondary light: Fl R 4s.
411.3	Berry Point 1A	On N. extremity of point, attached to rear range tower. 49 17 45.7 122 59 10.0	Fl R 4s 4.0	7		Square skeleton tower.	Private aid. Year round. Obscured 083°-091°.
411.4	Berry Point Sector Light	On N. extremity of point, attached to rear range tower. 49 17 45.7 122 59 10.0	F R W G	9		Square skeleton tower.	Private aid. Year round. R 086.10°-086.60°; AI RW 086.60°-086.90°; W 086.90°-087.20°; AI GW 087.20°-087.50°; G 087.50° to 088.00°. Radar reflector.
412 G5476	Roche Point	On S. extremity of point. 49 18 00.5 122 57 22.0	Fl W 4s 7.5	7		White cylindrical tower on 3-pile dolphin.	Year round.
412.3 G5481	Woodlands	N. side of Indian Arm. 49 20 28.2 122 55 10.1	Fl G 4s 4.2	4		White cylindrical tower with green band at top.	Year round. Radar reflector.
412.4 G5481.2	Twin Islands	49 21 03.3 122 53 26.4	Fl R 4s 8.9	5		White cylindrical tower with red band at top.	Year round. Radar reflector.
412.5 G5481.4	Best Point	On the point. 49 22 51.0 122 52 46.3	Fl W 4s 5.8	5		White cylindrical tower.	Year round. Radar reflector.
412.6 G5482	Croker Island South	49 25 49.2 122 51 47.3	Fl(2) W 6s 5.5	5		White cylindrical tower.	Year round. Flash 0.5 s; eclipse 1 s; flash 0.5 s; eclipse 4 s. Radar reflector.
413 G5477	Gosse Point	Off S. shore. 49 17 32.8 122 55 30.5	Fl R 4s 8.6	5		White cylindrical tower with red band at top on 7-pile dolphin.	Year round. Radar reflector.

List of Lights, Buoys and Fog Signals – Pacific Coast

No. ----- Intl No.	Name ----- RACON	Location ----- Latitude N. Longitude W.	Light Characteristics	Focal Height Above Water (m)	Nominal Range (NM)	Description ----- Height of Structure Above Ground Level (m)	Remarks ----- Audible Signals ----- AIS
--------------------------	------------------------	--	--------------------------	--	--------------------------	--	---

VANCOUVER HARBOUR

414 G5478	Burns Point	On point, N. side of entrance to Port Moody. 49 17 35.7 122 55 03.9	Fl W 4s	4.6	7	White cylindrical tower with green band at top.	Year round. Radar reflector.
415 G5479	Carraholly Point	On rock off point. 49 17 36.7 122 54 30.7	Fl G 4s	4.8	5	White cylindrical tower with green band at top.	Year round.
415.1 G5479.2	Carraholly front range light	Port Moody. 49 17 43.5 122 53 56.6	F Y	7.5	10	Square skeleton tower on 4-pile dolphin, white daymark with red vertical stripe.	Year round. Operates 24 h.
415.2 G5479.21	Carraholly rear range light	49 17 44.4 122 54 07.3 277°05' 218.0 m from front.	F Y	14.8	10	Square skeleton tower on 4-pile dolphin, white daymark with red vertical stripe.	Year round. Operates 24 h.
416 G5480	Reed Point	S. shore of Port Moody Arm, Burrard Inlet. 49 17 31.8 122 52 25.5	Q R 1s	9.9	3	White square tower with red band at top on 3-pile dolphin.	Year round.
416.5 G5480.4	Port Moody	Entrance to dredged area at Rocky Point. 49 17 04.4 122 51 07.6	Fl R 4s	2.9	2	3-pile dolphin, red, white and red triangular daymark.	Year round.